Influence of Geant4 Physics List on Simulation Accuracy and Performance

Róbert Breier¹, Alexander Fuss^{2, 3}, Holger Kluck², Valentyna Mokina², Veronika Palušová^{4*}, Pavel Povinec¹

 Department of Nuclear Physics and Biophysics, Faculty of Mathematics, Physics and Informatics, Comenius University, 84248 Bratislava, Slovakia
Institut für Hochenergiephysik der Österreichischen Akademie der Wissenschaften, Wien, 1050, Austria
Atominstitut, Technische Universität Wien, Wien, 1020, Austria
Institute of Experimental and Applied Physics, Czech Technical University in Prague, Prague, CZ-11000, Czech Republic
* veronika.palusova@cvut.cz

December 5, 2022



14th International Conference on Identification of Dark Matter Vienna, Austria, 18-22 July 2022 doi:10.21468/SciPostPhysProc.?

Abstract

A main goal of current low background physics is the search for rare and novel phenomena beyond the Standard Model of particle physics, e.g. the scattering off of a potential Dark Matter particle inside a $CaWO_4$ crystal or the neutrinoless double beta decay of Ge nucleus. The success of such searches depends on a reliable background prediction via Monte Carlo simulations. A widely used toolkit to construct these simulations is GEANT4, which offers a wide choice of physics models, so-called physics lists. To facilitate the selection of physics lists for simulations of $CaWO_4$ and Ge targets, we quantify their impact on the total energy deposition for several test cases.

1 Introduction

Rare event searches, such as the search for dark matter or neutrinoless double beta decay, depend crucially on a reliable and verified background prediction. Commonly, these predictions are based on Monte Carlo simulations of the relevant background sources. A widely used toolkit to create these simulations is GEANT4 [1–3].

In GEANT4, the physics models that describe the particle processes are specified in the so called *physics list*. Albeit the user is generally free to specify their own collection of models, GEANT4 provides with *physics constructors* predefined collections of processes to cover related particle processes that can be included in the physics list. In this work we will focus on the *electromagnetic* physics constructors.

In literature, the electromagnetic physics constructors and their settings are validated for a wide range of physics processes and observables, e.g. electron back scattering [4]. However,

to our knowledge, no such study exist about their impact on the total energy deposited by radioactive decays in $CaWO_4$ or Ge target material. As pointed out in [4], an observable like energy deposition by radioactive decays is the result of several physics processes. Hence, it can only be assessed for a specific use case, and it is usually precarious to extrapolate it from studies based on a different use case.

With this work we provide first results of a dedicated study for this missing use case: examine the impact of different electromagnetic physics constructors on the total energy deposition for several test cases, i.e. combinations of radioactive contaminants, target material (CaWO₄ and Ge) and target thickness. The goal is to give an assessment to what extent the selected physics constructors affect the simulated observable of total energy deposition, i.e. how compatible different physics constructors are. To assess the compatibility in a qualitative and objective way, we adopt the methodology established in [4–7]. To give some guidance which physics constructor to choose in case of compatibility, we consider also the computing performance.

2 Methodology

The strategy of this study is focused on the simulation of total energy deposition in a bulk crystal of two target materials, i.e. CaWO₄ and Ge. Simulations were produced with the ImpCRESST physics simulation code [8] based on GEANT4 version 10.6.3 released in 2020. *Test cases*, characterized by target material, target thickness and radioactive contaminant, are simulated for several GEANT4 physics constructor. The impact of different physics constructors on the total energy deposition in our test cases is assessed by the means of statistical methods.

2.1 Physics Constructor Configurations

GEANT4 provides several predefined physics constructors for electromagnetic (EM) physics. Twelve of them were used during this work: G4EmStandardPhysics_option1, 2, 3 and 4, G4EmLivermorePhysics, G4EmLivermorePolarizedPhysics, G4EmPenelopePhysics, G4EmStandardPhysics, G4EmStandardPhysicsWVI, and G4Em-StandarPhysicsSS.

We treat each physics constructor as its own one parametric-model with the range cut for secondary particle production as a free parameter. In a GEANT4 simulation, secondary particles that are unable to travel further than the range cut value, called *production cut*, are not produced, but their energy is deposited locally [9, p.256]. In order to study the impact of such parameter and to possibly improve the performance of simulations, each simulation was performed for five production cut values: 100 nm, 1 µm, 1 mm, 1 cm , 10 cm. In this work, one GEANT4 physics constructor *configuration* is characterized by physics constructor and cut value, yielding together 60 configurations (=12 physics constructors × 5 production cut values).

2.2 Test Cases

This study covers two target materials - CaWO₄ or Ge. The target geometry was defined as a cuboid with a cross section of 32×32 mm in two configurations: *bulky* with a thickness of 32 mm and *thin* with a thickness of $50 \text{ }\mu\text{m}^1$. Six common radioactive contaminants in chosen

¹Here, the thicknesses are motivated by the largest and smallest distinct parts in some CRESST detector module [8] (the absorber crystal and a bond wire respectively) to demonstrate extreme cases for the dimensions. However, the target thickness is an experiment specific value and future studies may cover a wider range of thicknesses and target materials, e.g. Si.

targets are considered - low Q-value β emitters (²²⁸Ra, ²¹⁰Pb), high Q-value β emitters (²⁰⁸Tl, ²¹⁰Tl) and α emitters (²¹¹Bi, ²³⁴U).

Each one of the 24 test cases (= 2 targets × 2 thicknesses × 6 contaminants) is simulated for each configuration, yielding together 1440 datasets (= 24 test cases × 60 configurations). As G4EmStandardPhysics_option4 is regarded the most accurate model² we chose it together with a 1 mm cut as reference dataset.

2.3 Statistical Analysis

Quantitative comparisons between simulated test case and reference datasets are determined by statistical tests and performed in two steps. In the first step, we address the question of how well a simulated dataset distribution is described by the distribution of the reference dataset by appropriate goodness-of-fit tests. The second step is based on categorical tests, which determine if the difference in compatibility observed across our GEANT4 configurations is statistically significant. This statistical significance is evaluated in two cases: for simulations using *different* physics constructors, which produce unpaired samples, and for simulations using the *same* physics constructor but differ in a secondary feature, i.e. in production cut, which are related and produce paired samples.

As the statistical tests are not uniformly sensitive to differences in distributions at all values, a variety of statistical tests is applied in each step of analysis to minimize the possibility of introducing systematic effects in validation of results. Three independent goodness-of-fit tests were performed to test compatibility: Anderson-Darling (AD) [10], Kolmogorov-Smirnov (KS) [11, 12] and χ^2 test [13, 14]. The tests used to compare groups of categorical data for a significant difference are χ^2 test of independence and Fisher's exact test [15] for unpaired data, and McNemar's test [16] for paired data. In each test, the significance level α was chosen at 5%, a conventional value.

3 Results

We show first results of step one of the statistical analysis, i.e. comparing the relative compatibility of energy deposition of several test cases with the reference configuration. Figure 1 shows the example of energy deposition per single event of ²¹⁰Tl decay in CaWO₄ for G4EmStandardPhysics_option1 and two cut values compared with the reference configuration. The outcome of χ^2 goodness-of-fit tests is reported in the form of efficiency, which is defined as the fraction of test cases where the p-value resulting from the χ^2 tests is larger than α . This quantifies the capability of a configuration to produce statistically consistent results with the reference configuration. Results of the efficiency for GEANT4 physics constructors are shown in Figure 2.

The analysis identifies G4EmLivermore as a constructor that is robust against changes of the production cut. Hence, tuning of the production cut may improve the performance of simulations without affecting its outcome. Analysis with AD and KS goodness-of-fit tests, and categorical analysis based on the results of compatibility, are currently conducted.

Besides maximizing the accuracy of simulations, one also wants to optimize the computational performance in terms of CPU time. Figure 3 shows the fraction of average run time of GEANT4 configurations relative to the reference dataset. The decreased performance of single scattering models (G4EmStandardWVI and G4EmStandardSS) is expected. Except for the 100 nm case, most values for the production cut affect the relative performance by $\mathcal{O}(10\%)$.

²See [9, p.215]: "G4EmStandardPhysics_option4, containing the most accurate models from the Standard and Low Energy Electromagnetic physics working groups."



Figure 1: Energy deposition per single event in thin $CaWO_4$ target for 2 configurations. Left - example of failed test of compatibility, right - example of passed test of compatibility.



Figure 2: Efficiency of GEANT4 physics constructors (left) and physics constructor configurations (right) based on the results of χ^2 goodness-of-fit test.



Figure 3: Average run time of GEANT4 physics constructor configurations relative to the reference configuration.

4 Conclusion

With this study, we aim to determine the compatibility between total energy deposition of different GEANT4 EM physics constructors compared to the most accurate one, G4EmStandardPhysics_option4. Besides the effects due to the physics constructor, this study also evaluates the sensitivity to features such as the production range cut value. Compared to G4EmStandardPhysics-_option4, we found that G4EmLivermore is more efficient in terms of χ^2 -GoF test and its outcome less dependent on the production cut value. All configurations of physics constructors feature similar computation performance within $\mathcal{O}(10\%)$ in terms of CPU time, except two cases: configurations with constructors based on single scattering models (i.e.4EmStandardWVI and G4EmStandardSS) or a production cut value of 100 nm are substantially slower than any other configuration. First results of this analysis could already provide guidance to users which physics constructor to include in the physics list of their GEANT4 based background prediction studies and how to optimize the configuration of the constructor. Further analysis will be conducted to characterize the differences in simulated total energy depositions observed over the various GEANT4 electromagnetic physics constructors. A publication with the final results is currently under preparation.

Acknowledgements

This work has been funded through the Sonderforschungsbereich (Collaborative Research Center) SFB1258 'Neutrinos and Dark Matter in Astro- and Particle Physics', by the Austrian science fund (FWF): I5420-N, W1252-N27, P34778-N and by Austria's Agency for Education and Internationalisation (project SK 06/2018). The Bratislava group acknowledges a partial support provided by the Slovak Research and Development Agency (projects SK-AT-2017-001, APVV-15-0576 and APVV-21-0377).

References

- S. Agostinelli *et al.*, *GEANT4–a simulation toolkit*, Nuclear Instruments and Methods A 506, 250 (2003), doi:10.1016/S0168-9002(03)01368-8.
- [2] J. Allison et al., Geant4 developments and applications, IEEE Transactions on Nuclear Science 53, 270 (2006), doi:10.1109/TNS.2006.869826.
- [3] J. Allison *et al.*, *Recent developments in Geant4*, Nuclear Instruments and Methods A 835, 186 (2016), doi:10.1016/j.nima.2016.06.125.
- [4] T. Basaglia, M. C. Han, G. Hoff, C. H. Kim, S. H. Kim, M. G. Pia and P. Saracco, *Quantitative test of the evolution of Geant4 electron backscattering simulation*, IEEE Transactions on Nuclear Science 63(6), 2849 (2016), doi:10.1109/tns.2016.2617834.
- [5] S. Guatelli, A. Mantero, B. Mascialino, M. G. Pia and V. Zampichelli, Validation of Geant4 atomic relaxation against the NIST physical reference data, IEEE Transactions on Nuclear Science 54(3), 594 (2007), doi:10.1109/TNS.2007.894814.
- [6] A. Lechner, M. G. Pia and M. Sudhakar, Validation of Geant4 low energy electromagnetic processes against precision measurements of electron energy deposition, IEEE Transactions on Nuclear Science 56(2), 398 (2009), doi:10.1109/tns.2009.2013858.
- [7] M. Batic, G. Hoff, M. G. Pia, P. Saracco and G. Weidenspointner, Validation of Geant4 simulation of electron energy deposition, IEEE Transactions on Nuclear Science 60(4), 2934 (2013), doi:10.1109/tns.2013.2272404.

- [8] A. H. Abdelhameed, G. Angloher, P. Bauer, A. Bento, E. Bertoldo, R. Breier, C. Bucci, L. Canonica, A. D'Addabbo, S. D. Lorenzo, A. Erb, F. v. Feilitzsch et al., Geant4-based electromagnetic background model for the CRESST dark matter experiment, The European Physical Journal C 79(10), 881 (2019), doi:10.1140/epjc/s10052-019-7385-0.
- [9] Geant4 Collaboration, *Book for application developers: Release 10.6*, Rev4.1 August 11th, 2020.
- [10] T. W. Anderson and D. A. Darling, A test of goodness of fit, Journal of the American Statistical Association 49(268), 765 (1954), doi:10.1080/01621459.1954.10501232.
- [11] A. L. Kolmogorov, *Sulla determinazione empirica di una legge di distribuzione*, Giornale dell'Istituto Italiano Degli Attuari **4**, 83 (1933).
- [12] N. V. Smirnov, On the estimation of discrepancy between empirical curves of distribution for two independent samples, Moscow University Mathematics Bulletin 2, 3 (1939).
- [13] K. Pearson, X. on the criterion that a given system of deviations from the probable in the case of a correlated system of variables is such that it can be reasonably supposed to have arisen from random sampling, The London, Edinburgh, and Dublin Philosophical Magazine and Journal of Science 50(302), 157 (1900), doi:10.1080/14786440009463897.
- [14] W. G. Cochran, *The* χ^2 *Test of Goodness of Fit*, The Annals of Mathematical Statistics **23**(3), 315 (1952), doi:10.1214/aoms/1177729380.
- [15] R. A. Fisher, On the Interpretation of χ^2 from Contingency Tables, and the Calculation of *P*, doi:10.2307/2340521 (1922).
- [16] Q. McNemar, Note on the sampling error of the difference between correlated proportions or percentages, doi:10.1007/BF02295996 (1947).