ELOISE – Reliable background simulation at sub-keV energies

Holger Kluck^{1*}

1 Institut für Hochenergiephysik der Österreichischen Akademie der Wissenschaften, A-1050 Wien, Austria * holger.kluck@oeaw.ac.at

October 2, 2022



14th International Conference on Identification of Dark Matter Vienna, Austria, 18-22 July 2022 doi:10.21468/SciPostPhysProc.?

Abstract

 $CaWO_4$ and Al_2O_3 are well-established target materials which are used by experiments searching for rare events like the elastic scattering off of a hypothetical Dark Matter particle. In recent years, experiments have established detection thresholds for nuclear recoils at the 10 eV-scale. At this energy scale, a reliable Monte Carlo simulation of the expected background is crucial. However, none of the publicly available general-purpose simulation packages are validated at this energy scale and for these targets. The recently started ELOISE project aims to provide reliable simulations of electromagnetic particle interactions for this use case by obtaining experimental reference data, validating the simulation code against them, and, if needed, calibrating the code to the reference data.

Contents

| 1 | Introduction | 2 | |
|----|--|---|--|
| 2 | Importance of a reliable background simulation | 2 | |
| 3 | Relevant physics processes | 2 | |
| 4 | Suitable MC packages | 3 | |
| 5 | Validation protocol | 4 | |
| 6 | Status of ELOISE | 4 | |
| 7 | Conclusion | 4 | |
| Re | ferences | - | |

1 Introduction

The ELOISE (Reliable Background Simulation at Sub-keV Energies) project aims to validate and, if necessary, to tune and extend the Monte Carlo (MC) simulation of electromagnetic interactions in CaWO₄ and Al₂O₃ at sub-keV energies of the free particle approximation. We first motivate the necessity for a reliable simulation in these materials and at this energy scale in section 2. Afterwards, we identify relevant physics processes for ELOISE in section 3 and review suitable MC codes in section 4. In section 5, we outline the applied methodology. We report the current status of ELOISE in section 6 before we conclude in section 7.

2 Importance of a reliable background simulation

CaWO₄ and Al₂O₃ are widely used target materials for cryogenic calorimeters. Operated at mK-temperatures, the measured phonon signal allows the detection of nuclear recoils which are the signal signature for highly interesting *rare* particle processes: Within the Standard Model (SM) of particle physics, the Coherent Elastic Neutrino-Nucleus Scattering (CE_VNS) is known to cause nuclear recoils. The NUCLEUS experiment [1] aims to measure CE_VNS with CaWO₄ calorimeters as a new probe for electro-weak precision measurements. New Physics beyond the SM may provide a particle candidate for Dark Matter (DM), one of the greatest mysteries of modern physics. The CRESST experiment [2] searches for nuclear recoils caused by the elastic scattering of hypothetical DM particles off the nuclei in CaWO₄ and Al₂O₃ among other target materials. Beyond basic research, the CRAB project [3] aims to develop a new energy calibration technique for nuclear recoils in CaWO₄ based on thermal neutron capturing.

In all three cases, the respective energy scales go down to the sub-keV regime: NUCLEUS and CRESST demonstrated detection threshold for nuclear recoils of 19.7 eV [4] and 30.1 eV [2], respectively. CRAB aims for a calibration signal as low as 112.5 eV [3].

At these energies nearly all¹ particle interactions that deposits energy in the respective energy range of interest cause background events. The identification of the sought-after rare events against this dominant background relies crucially on a reliable background model.

Further interest in the detailed physics at lowest energies was sparked by the so-called *low-energy excess*: the observation by CRESST, NUCLEUS, and others of a yet unexplained increase of events with decreasing energies at the sub-keV regime, constituting an excess above the established background [7].

3 Relevant physics processes

Table 1 lists the maximal recoil energies for two typical benchmark cases. If the recoil energy $(E_{\rm rec})$ is below the displacement energy $(E_{\rm dis})$, as for W in the benchmark cases, it is transformed to electron and phonon excitations of the crystal lattice. In case of $E_{\rm rec} > E_{\rm dis}$, as is the case for O, Al, Ca, the atom leaves its lattice site as primary knock-on atom (PKA) and creates a vacancy (see e.g. [10]). In general, $E_{\rm dis}$ depends on the orientation of the PKA relative to the crystal lattice structure [9]. Via nuclear and electronic stopping the PKA loses kinetic energy until it ends as an interstitial atom and causes a crystal defect. At the expected PKA energies, the displaced nucleus loses its kinetic energy mainly via *Coulomb scattering* (nuclear stopping) [11]. If enough energy is transferred to secondary atoms, a nuclear recoil cascade

¹For scintillating CaWO₄ targets, it is generally possible to separate nuclear recoils from other types of interactions via the scintillation light yield. However, at the 10 eV-scale the effectiveness of this approach degenerates quickly [2, 5, 6].

Table 1: The maximal recoil energies caused by CEvNS with a neutrino of 2 MeV kinetic energy ($E_{rec,\nu}$) and by elastic scattering with a 2 GeV/c²-DM particle with a velocity of 220 m s⁻¹ ($E_{rec,DM}$) and the minimal displacement energies (E_{dis}) for CaWO₄ [8] and Al₂O₃ in case of Al [9].

| | O ₈ | ₁₃ Al | ₂₀ Ca | ₇₄ W |
|-----------------------------|----------------|------------------|------------------|-----------------|
| $E_{\rm rec,DM}/{\rm eV}$ | 106.4 | 69.2 | 48.6 | 11.5 |
| $E_{\rm rec, \nu}/{\rm eV}$ | 499.9 | 296.5 | 199.5 | 43.5 |
| $E_{\rm dis}/{\rm eV}$ | 20 | 47.5 | 24 | 196 |

may form. As the target crystals are operated at mK-temperatures, an annealing of the caused damage is strongly suppressed. The PKA and secondary atoms may de-excite via *fluorescence* and emission of *Auger electrons*. At a tertiary stage, the X-rays and electrons may lose their energies mainly via *photoelectric absorption* and *ionisation*, respectively (cf. fig. 1).




Figure 1: Attenuation for photons [12] (*top* row) and stopping power for electrons [13] (*bottom* row) in Al_2O_3 (*left* column) and CaWO₄ (*right* column).

As also neutronic background finally converts to effective electromagnetic interactions via the neutron-nucleus scattering and the resulting recoiling nucleus, ELOISE will be focused on the highlighted electromagnetic processes.

4 Suitable MC packages

Due to the wide range of involved particles and processes as well as the complex detector geometry, the background is usually modelled with a general purpose MC package like Geant4 [14], FLUKA [15], or MCNP [16]. Albeit these codes were validated for various materials and energies, none of them has been validated specifically for CaWO₄ and Al₂O₃ at sub-keV

energies. As pointed out in [17, 18], it is usually precarious to extrapolate the correctness for a given use case from studies based on a different use case. As all three codes are based on the *free particle approximation* of cold, neutral, and unbound atoms, only a dedicated validation can determine if this approximation is still suitable at the 10 eV-scale in CaWO₄ and Al₂O₃. Based on the displacement energies listed in table 1, we expect the onset of significant solid state-effects and hence the break-down of the free particle approximation at roughly 50 eV.

Out of the listed MC codes, the recommended application limit² of Geant4 is the lowest with 250 eV. Furthermore, its source code is publicly available and well documented. This has already enabled the user community to extend Geant4's applicability down to the 10 eV-scale in crystalline Si ("MicroElec" project [19]). Hence, we adopted Geant4 for our studies.

5 Validation protocol

To provide reliable simulations of the electromagnetic processes in $CaWO_4$ and Al_2O_3 from 1 keV down to the onset of solid state-effects, we will apply a four-step approach: (i) collect experimental reference data, (ii) run Geant4 based MC simulations of the reference measurements, (iii) validate the simulation against the references data, and if needed (iv) tune the existing MC models to the reference data or, if this is not sufficient, develop new models.

Step (i) will be realized either via literature searches or via dedicated measurements conducted within ELOISE. To minimise systematic errors, step (ii) requires a detailed simulation of the experimental measurement. In step (iii) we will apply the methodology developed by T. Basaglia et al. (see e.g. [18]) for the objective validation of Geant4 based Monte Carlo simulations. If the development of new, dedicated physics models is needed in step (iv), we plan to adapt the approach of the MicroElec project [19].

6 Status of ELOISE

At the moment, we are studying the energy loss of electrons in $CaWO_4$ by ionisation. As indicated in fig. 1d, the commonly tabulated reference data goes down only to 10 keV. Hence, in step (i) we conducted a dedicated electron energy loss spectroscopy (EELS, see e.g. [20]) of a 105 nm thick $CaWO_4$ sample. The obtained data in the energy range from 0 keV to 2 keV are presently prepared for publication. In step (ii) we are currently running a detailed simulation of the measurement based on Geant4 version 10.6.3.

7 Conclusion

Experiments searching at the 10 eV-scale for nuclear recoils as signature for rare events depend crucially on a reliable MC simulation of their background. At this energy scale, only electromagnetic interactions contribute to the background. As the breakdown of the free particle approximation in CaWO₄ and Al₂O₃ can be expected at \approx 50 eV, a validation of the MC codes is necessary. Currently, ELOISE prepares the validation of Geant4 for electron ionisation in CaWO₄ against a dedicated reference measurement in the energy range of 0 keV to 2 keV.

Funding information The ELOISE project and HK are funded by the Austrian Science Fund (FWF): P 34778-N "ELOISE".

²See https://geant4.web.cern.ch/node/1619.

References

- [1] G. Angloher, F. Ardellier-Desages, A. Bento, L. Canonica, A. Erhart, N. Ferreiro, M. Friedl, V. M. Ghete, D. Hauff, H. Kluck, A. Langenkämper, T. Lasserre *et al.*, *Exploring CE vNS with NUCLEUS at the Chooz nuclear power plant*, The European Physical Journal C **79**(12), 1018 (2019), doi:10.1140/epjc/s10052-019-7454-4.
- [2] A. H. Abdelhameed, G. Angloher, P. Bauer, A. Bento, E. Bertoldo, C. Bucci, L. Canonica, A. D'Addabbo, X. Defay, S. Di Lorenzo, A. Erb, F. v. Feilitzsch et al., First results from the CRESST-III low-mass dark matter program, Phys. Rev. D 100, 102002 (2019), doi:10.1103/PhysRevD.100.102002.
- [3] L. Thulliez, D. Lhuillier, F. Cappella, N. Casali, R. Cerulli, A. Chalil, A. Chebboubi, E. Dumonteil, A. Erhart, A. Giuliani, F. Gunsing, E. Jericha *et al.*, *Calibration of nuclear recoils at the 100 eV scale using neutron capture*, Journal of Instrumentation 16(07), P07032 (2021), doi:10.1088/1748-0221/16/07/p07032.
- [4] R. Strauss et al., The v-cleus experiment: A gram-scale fiducial-volume cryogenic detector for the first detection of coherent neutrino-nucleus scattering, Eur. Phys. J. C 77, 506 (2017), doi:10.1140/epjc/s10052-017-5068-2.
- [5] A. H. Abdelhameed, G. Angloher, P. Bauer, A. Bento, E. Bertoldo, R. Breier, C. Bucci, L. Canonica, A. D'Addabbo, S. D. Lorenzo, A. Erb, F. v. Feilitzsch et al., Geant4-based electromagnetic background model for the cresst dark matter experiment, The European Physical Journal C 79(10), 881 (2019), doi:10.1140/epjc/s10052-019-7385-0.
- [6] A. H. Abdelhameed, G. Angloher, P. Bauer, A. Bento, E. Bertoldo, R. Breier, C. Bucci, L. Canonica, A. D'Addabbo, S. D. Lorenzo, A. Erb, F. v. Feilitzsch *et al.*, *Erratum to: Geant4-based electromagnetic background model for the cresst dark matter experiment*, The European Physical Journal C **79**(12), 987 (2019), doi:10.1140/epjc/s10052-019-7504y.
- [7] P. Adari, A. Aguilar-Arevalo, D. Amidei, G. Angloher, E. Armengaud, C. Augier, L. Balogh, S. Banik, D. Baxter, C. Beaufort, G. Beaulieu, V. Belov *et al.*, *EXCESS work-shop: Descriptions of rising low-energy spectra*, SciPost Phys. Proc. p. 001 (2022), doi:10.21468/SciPostPhysProc.9.001.
- [8] Z. Shao, Q. Zhang, T. Liu and J. Chen, Computer study of intrinsic defects in CaWO₄, Nuclear Instruments and Methods in Physics Research Section B: Beam Interactions with Materials and Atoms 266(5), 797 (2008), doi:10.1016/j.nimb.2008.01.018.
- [9] Y. G. Yuan, M. Jiang, F. A. Zhao, H. Chen, H. Gao, H. Y. Xiao, X. Xiang and X. T. Zu, *Ab initio molecular dynamics simulation of low energy radiation responses of α-Al*₂O₃, Scientific Reports 7(1), 3621 (2017), doi:10.1038/s41598-017-03827-1.
- [10] G. H. Kinchin and R. S. Pease, *The displacement of atoms in solids by radiation*, Reports on Progress in Physics 18(1), 1 (1955), doi:10.1088/0034-4885/18/1/301.
- [11] M. Tanabashi, K. Hagiwara, K. Hikasa, K. Nakamura, Y. Sumino, F. Takahashi, J. Tanaka, K. Agashe, G. Aielli, C. Amsler, M. Antonelli, D. M. Asner *et al.*, *Review of particle physics*, Phys. Rev. D **98**, 030001 (2018), doi:10.1103/PhysRevD.98.030001.

- [12] M. Berger, J. Hubbell, S. Seltzer, J. Chang, J. Coursey, R. Sukumar, D. Zucker and K. Olsen, *XCOM: Photon cross sections database*, Tech. Rep. NIST Standard Reference Database 8 (XGAM), National Institute of Standards and Technology, doi:10.18434/T48G6X (2010).
- [13] M. Berger, J. Coursey, M. Zucker and J. Chang, *Stopping-power & range tables for electrons, protons, and helium ions*, Tech. Rep. NIST Standard Reference Database 124, National Institute of Standards and Technology, doi:10.18434/T4NC7P (2017).
- [14] J. Allison, K. Amako, J. Apostolakis, P. Arce, M. Asai, T. Aso, E. Bagli, A. Bagulya, S. Banerjee, G. Barrand, B. Beck, A. Bogdanov *et al.*, *Recent developments in Geant4*, Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment 835, 186 (2016), doi:10.1016/j.nima.2016.06.125.
- [15] T. Böhlen, F. Cerutti, M. Chin, A. Fassò, A. Ferrari, P. Ortega, A. Mairani, P. Sala, G. Smirnov and V. Vlachoudis, *The FLUKA code: Developments and challenges for high energy and medical applications*, Nuclear Data Sheets **120**, 211 (2014), doi:10.1016/j.nds.2014.07.049.
- [16] C. J. Werner, J. S. Bull, C. J. Solomon, F. B. Brown, G. W. McKinney, M. E. Rising, D. A. Dixon, R. L. Martz, H. G. Hughes, L. J. Cox, A. J. Zukaitis, J. C. Armstrong *et al.*, *MCNP version 6.2 release notes*, Tech. Rep. LA-UR-18-20808, Los Alamos National Laboratory, doi:10.2172/1419730 (2018).
- [17] T. Basaglia, M. C. Han, G. Hoff, C. H. Kim, S. H. Kim, M. G. Pia and P. Saracco, Experimental quantification of Geant4 PhysicsList recommendations: methods and results, Journal of Physics: Conference Series 664(7), 072037 (2015), doi:10.1088/1742-6596/664/7/072037.
- [18] T. Basaglia, M. C. Han, G. Hoff, C. H. Kim, S. H. Kim, M. G. Pia and P. Saracco, *Quantitative test of the evolution of Geant4 electron backscattering simulation*, IEEE Transactions on Nuclear Science 63(6), 2849 (2016), doi:10.1109/tns.2016.2617834.
- [19] M. Raine, M. Gaillardin and P. Paillet, Geant4 physics processes for silicon microdosimetry simulation: Improvements and extension of the energy-range validity up to 10 GeV/nucleon, Nuclear Instruments and Methods in Physics Research Section B: Beam Interactions with Materials and Atoms 325, 97 (2014), doi:10.1016/j.nimb.2014.01.014.
- [20] R. Egerton, Electron Energy-Loss Spectroscopy in the Electron Microscope, Springer, doi:10.1007/978-1-4419-9583-4 (2011).