

evortran: a modern Fortran package for genetic algorithms with applications from LHC data fitting to LISA signal reconstruction

Thomas Biekötter^{1*}

¹ Instituto de Física Teórica UAM/CSIC, Calle Nicolás Cabrera 13-15,
Cantoblanco, 28049, Madrid, Spain

★ thomas.biekoetter@desy.de

Abstract

evortran is a modern Fortran library designed for high-performance genetic algorithms and evolutionary optimization. evortran can be used to tackle a wide range of problems in high-energy physics and beyond, such as derivative-free parameter optimization, complex search tasks, parameter scans and fitting experimental data under the presence of instrumental noise. The library is built as an fpm package with flexibility and efficiency in mind, while also offering a simple installation process, user interface and integration into existing Fortran (or Python) programs. evortran offers a variety of selection, crossover, mutation and elitism strategies, with which users can tailor an evolutionary algorithm to their specific needs. evortran supports different abstraction levels: from operating directly on individuals and populations, to running full evolutionary cycles, and even enabling migration between independently evolving populations to enhance convergence and maintain diversity. In this paper, we present the functionality of the evortran library, demonstrate its capabilities with example benchmark applications, and compare its performance with existing genetic algorithm frameworks. As physics-motivated applications, we use evortran to confront extended Higgs sectors with LHC data and to reconstruct gravitational wave spectra and the underlying physical parameters from LISA mock data, demonstrating its effectiveness in realistic, data-driven scenarios.

Copyright attribution to authors.

This work is a submission to SciPost Physics Codebases.

License information to appear upon publication.

Publication information to appear upon publication.

Received Date

Accepted Date

Published Date

1

2 Contents

3	1 Introduction	2
4	2 Library design and functionality	5
5	2.1 Individuals	5
6	2.1.1 Integer individuals	5
7	2.1.2 Float individuals	7
8	2.1.3 Operate on individuals	8
9	2.2 Populations	9
10	2.2.1 Integer populations	9

11	2.2.2	Float populations	12
12	2.2.3	Operate on populations	13
13	2.3	Genetic algorithm operations	14
14	2.3.1	Selection routines	15
15	2.3.2	Crossover routines	16
16	2.3.3	Mutation routines	18
17	2.3.4	Elitism	20
18	2.4	Evolution of a population	20
19	2.5	Migration of populations	23
20	2.6	Parallelization using OpenMP	26
21	2.7	Core utilities and numerical tools	26
22	2.7.1	Pseudo-random number generation	27
23	2.7.2	Sorting methods	27
24	2.7.3	Function interpolation	28
25	3	User instructions	29
26	3.1	Installation	29
27	3.1.1	Prerequisites	29
28	3.1.2	Building evortran	30
29	3.1.3	Running tests and applications	31
30	3.2	Quick start: basic usage and main features	32
31	3.3	Using evortran from Python	34
32	4	Example applications	36
33	4.1	Minimizing multimodal benchmark functions	36
34	4.1.1	Rastrigin function	36
35	4.1.2	Michalewicz function	38
36	4.1.3	Himmelblau function	40
37	4.1.4	Drop-Wave function	42
38	4.2	Physics applications	46
39	4.2.1	Confronting extended Higgs sector with LHC data	46
40	4.2.2	Reconstructing gravitational wave spectrum from LISA mock data	53
41	5	Conclusions	61
42		References	63

1 Introduction

Genetic algorithms (GAs) are a class of optimization techniques inspired by natural selection and evolution. Unlike gradient-based optimization methods, which rely on derivative information to navigate the solution space, GAs explore the solution space through stochastic processes that mimic the principles of biological evolution. A so-called *population* of candidate solutions, each represented as an *individual*, is iteratively evolved over successive generations. Each individual is represented by a set of parameters referred to as *genes*, and the *fitness* of an individual is a measure of how well it solves the optimization problem at hand. The fitness is obtained

by computing the so-called fitness function that depends on the genes of the individual.¹ In order to evolve one or a set of populations, a GA applies genetic operations that act on the individuals:

1. **Selection:** The selection step involves choosing individuals from the population for reproduction based on their fitness, with fitter individuals having a higher probability of being selected to reproduce and pass on their genes.
2. **Crossover:** The crossover (also called mating) step involves combining the genes of two or more parent individuals to create one or more offspring individuals, with the goal of producing new solutions that inherit desirable traits from the parent individuals.
3. **Mutation:** The mutation step introduces random changes to the genes of a subset of the offspring individuals, ensuring diversity within the population and helping to prevent premature convergence.
4. **Elitism:** The elitism step involves preserving a certain number of the fittest individuals from one generation to the next, ensuring that the best solutions are kept and not lost due to the stochastic nature of the previous selection, crossover and mutation steps.

In addition to the total number of individuals contained in the populations, a specific GA is defined by the precise operations performed at each of the four steps and the probabilities assigned to each of these operations. Different optimization problems often require vastly different choices for these operations and probabilities. It is therefore essential to have a flexible framework that allows for easy customization and adaptation to different optimization tasks.

The stochastic-driven approach allows GAs to explore complex, high-dimensional, non-convex, discontinuous and noisy solution spaces where traditional methods may struggle due to premature convergence to local minima or undefined gradients. GAs have shown great potential in several areas of high-energy physics and cosmology. For instance, in string theory GAs have been used to explore the vast landscape of viable string vacua with phenomenologically consistent properties [1–11]. In particle physics phenomenology, GAs have been applied to scan the parameter spaces of beyond-the-Standard-Model (BSM) theories in order to identify regions of parameter space that are compatible with theoretical and experimental constraints [12–19]. GAs have also played an important role in numerical fitting tasks, such as in the determination of parton distribution functions [20–23]; in the analyse, reconstruction and classification of (detector-level) events at particle accelerators [24–27]; and in the extraction of neutrino oscillation [28–32], astrophysical [33, 34], and cosmological parameters [35–41]. These examples are not intended to be exhaustive, but rather to illustrate the broad applicability of GAs across both experimental and theoretical fields of physics.

GAs often require significant computational costs in terms of evaluations of the fitness function due to their stochastic nature, and they may converge slower to the optimal solution compared to derivative-based techniques, such as gradient descent, especially when a high degree of precision is required. This highlights the need for fast and scalable implementations of GAs to make them suitable for large-scale high-dimensional optimization problems. Several well-established libraries exist already that provide implementations of GAs across different programming languages. In Python, popular open-source packages include DEAP [42], a flexible evolutionary computation framework, and PyGAD [43] that supports training deep

¹The fitness function in GAs does not necessarily depend solely on the genes of a single individual. It can also incorporate external parameters that change over time to simulate environmental changes, or depend on the genes of a subset or the entire population to define a relative fitness value. This allows for more complex selection mechanisms, such as competitive or cooperative fitness evaluation, but also increases the number of calls of the fitness function. `evortran` supports such generalized fitness functions, but for brevity, all examples in this paper will assume the most common case, where the fitness function maps the genes of each individual directly to a fitness value without further dependencies.

learning models created with Keras. GA frameworks in C and C++ which provide efficient and customizable implementations are, for instance, CMAES [44] GAUL [45], EO [46] and OpenGA [47]. Furthermore, PGAPack is a general-purpose GA framework written in C and using the Message Passing Interface (MPI) for parallelization [48]. In the Fortran ecosystem, a well-known optimization library based on GAs is Pikaia [49], which was originally developed for astrophysical applications and recently has become available as a modern Fortran package converted to free-form source and with a new object-oriented user interface [50].

While several GA libraries with varying degree of flexibility exist, `evortran` was developed to provide a modern Fortran-based alternative that balances performance and ease of use. Like Pikaia, it is available as a Fortran package manager (`fpm`) [51, 52] package, making the compilation, installation and integration into other Fortran programs seamless. Compared to C/C++ libraries, `evortran` offers a more user-friendly interface, while still making use of the increased computational performance of a low-level programming language. In addition, its main optimization routines can be accessed from Python via lightweight wrappers, allowing seamless integration into Python-based workflows and outperforming native Python implementations. One of the key strengths of GAs is their inherently modular structure, which allows for straightforward and efficient parallelization, operating on individuals in parallel across one or more populations. To take advantage of this property, `evortran` includes support for parallel execution using OpenMP, which significantly reduces the runtime on multi-core systems. This makes `evortran` an attractive choice for computationally intensive optimization problems in scientific computing. Moreover, `evortran` is designed with a modular structure that allows new GA operations for selection, crossover, mutation and selection to be easily added, such that the library can naturally grow and evolve over time. Finally, `evortran` stands out due to its flexible design which allows users to work at different abstraction levels: (1) the user can operate on individuals directly, (2) the user can evolve whole populations, (3) and the user can evolve a set of populations in parallel with the possibility of periodically migrating individuals in between the populations.

The migration approach is particularly useful for optimization problems where the goals is not only to find the globally optimal solution but also to identify multiple diverse solutions with sufficiently good fitness (see also Ref. [19]). This feature is relevant for a variety of optimization tasks encountered in high-energy physics. For example, in studies of the phenomenology of BSM theories, one often performs extensive parameter space scans involving models with a large number of free parameters, while at the same time different sets of theoretical and experimental requirements constrain the allowed parameter space (see, e.g. Refs. [12, 13, 15–17]). These scans are constrained by experimental measurements, which come with their own uncertainties. In such contexts, the goal of the parameter scan is not merely to find a single best-fit point, but rather to identify all distinct regions of parameter space that satisfy the imposed constraints within the uncertainties. The migration-based approach of `evortran` is especially well-suited to this task, as independently evolving populations can converge to different viable regions of the parameter space. This enables a more comprehensive exploration and characterization of phenomenologically acceptable solutions which might be missed in simple random scans or when using gradient-based optimization methods.

The outline of the paper is as follows: in Section 2, we describe the design and core functionality of the `evortran` library in detail. Section 3 provides user instructions, including installation steps and usage guidelines. In Section 4, we present example applications that illustrate the capabilities of the library, focusing on well-known benchmark functions for optimization problems in Section 4.1 and on realistic physics applications in Section 4.2. Finally, Section 5 contains our conclusions. Readers who are already familiar with GAs and are primarily interested in how to install and use `evortran` may wish to skip directly to Section 3.

2 Library design and functionality

The design of `evortran` is centered around flexibility, modularity, and performance, enabling users to employ GAs using varying degrees of computational resources depending on the complexity and requirements of their optimization tasks. This section outlines the core components and features of the library, introducing the derived types and utilities that structure the implementation. As already mentioned in Section 1, a key concept underlying `evortran` is its multi-layered interface, which allows users to work at different abstraction levels: (1) work directly on arrays of individuals, (2) handle entire populations of individuals using population-level methods, and (3) apply evolution strategies acting on one or more populations in parallel through a migration framework, with optional inter-population exchange of individuals. This design makes `evortran` suitable for both fine-grained control and high-level optimization applications. The subsections that follow below are organized accordingly. We begin by introducing the derived types for the individual and population data structures in Section 2.1 and Section 2.2, respectively, which serve as the most fundamental building blocks of the library. We then present the available GA operations in Section 2.3, followed by the two key utilities that implement full population evolution in Section 2.4 and migration-based evolution in Section 2.5. Finally, we summarize the core numerical tools and auxiliary utilities that are included in `evortran` in Section 2.7.

2.1 Individuals

The most fundamental building block of `evortran` is the individual derived type, which represents a single candidate solution within a GA. `evortran` contains two types of individuals, one for integer valued genes and one for genes that can take continuous values as floating-point numbers.

2.1.1 Integer individuals

We start by describing the version of individuals with integer-valued genes, hereafter referred to as *integer individuals*. The declaration of the individual type for integer individuals is as follows:

```

1  type, public :: individual
2  integer :: length
3  integer :: base_pairs
4  integer, dimension(:), allocatable :: genes
5  procedure(func_abstract), pointer, private :: func => null()
6  real(wp), private :: fitness = 0.0e0_wp
7  logical, private :: fitness_calculated = .false.
8  contains
9  procedure, public :: calc_fitness
10 procedure, public :: get_fitness
11 procedure, public :: reset_fitness
12 end type individual
13
14 interface individual
15   procedure create_individual
16 end interface individual

```

The components of the derived type are as follows:

- `length`: The number of genes in the individual. It is set during initialization and must be greater than 1.

- 191 - `base_pairs`: The number of distinct values that each gene can take. The default is 2,
192 corresponding to binary genomes where each gene is either 0 or 1.
- 193 - `genes`: An allocatable integer array of size `length` that stores the genome of the indi-
194 vidual.
- 195 - `func`: A procedure pointer that points to the fitness function associated with this indi-
196 vidual. The fitness function is set during initialization.
- 197 - `fitness`: A real number storing the most recently computed fitness value.
- 198 - `fitness_calculated`: A logical flag indicating whether the current fitness value cor-
199 responds to the current genome. This avoids redundant calls of the fitness function.

200 To create a new integer individual, users can use the overloaded interface `individual`, which
201 wraps the internal `create_individual` function. This provides a clean and intuitive way to
202 construct an individual object by specifying the number of genes, a fitness function, the number
203 of base pairs, and optionally a seed value for the genes at initialization. For example, a typical
204 initialization might look like:²

```
205 1 use evortran__individuals_integer, only : individual
206 2
207 3 type(individual) :: ind
208 4
209 5 ind = individual(length=10, fit_func=fit_func, base_pairs=2)
```

210 This constructs an individual with 10 binary genes and associates it with the fitness function
211 `fit_func`. Since the optional argument `seed` is not given, the gene values are assigned
212 randomly within the allowed range. The fitness function must be defined by the user (either
213 in the main program or in an external module) following the abstract interface defined as:

```
214 1 subroutine func_abstract(ind, f)
215 2   class(individual), intent(in) :: ind
216 3   real(wp), intent(out) :: f
217 4 end subroutine func_abstract
```

218 Thus, the fitness function is a subroutine that takes an individual object as input and com-
219 puts the fitness value that is returned as the second argument. In contrast to many existing
220 GA frameworks that maximize the fitness function, `evortran` is designed to minimize it, and
221 the fitness function should be defined accordingly. The type `real(wp)` uses the working pre-
222 cision `wp` defined in the module `evortran__util_kinds`. By default, `wp` corresponds to
223 double precision, but it can be changed to quad precision at compile time by providing the
224 preprocessor flag `-DQUAD`. Further details on compilation and installation are provided in Sec-
225 tion 3. The declarations of the procedure associated to the derived type of integer individuals
226 are as follows:

```
227 1 subroutine calc_fitness(this)
228 2   class(individual), intent(inout) :: this
229 3   real(wp) :: f
230 4 end subroutine calc_fitness
231 5
232 6 function get_fitness(this) result(f)
233 7   class(individual), intent(inout) :: this
234 8   real(wp) :: f
```

²For brevity, we do not show the statements required to initialize the PRNG here and in the following code snippets contained in this section. These should be called at the beginning of any program that uses the `evortran` library. For details, see the discussion in Section 2.7.1.

```

235     9 end function get_fitness
236    10
237    11 subroutine reset_fitness(this)
238    12   class(individual), intent(inout) :: this
239    13 end subroutine reset_fitness

```

240 These procedures carry out the following tasks:

- 241 – `calc_fitness`: Calculates the fitness with the current gene values by calling the fitness
- 242 function if the fitness has not yet been computed.
- 243 – `get_fitness`: Same as `calc_fitness`, but also returns the computed fitness value.
- 244 – `reset_fitness`: Resets the fitness to zero and marks it as not yet computed, which is
- 245 necessary after any genetic operation that modifies the genes of the individual.

246 2.1.2 Float individuals

247 In addition to supporting individuals with discrete integer-valued genes, `evortran` also pro-
 248 vides a derived type for individuals with genes represented by continuous floating-point num-
 249 bers. These *float individuals* are useful for optimization problems in continuous parameter
 250 spaces. Below is the definition of the derived type used to represent float individuals:

```

251    1 type, public :: individual
252    2   integer :: length
253    3   real(wp) :: lower_lim = 0.0e0_wp
254    4   real(wp) :: upper_lim = 1.0e0_wp
255    5   real(wp), dimension(:), allocatable :: genes
256    6   procedure(func_abstract), pointer, private :: func => null()
257    7   real(wp), private :: fitness = 0.0e0_wp
258    8   logical, private :: fitness_calculated = .false.
259    9 contains
260   10   procedure, public :: calc_fitness
261   11   procedure, public :: get_fitness
262   12   procedure, public :: reset_fitness
263  13 end type individual
264  14
265  15 interface individual
266  16   procedure create_individual
267  17 end interface individual

```

268 Here, `wp` is the real kind working precision with which `evortran` operates, defined in the
 269 module `evortran_util_kinds`. By default, `evortran` uses double precision with 15 signif-
 270 icant digits, but the precision can be changed to quadruple-precision with 30 significant digits
 271 at compile time, see Section 3.1. The components of the float individual type are:

- 272 – `length`: The number of genes in the individual. It is set during initialization and must
- 273 be greater than 1.
- 274 – `lower_lim`: the lower bound of the valid range for gene values (default is 0.0).
- 275 – `upper_lim`: the upper bound of the valid range for gene values (default is 1.0).
- 276 – `genes`: a real-valued array of size `length` that stores the gene values.
- 277 – `func`: a procedure pointer to the fitness function.
- 278 – `fitness`: the cached fitness value.
- 279 – `fitness_calculated`: logical flag indicating whether the fitness has already been
- 280 computed.

Furthermore, the derived type for the float individuals are associated to the same procedures as present in the type for integer individuals, which are described above. New float individual objects can be created using the generic interface `individual`, which internally calls the `create_individual` function, in the same way as for integer individuals. A float individual is initialized by providing the gene length, the fitness function, and optionally the lower and upper bounds for the gene values, as well as a random seed:

```

1 use evortran__individuals_float, only : individual
2
3 type(individual) :: ind
4
5 ind = individual( &
6   length=10, fit_func=fit_func, &
7   lower_lim=-1.0e0_wp, upper_lim=1.0e0_wp, seed=0.0e0_wp)

```

This creates a float individual with 10 floating-point number genes and associates it with the fitness function `fit_func`. The fitness function must be defined by the user using the same abstract interface as for the integer individuals discussed above. The optional arguments `lower_lim` and `upper_lim` enforce that allowed gene values should lie between -1 and 1, and the optional seed argument is provided to initialize all 10 gene values with the value 0.

2.1.3 Operate on individuals

Although `evortran` is primarily designed to carry out optimization tasks at higher abstraction levels, through evolving entire populations or even sets of populations, it is also possible to operate directly on individual objects. This can be useful for testing, debugging, or for users who require fine-grained control over their GA.

The following example program demonstrates how to manually create and operate on float individuals. It shows the initialization of two individuals, application of simulated binary crossover (see Section 2.3.2) to generate two offspring individuals, and it uses the shuffle mutation routine (see Section 2.3.3) to modify the genes of one of the two offspring individuals.

```

1 program operate_on_individuals
2
3 use evortran__util_kinds, only : wp
4 use evortran__individuals_float, only : individual
5 use evortran__crossovers_sbx, only :
6   simulated_binary_crossing
7 use evortran__mutations_shuffle, only : shuffle_mutate
8 use evortran__prng_rand, only : initialize_rands
9
10 implicit none
11
12 type(individual) :: ind1
13 type(individual) :: ind2
14 type(individual) :: ind3
15 type(individual) :: ind4
16
17 call initialize_rands(mode='twister')
18
19 ind1 = individual(6, func)
20 ind2 = individual(6, func)

```

```

330      21  call simulated_binary_crossing( &
331      22      ind1, ind2, ind3, ind4, eta_c=30e0_wp, p_c=0.5e0_wp)
332      23
333      24  call shuffle_mutate(ind3)
334      25
335      26  contains
336      27
337      28  subroutine func(ind, f)
338      29
339      30      class(individual), intent(in) :: ind
340      31      real(wp), intent(out) :: f
341      32
342      33      f = sum(ind%genes**2)
343      34
344      35  end subroutine func
345      36
346      37  end program operate_on_individuals

```

Specifically, this example illustrates the following sequence of operations:

- The pseudo-random number generator is initialized using the Mersenne Twister algorithm (see also Section 2.7.1) by calling `initialize_rands`.
- Two float individuals `ind1` and `ind2` are created with 6 genes each. They are associated with the fitness function `func`, which in this example computes the sum of squares of the gene values.
- The procedure `simulated_binary_crossing` performs crossover between the parent individuals `ind1` and `ind2`, producing two offspring individuals `ind3` and `ind4`. The parameters `eta_c` and `p_c` are optional arguments that control the shape and probability of the crossover, see Section 2.3.2 for details.
- A shuffle mutation is applied to one of the offspring (`ind3`) using `shuffle_mutate`, see Section 2.3.3 for details.

While this example provides insight into the inner workings of the library, it is generally not the preferred way to use `evortran` for actual optimization tasks. These are better handled at the level of populations, as discussed in the following.

2.2 Populations

Instead of working with individuals directly, it is usually more convenient to work with a set of individuals and perform different steps of a GA on this set as a whole. `evortran` defines for this purpose the derived type `population` both for integer and float individuals. This enables users to apply selection, crossover, mutation, and elitism operations in a modular and efficient way.

2.2.1 Integer populations

The declaration of the population derived type for integer individuals is given below:

```

370      1  type, public :: population
371      2      integer :: popsize
372      3      integer :: gene_length
373      4      integer :: base_pairs
374      5      type(individual), public, dimension(:), allocatable :: inds
375      6      type(individual), public, dimension(:), allocatable ::
376          selection

```

```

377 7  type(individual), public, dimension(:), allocatable :: elite
378 8  type(individual), public, dimension(:), allocatable ::
379   offspring
380 9  integer, public, dimension(:), allocatable ::
381   indices_sorted_fitness
382 10 contains
383 11  procedure, public :: calc_fitnesses
384 12  procedure, public :: select_individuals
385 13  procedure, public :: select_elite
386 14  procedure, public :: produce_offspring
387 15  procedure, public :: make_population_from_offspring
388 16  procedure, public :: get_fittest_individual
389 17 end type population
390 18
391 19 interface population
392 20  procedure create_population
393 21 end interface population

```

394 The components of the integer population type are:

- 395 - popsize: Number of individuals in the population.
- 396 - gene_length: Length of the gene array for each individual.
- 397 - base_pairs: Number of possible discrete values each gene can take (default is 2).
- 398 - inds: The array of actual individual objects in the population.
- 399 - selection: Array storing selected individuals.
- 400 - elite: Array for elite individuals that are preserved between generations.
- 401 - offspring: Array holding new individuals generated from crossover and mutation.
- 402 - indices_sorted_fitness: Indices of individuals sorted by fitness.

403 A new integer population object can be initialized using the constructor interface:

```

404 1  use evortran__populations_integer, only: population
405 2
406 3  type(population) :: pop
407 4
408 5  pop = population( &
409 6   popsize, gene_length, fit_func, &
410 7   base_pairs, seed, inds)

```

411 Here, popsize is the number of individuals, gene_length the length of the gene array of
412 each individual, fit_func the fitness procedure, base_pairs (optional) the number of pos-
413 sible gene values, and seed (optional) sets the initial values of the genes of all individuals
414 contained in the population. If seed is not given, the gene values of the initial populations
415 are randomly generated following a uniform distribution. Finally, the optional argument inds
416 is an array of integer individuals that shall be contained in the initial population. The derived
417 type for integer populations contains the following type-bound procedures:

```

418 1  subroutine calc_fitnesses(this)
419 2   class(population), intent(inout) :: this
420 3  end subroutine
421 4
422 5  subroutine select_individuals( &
423 6   this, num, mode, tourn_size, wheele_size)
424 7   class(population), intent(inout) :: this
425 8   integer, intent(in) :: num

```

```

426      9  character(len=*), intent(in) :: mode
427     10  integer, intent(in), optional :: tourn_size
428     11  integer, intent(in), optional :: wheele_size
429     12  end subroutine
430     13
431     14  subroutine select_elite(this, num, mode)
432     15  class(population), intent(inout) :: this
433     16  integer, intent(in) :: num
434     17  character(len=*), intent(in) :: mode
435     18  end subroutine
436     19
437     20  subroutine produce_offspring( &
438     21      this, num, mating, mating_prob, mutate, mutate_prob, &
439     22      mutate_gene_prob, include_elite, uniform_mating_ratio)
440     23  class(population), intent(inout) :: this
441     24  integer, intent(in) :: num
442     25  character(len=*), intent(in) :: mating
443     26  real(wp), intent(in), optional :: mating_prob
444     27  character(len=*), intent(in), optional :: mutate
445     28  real(wp), intent(in), optional :: mutate_prob
446     29  real(wp), intent(in), optional :: mutate_gene_prob
447     30  logical, intent(in), optional :: include_elite
448     31  real(wp), intent(in), optional :: uniform_mating_ratio
449     32  end subroutine
450     33
451     34  function make_population_from_offspring( &
452     35      this, fit_func, add_elite) result(pop)
453     36  class(population), intent(inout) :: this
454     37  procedure(func\_abstract) :: fit\_func
455     38  logical, intent(in), optional :: add\_elite
456     39  type(population) :: pop
457     40  end function
458     41
459     42  function get_fittest_individual(this) result(ind)
460     43  class(population), intent(in) :: this
461     44  type(individual) :: ind
462     45  end function

```

463 These procedures carry out the following tasks:

- 464 – `calc_fitnesses`: Computes the fitness values of all individuals in the population by
465 calling each individual's `calc_fitness` routine.
- 466 – `select_individuals`: Selects `num` individuals from the population using the method
467 specified by `mode`. Supported selection modes include tournament, rank, and roulette
468 wheel selection, see Table 1. The optional arguments `tourn_size` and `wheele_size`
469 control the subset size in tournament and roulette wheel selection, respectively.
- 470 – `select_elite`: Selects an elite of `num` high-performing individuals that can be pre-
471 served and reintroduced after crossover and mutation to ensure that they are main-
472 tained in the next generation of the population. So far the only mode supported is called
473 `best_fitness` which includes the individuals with the best fitness values in the elite.
474 These individuals are stored in the type-bound `elite` array.
- 475 – `produce_offspring`: Generates an array of offspring individuals with size `num` by
476 applying the specified crossover, mutation and elitism routines. These individuals
477 are stored in the type-bound `offspring` array. The argument `mating` selects the
478 crossover method, see Table 2, while `mating_prob` defines the crossover probabil-
479 ity. The argument `mutate` selects the mutation method, see Table 3, while `muta-`

tion is applied according to a probability of `mutate_prob`. If the mutation method accepts a gene-wise mutation probability, this probability can be given with the argument `mutate_gene_prob`. If `include_elite` is set to true, the elite individuals are also added to the offspring. The `uniform_mating_ratio` is used if uniform crossover is selected, see the discussion in Section 2.3.3.

- `make_population_from_offspring`: Returns an instance of type `population` with the individuals given by the offspring individuals. The fitness function `fit_func` is associated with the new population. If `add_elite` is set to true, the previously selected elite individuals are also added to the new population.
- `get_fittest_individual`: Returns the single individual with the highest fitness value in the population.

2.2.2 Float populations

Similar to integer individuals, `evortran` provides a population derived type to manage and evolve collections of float individuals. These float individuals have real-valued genes and are suited for optimization problems defined over continuous search spaces. The population type offers the same high-level routines for selection, crossover, mutation, and elitism as for integer populations. The definition of the *float population* type is shown below:

```

1  type, public :: population
2  integer :: popsize
3  integer :: gene_length
4  real(wp) :: lower_lim = 0.0e0_wp
5  real(wp) :: upper_lim = 1.0e0_wp
6  type(individual), public, dimension(:), allocatable :: inds
7  type(individual), public, dimension(:), allocatable ::
8      selection
9  type(individual), public, dimension(:), allocatable :: elite
10 type(individual), public, dimension(:), allocatable ::
11     offspring
12 integer, public, dimension(:), allocatable ::
13     indices_sorted_fitness
14 contains
15 procedure, public :: calc_fitnesses
16 procedure, public :: select_individuals
17 procedure, public :: select_elite
18 procedure, public :: produce_offspring
19 procedure, public :: make_population_from_offspring
20 procedure, public :: get_fittest_individual
21 procedure, public :: get_fittest_individuals
22 end type population
23
24 interface population
25   procedure create_population
26 end interface population

```

In addition to the components contained also in the integer population type, see the discussion above, the float population type contains the following additional components:

- `lower_lim`: a real number defining the lower bound of possible gene values (default 0.0).
- `upper_lim`: a real number defining the upper bound of possible gene values (default 1.0).

These values are respected when generating initial genes, and when applying crossover and mutation operators, where the stochastic nature of these operations might otherwise lead to gene values outside of the interval defined by `lower_lim` and `upper_lim`.

A new float population object can be created using the same constructor interface as for integer populations:

```

534 1 use evortran__populations_float, only: population
535 2
536 3 type(population) :: pop
537 4
538 5 pop = population( &
539 6   popsize, gene_length, fit_func, &
540 7   lower_lim, upper_lim, seed)

```

Here, `lower_lim` and `upper_lim` (optional) define the possible range the genes. All other arguments behave as in the case of integer populations.

Besides the procedures available for integer populations (see previous subsection), the float population type defines one additional procedure called `get_fittest_individuals`. This routine returns the `n` fittest individuals in the population, sorted by fitness in ascending order.

2.2.3 Operate on populations

Similar to operating on individuals, as discussed in Section 2.1.3, `evortran` allows to create and manipulate directly instances of the population types. While operating directly on populations is a step up in abstraction compared to manipulating individual objects, it is still not the most convenient to use `evortran` for real-world optimization tasks. The library provides higher-level functions which allow users to evolve populations over multiple generations and epochs with minimal code, see the discussions in Section 2.4 and Section 2.5. However, working at the population level offers insights into the inner workings of these functions and can be helpful for advanced users who need more fine-grained control.

The following example demonstrates how to manually evolve a population of float individuals over one generation, using built-in selection, crossover, and mutation operations:

```

558 1 program operate_on_populations
559 2
560 3 use evortran__util_kinds, only : wp
561 4 use evortran__populations_float, only: population
562 5 use evortran__individuals_float, only: individual
563 6 use evortran__prng_rand, only : initialize_rands
564 7
565 8 implicit none
566 9
567 10 type(population) :: pop
568 11 type(population) :: new_pop
569 12 type(individual) :: best
570 13
571 14 call initialize_rands(mode='twister')
572 15
573 16 pop = population(100, 10, func)
574 17
575 18 call pop%select_individuals(50, 'roulette', wheel_size=7)
576 19
577 20 call pop%produce_offspring( &

```

```

578 21      100,  &
579 22      mating='blend',  &
580 23      include_elite=.true.,  &
581 24      mutate='uniform')
582 25
583 26      new_pop = pop%make_population_from_offspring(func)
584 27      best = new_pop%get_fittest_individual()
585 28
586 29      write(*,*) "Genes of best-fit ind.: ", best%genes
587 30      write(*,*) "Fitness of best-fit ind.:", best%get_fitness()
588 31
589 32 contains
590 33
591 34      pure subroutine func(ind, f)
592 35
593 36          class(individual), intent(in) :: ind
594 37          real(wp), intent(out) :: f
595 38
596 39          f = sum(ind%genes) / real(ind%length, wp)
597 40
598 41      end subroutine func
599 42
600 43 end program operate_on_populations

```

601 This example demonstrates a typical evolutionary step operating on a float population:

- 602 – The random number generator is initialized with the Mersenne Twister method.
- 603 – A population pop of 100 float individuals is created, each with 10 genes, and associated with the custom fitness function func.
- 604
- 605 – A subset of individuals is selected for reproduction using the roulette selection method, which are stored in pop%selection. The optional argument wheel_size is propagated to the roulette wheel selection routine (see Section 2.3.1).
- 606
- 607
- 608 – The procedure produce_offspring is called to generate 100 new offspring individuals, which are stored in pop%offspring. The arguments set blend crossover and uniform mutation as operations to produce the offspring, and the optional argument include_elite is set to true to enforce that the fittest individual in the population is taken over into the set of offspring individuals.
- 609
- 610
- 611
- 612
- 613 – By calling make_population_from_offspring, a new population new_pop is constructed from the offspring, using the same fitness function.
- 614
- 615 – The fittest individual of the new population is extracted by calling
- 616 get_fittest_individual. Finally, the gene values and the fitness value of the
- 617 best-fit individual is printed.

618 This example provides a closer look at the operations evortran offers for manipulating populations manually. It gives users full control over each step of the evolutionary process and illustrates how populations are typically evolved internally when higher-level functions are used.

622 2.3 Genetic algorithm operations

623 A GA progresses through repeated application of four key operations that mimic the principles of natural selection and evolution: selection, crossover, mutation, and elitism. The specific strategies and implementations of these operations greatly influence the effectiveness and efficiency of the GA. The evortran library provides flexible and modular routines for each of these operations, allowing users to tailor the GA to their demands. In the following

	Kinds	Optional arguments [default values]
tournament	I/F	tourn_size [2]
rank	I/F	-
roulette	I/F	wheele_size [3]

Table 1: Selection methods implemented in `evortran`. The first column shows the names of the three selection methods in `evortran`. The respective functions are labeled in the second column as I, F, or I/F, indicating the type of genes they operate on: I for individuals with integer-valued genes, F for those with floating-point genes, and I/F for functions that can handle both types. The last column shows optional arguments of each routine and their default values.

subsections, we describe in detail the selection, crossover, mutation, and elitism mechanisms currently implemented in `evortran`, highlighting their underlying principles and typical use cases. We also comment on the advantages and disadvantages of the different methods.

2.3.1 Selection routines

The first step in the evolution of a population from one generation to the other is the selection step. During the selections step, samples of the initial population are selected that are allowed to take part in the subsequent crossover step. The selection of the individuals is guided by their fitness values, with the aim of increasing the likelihood of producing fitter offspring. To this end, the selection procedure favors individuals with good fitness values. In Table 1 we show the selection routines that are currently implemented in `evortran`. These routines are implemented generically and can act on both integer and float individuals.

One of the most commonly used selection strategies is *tournament* selection. In this method, a subset of individuals is randomly sampled from the population, and the individual with the highest fitness within this subset is selected to proceed to the crossover step. This process is repeated as many times as needed to construct the mating pool. The tournament size determines the selection pressure. Larger tournament sizes increase the chance of selecting individuals with good fitness, while smaller ones help preserve diversity. In `evortran`, the default tournament size is set to 2, which provides a good balance between selection pressure and population diversity for many applications.

Another selection strategy implemented in `evortran` is *rank* selection. In this approach, individuals in the population are first sorted according to their fitness values, and the selection is based on their rank rather than their absolute fitness. This method helps prevent the premature domination of highly fit individuals and maintains a more balanced selection pressure, particularly in cases where fitness values vary widely. In `evortran`, rank selection is implemented in a straightforward way: the size of the mating pool is specified, and the top-ranking individuals, i.e. those with the best fitness values, are selected until the pool is full. While this ensures that only the most promising individuals participate in the crossover step, it also reduces diversity more aggressively than other selection methods. Compared to tournament selection, rank selection offers more deterministic control over selection pressure but comes with a computational cost. First, it requires the evaluation of the fitness of all individuals contained in the population. Second, a sorting step is required to rank the individuals, which can become expensive for large population sizes. In contrast, tournament selection is more scalable, as it only operates on small subsets of the population and avoids global sorting.

The third selection method currently implemented in `evortran` is a modified version of *roulette wheel* selection, designed to balance randomness and selection pressure in a com-

putationally more efficient way than the usual wheel selection. Unlike standard fitness-proportionate selection over the entire population, the `evortran` implementation first randomly selects a small subset of individuals called the wheel size k . The default value of the wheel size in `evortran` is $k = 3$. Let the subset consist of individuals $i = \{1, 2, \dots, k\}$. Among these, the best fitness value is determined as

$$f_{\text{best}} = \min\{f_1, f_2, \dots, f_k\}, \quad (1)$$

where f_i is the fitness values of the individual i .³ Then, for each individual in the subset, a weight parameter

$$w_i = \exp\left[\frac{-(f_i - f_{\text{best}})^2}{f_{\text{best}}^2}\right], \Rightarrow 0 < w_i \leq 1, \quad w_{\text{best}} = 1, \quad (2)$$

is computed. The selection probabilities for the individuals are computed using these weights, instead of using the fitness values f_i themselves as in usual roulette wheel selection, via

$$p_i = \frac{w_i}{\sum_{j=1}^k w_j}. \quad (3)$$

Then a single individual from the subset is selected based on these probabilities. The whole operation is repeated until the mating pool is full. Compared to tournament selection and rank selection, this approach can better preserve diversity, with the diversity generally increasing with increasing wheel size k , while still biasing toward candidates with better fitness in the population. Unlike tournament selection, where only the best-fitted individual in the subset is selected, here all individuals in the subset have a non-zero probability p_i of being chosen. This selection strategy can therefore be viewed as a more relaxed version of tournament selection (with the tournament size equal to the wheel size). Compared to rank selection, it avoids the need to sort the entire population, making it computationally less expensive for large populations. However, the influence of the wheel size and fitness distribution can significantly affect its behavior, requiring carefully choosing the wheel size k for good performance in specific applications.

2.3.2 Crossover routines

The crossover step is the process during which new offspring individuals are created whose genes are determined by exchanging and potentially modifying the genes of two or more parent individuals. `evortran` currently offers several crossover routines that are summarized in Table 2.

The *one-point* crossover routine takes two parent individuals as input and returns two offspring individuals. The genes of the offspring individuals are created by selecting a random point along the genes of the parent individuals and exchanging their genes beyond this point. One-point crossing should be used if one wants to maintain some structure in the gene pool since it preserves large segments of the genes of the parent individuals. However, if the optimization problems is high-dimensional and complex, one-point crossing may not introduce sufficient diversity, leading to premature convergence. Moreover, it disrupts the positional dependencies of neighbouring genes, which may be disadvantageous for optimization problems in which certain genes must remain next to each other for meaningful solutions.

The *two-point* crossover routine works in a very similar way as the one-point crossover routine. The only difference is that two-point crossing uses two (instead of one) randomly chosen points along the genes, and only the genes between these two points are swapped in

³We remind the reader that `evortran` minimizes the fitness function.

	Kinds	N_{par}	N_{off}	Optional arguments [default values]
one-point	I/F	2	2	-
two-point	I/F	2	2	-
uniform	I/F	2	2	ratio [0.5]
blend	F	2	2	alpha [0.5]
sbx	F	2	2	eta_c [1.0], p_c [0.5]

Table 2: Crossover methods implemented in *evortran*. The first column shows the names of the four crossover methods in *evortran*. The respective functions are labeled in the second column as I, F, or I/F, indicating the type of genes they operate on: I for individuals with integer-valued genes, F for those with floating-point genes, and I/F for functions that can handle both types. The third and fourth columns show N_{par} and N_{off} which are the number of parent individuals and offspring individuals, respectively. The last column shows optional arguments of each routine and their default values.

order to create the genes of two offspring individuals. Compared to one-point crossing, the two-point crossing method provides more genetic mixing, while still preserving large segments of genetic material. However, it also disrupts genetic structure by separating neighbouring genes.

The *uniform* crossover routine takes two parent individuals as input, and their genes are inherited randomly by two offspring individuals. Each gene of the offspring individuals is randomly assigned to be taken over from either the first or the second parent individual. Typically, the probability to inherit a gene from parent A or parent B is set to be equal, such that both offspring individuals on average acquire 50% of their genes from one parent and 50% from the other. This is also the default setting in *evortran*. By disrupting the genes of the parent individuals at various positions along the genes, uniform crossing leads to excellent diversity in the gene pool. This makes it well suited for highly complex optimization tasks because it is less affected by premature convergence compared to one- and two-point crossing. However, the highly disruptive behaviour of uniform crossing with 50% exchange probability does not maintain larger blocks of genes, which may cause slow convergence. In such cases, it can be useful to lower the degree of diversity. This can be achieved in *evortran* by changing the ratio of the genes assigned from either parent A or parent B via the optional argument *ratio*. The value given for this argument is the probability for each gene of parent A to be inherited by the first offspring individual, and the second offspring individual inherits the corresponding gene from parent B. Accordingly, the probability for the second offspring individual to inherit a gene from parent A is one minus the value given for *ratio*.

The *blend* crossover routine (also called BLX- α) is a crossing procedure that can only be applied to individuals with genes consisting of continuous numbers and not integers. This method generates two offspring individuals by selecting new gene values within an extended range between the gene values of two parent individuals. With a_i being the genes from parent A and b_i the genes from parent B, the genes c_i and d_i of the offspring individuals C and D are given, respectively, by randomly and uniformly selecting a number in the ranges

$$c_i \in [a_i - \alpha(b_i - a_i), b_i + \alpha(b_i - a_i)] \quad \text{and} \quad d_i \in [b_i - \alpha(a_i - b_i), a_i + \alpha(a_i - b_i)], \quad (4)$$

for all $i = 1, \dots, N_g$. If the above operation leads to gene values c_i and/or d_i that fall outside of the allowed range of the genes of the individuals, their values are clipped to the nearest valid value, i.e. either the lower or the upper limit. The parameter α controls the range beyond

which the genes of the offspring individuals can extend beyond the ones of the parent individuals. In many applications it is set to $\alpha = 0.5$, and this is also the default setting in `evortran`. The presence of this parameter allows tunable exploration of the solution space, in contrast to the other implemented crossover strategies. However, in many cases a good choice for α can only be obtained on heuristic grounds by “trial and error”. Blend crossing is fundamentally different from the other crossover methods due to its continuous nature, creating gene values for the offspring individuals that are similar but not identical to the genes contained in the parent individuals. This feature makes blend crossing often more suitable for continuous optimization problems in which small variations can give rise to significant improvements in the fitness of an individual.

Finally, *simulated binary crossover* (usually abbreviated as SBX) is a widely used operator in GAs for individuals with floating-point genes. Inspired by one-point crossover in binary-coded GAs, SBX simulates a similar effect in continuous search spaces. For each corresponding gene pair (a_i, b_i) from two parent individuals, a random number $0 \leq u_i \leq 1$ is drawn from a uniform distribution. From the random variables u_i , spread factor $\beta_{q,i}$ are computed using the distribution index η_c via

$$\beta_{q,i}(u) = \begin{cases} (2u_i)^{1/(\eta_c+1)}, & \text{if } u_i \leq 0.5 \\ \left(\frac{1}{2(1-u_i)}\right)^{1/(\eta_c+1)}, & \text{if } u_i > 0.5 \end{cases} . \quad (5)$$

Then the corresponding pair of offspring genes c_i and d_i are computed as

$$\begin{aligned} c_i &= 0.5 \left[(1 + \beta_{q,i})a_i + (1 - \beta_{q,i})b_i \right], \\ d_i &= 0.5 \left[(1 - \beta_{q,i})a_i + (1 + \beta_{q,i})b_i \right]. \end{aligned} \quad (6)$$

This operation is applied independently to each gene pair ($i = 1, \dots, N_g$) with a certain gene-wise crossover probability p_c . For each gene pair, the SBX operation described above is applied to generate new gene values c_i and d_i , and otherwise (with probability $1 - p_c$) the two offspring individuals simply inherit the genes a_i or b_i , respectively. As for blend crossover, if the above operation leads to gene values c_i and/or d_i that fall outside of the allowed range of the genes of the individuals, their values are clipped to the lower or upper limit of the allowed range. In `evortran` the probability p_c has the default value $p_c = 0.5$, but its value can be changed by the user. The parameter η_c controls the distribution of offspring genes. It has the default value $\eta_c = 1.0$ in `evortran`, but can also be modified by the user. Smaller values of η_c promote broader exploration, allowing the genes of the offspring to deviate more significantly from the genes of the parent individuals. On the contrary, larger values of η_c lead to offspring genes that are centered more closely to the genes of the parent individuals, which typically yields faster convergence but less exploration of the solution space. Compared to the blend crossover method discussed above, SBX offers a more adjustable and often more efficient trade-off between exploration (searching broadly across the solution space) and exploitation (refining and improving solutions near individuals with high fitness). However, blend crossover requires fewer computation steps and only has a single meta parameter α . Therefore, while SBX is often more effective for detailed local optimization in promising regions of the solution space, blend crossover is simpler and better suited for broad, uniform searches across the entire solution space where less precision is initially required.

2.3.3 Mutation routines

We discuss here the mutation routines that `evortran` provides. Mutation introduces diversity by randomly modifying gene values, helping the GA escape local optima and explore the search space more comprehensively. The available mutation routines are summarized in Table 3. Each

	Kinds	Optional arguments [default values]
uniform	I/F	prob [1/ind%length]
shuffle	I/F	prob [1/ind%length]
gaussian	F	prob [1/ind%length], sigma [1.0]

Table 3: Mutation methods implemented in `evortran`. The first column shows the names of the three mutation methods in `evortran`. The respective functions are labeled in the second column as I, F, or I/F, indicating the type of genes they operate on: I for individuals with integer-valued genes, F for those with floating-point genes, and I/F for functions that can handle both types. The third column shows optional arguments of each routine and their default values.

772 mutation routine operates in-place on a given individual, i.e. it directly modifies the genes of
 773 the individual given as input. After mutation, the fitness of the individual is invalidated by a
 774 call to its internal `reset_fitness()` procedure. This ensures that the next time the fitness
 775 is accessed, it is correctly recalculated using the mutated genes.

776 The *uniform* mutation routine can be applied to both integer and float individuals. Each
 777 gene has an independent probability `prob` (defaulting to `1/ind%length`, where `ind%length`
 778 is the length of the genes of the individual) of being replaced by a new value sampled uni-
 779 formly from the full range of allowable gene values. A main advantage of uniform mutation
 780 is that it introduces new gene values into the population over the whole possible range. It
 781 is therefore particularly useful in early stages of the GA, where the solution space should be
 782 covered broadly without converging prematurely into a local minimum. However, uniform
 783 mutation might be too disruptive at final stages of the GA, when there are solutions that are
 784 already close to the desired (global) optimum, since its coarse nature may modify gene values
 785 far away from suitable values instead of refining them.

786 Also compatible with both integer and float genes is the *shuffle* mutation routine. With the
 787 specified probability `prob` per gene (default `1/ind%length`), each gene switches the place in
 788 the array of genes with another randomly selected gene. In contrast to the uniform mutation
 789 discussed above, shuffle mutation only modifies the order of the gene values, but it does not
 790 introduce new gene values which were not present in the population before. In a GA with
 791 a continuous solution space, it should therefore be combined with a crossover method that
 792 produces new gene values (e.g. blend or sbx crossover) instead of only transferring gene val-
 793 ues from parent to offspring individuals. Since shuffle mutation keeps the gene values, only
 794 altering their positions, the mutation is often less disruptive than uniform mutation and can
 795 maintain some beneficial building blocks. This makes it more suitable for permutation-based
 796 optimization problems, such as scheduling, path finding or ordering tasks. However, it might
 797 lack sufficient exploration power, and it is usually not suitable for problems in which the po-
 798 sitions of the gene values within the sequence are highly structured for good solutions to the
 799 problem at hand.

800 Available only for float individuals, `evortran` offers a third mutation routine called *gaus-*
 801 *sian* mutation. Here, each gene has a chance `prob` to be replaced by a normally distributed
 802 random number with mean given by the gene value to be replaced and standard deviation
 803 `sigma`. This introduces smooth, local variations suitable for continuous optimization prob-
 804 lems. The default value of `sigma` is set to 1.0 because the default range of allowed gene
 805 values is from 0.0 to 1.0, see the discussion in Section 2.2.2. If the actual lower and upper
 806 limits of possible gene values differ from this default, it is advisable to adjust `sigma` accord-
 807 ingly to ensure that the spread of mutation remains appropriate relative to the full range of

possible gene values. Since the mean of the normal distribution is the original gene value itself, Gaussian mutation tends to produce values close to the original, making this method less disruptive than uniform mutation, where the gene value is replaced with a completely random value from the entire allowed range. The argument `sigma` controls the spread of the distribution. A larger value increases variability and allows for more exploratory mutations, whereas a smaller value makes mutations more conservative, favoring fine-tuning. Gaussian mutation is especially useful if the GA has already determined solutions near a good solution in order to explore the local neighborhood efficiently and fine-tune the final solution.

2.3.4 Elitism

Elitism is a common strategy in GAs that ensures the preservation of the best-performing individuals across generations. Its main purpose is to prevent the loss of the best solutions at intermediate stages of the GA due to the stochastic nature of selection, crossover, and mutation. By retaining a subset of the best individuals, elitism promotes convergence and often improves the stability and performance of the GA. However, if the number of elite individuals is too large, it might lead to premature convergence and poor coverage of the solution space.

In `evortran`, elitism is currently implemented in the most simple form. Users can specify a number of elite individuals to be preserved during reproduction. The individuals in the population that have the lowest fitness values are directly appended to the offspring. It is worth noting that this elitism procedure can become computationally significant for large population sizes or when fitness evaluations are costly, as it requires computing the fitness values of all individuals in the population and sorting them based on those values.

2.4 Evolution of a population

We have discussed above how to operate on individuals and populations directly. In principle, a user can define their own GA using these functionalities to their specific needs. However, with a certain optimization task at hand, it is usually more practical to call a function which takes the fitness function as input and performs a whole evolution of a population in order to optimize the fitness function. To this end, `evortran` provides the function `evolve_population`, which corresponds to the next level of abstraction and encapsulates the entire process of evolving a population through the different stages of a GA. This function iteratively applies the four fundamental operations (selection, crossover, mutation, and elitism) until either a maximum number of generations has been reached or a predefined fitness target has been achieved.

This is one of the two interfaces that are most likely to be used by users of `evortran` (with the other one being the `evolve_migration` function discussed in Section 2.5). It allows users to easily apply GAs to their problems with minimal boilerplate code. The only requirement is to implement a user-defined fitness function conforming to the abstract interface described in Section 2.1.1. Once the fitness function is defined, optimization is as simple as calling `evolve_population` with the desired parameters.

The function `evolve_population` is highly flexible, offering a large number of optional arguments that enable customization of the GA, such as gene initialization, selection and mating strategies, mutation behavior, elitism, and output tracking. The whole function declaration is as follows:

```
1 function evolve_population( &
2   pop_size, &
3   gene_length, &
4   fit_func, &
5   lower_lim, &
6   upper_lim, &
```

```

855     7   max_generations, &
856     8   fitness_target, &
857     9   verbose, &
858    10   gene_seed, &
859    11   add_ind, &
860    12   selection, &
861    13   selection_size, &
862    14   tourn_size, &
863    15   wheele_size, &
864    16   elitism, &
865    17   elite_size, &
866    18   mating, &
867    19   offspring_size, &
868    20   offspring_include_elite, &
869    21   mating_prob, &
870    22   blend_alpha, &
871    23   sbx_eta_c, &
872    24   sbx_p_c, &
873    25   uniform_mating_ratio, &
874    26   mutate, &
875    27   mutate_prob, &
876    28   mutate_gene_prob, &
877    29   mutate_gaussian_sigma, &
878    30   fittest_inds_from_gen, &
879    31   pops_from_gen, &
880    32   init_pop, &
881    33   final_pop) result(best_ind)
882    34
883    35   integer, intent(in) :: pop_size
884    36   integer, intent(in) :: gene_length
885    37   procedure(func_abstract) :: fit_func
886    38   real(wp), intent(in), optional :: lower_lim
887    39   real(wp), intent(in), optional :: upper_lim
888    40   integer, intent(in), optional :: max_generations
889    41   real(wp), intent(in), optional :: fitness_target
890    42   logical, intent(in), optional :: verbose
891    43   real(wp), intent(in), optional :: gene_seed
892    44   type(individual), intent(in), optional :: add_ind
893    45   character(len=*), intent(in), optional :: selection
894    46   integer, intent(in), optional :: selection_size
895    47   integer, intent(in), optional :: tourn_size
896    48   integer, intent(in), optional :: wheele_size
897    49   character(len=*), intent(in), optional :: elitism
898    50   integer, intent(in), optional :: elite_size
899    51   character(len=*), intent(in), optional :: mating
900    52   integer, intent(in), optional :: offspring_size
901    53   logical, intent(in), optional :: offspring_include_elite
902    54   real(wp), intent(in), optional :: mating_prob
903    55   real(wp), intent(in), optional :: blend_alpha
904    56   real(wp), intent(in), optional :: sbx_eta_c
905    57   real(wp), intent(in), optional :: sbx_p_c
906    58   real(wp), intent(in), optional :: uniform_mating_ratio
907    59   character(len=*), intent(in), optional :: mutate
908    60   real(wp), intent(in), optional :: mutate_prob
909    61   real(wp), intent(in), optional :: mutate_gene_prob
910    62   real(wp), intent(in), optional :: mutate_gaussian_sigma
911    63   type(individual), intent(out), dimension(:), &

```

```

912     64     allocatable, optional :: fittest_inds_from_gen
913     65     type(population), intent(out), dimension(:), &
914     66     allocatable, optional :: pops_from_gen
915     67     type(population), intent(in), optional :: init_pop
916     68     type(population), intent(out), optional :: final_pop
917     69     type(individual) :: best_ind

```

918 The arguments to this function are:

- 919 – pop_size: Number of individuals in the population.
- 920 – gene_length: Number of gene values in each individual. Should be equal to the di-
921 mension of the fitness function.
- 922 – fit_func: User-defined fitness function following the abstract interface
923 func_abstract given in Section 2.1.1.
- 924 – lower_lim, upper_lim: Limits of the range of possible gene values (defaults are 0.0
925 and 1.0). These optional arguments can only be set together.
- 926 – max_generations: Maximum number of generations to run (default is pop_size).
- 927 – fitness_target: Optimization stops early if this fitness value is reached.
- 928 – verbose: If true, prints evolving summary output during execution.
- 929 – gene_seed: Seed used to initialize gene values of all individuals in the initial popula-
930 tion.
- 931 – add_ind: An individual to insert into the initial population.
- 932 – selection: The selection method, currently possible values are tournament, rank or
933 roulette, see Section 2.3.1 (default is tournament).
- 934 – selection_size: Number of individuals to select (default is pop_size).
- 935 – tourn_size: Given as optional argument tourn_size when tournament selection is
936 used, see Section 2.3.1.
- 937 – wheele_size: Given as optional argument wheele_size if roulette wheele selection
938 is used, see Section 2.3.1.
- 939 – elitism: Elitism mode, where currently only the default option best_fitness is sup-
940 ported, see Section 2.3.4.
- 941 – elite_size: Number of elite individuals to keep (default is 1).
- 942 – mating: The crossover method, currently possible values are one-point, two-point,
943 uniform for both integer and float populations, and additionally blend, and sbx only
944 for float populations (default is one-point).
- 945 – offspring_size: Number of offspring individuals to generate (default is pop_size).
- 946 – offspring_include_elite: Whether to apply elitism, see Section 2.3.4 (default is
947 .true.).
- 948 – mating_prob: The mating probability, see Section 2.3.2 (default is 0.95).
- 949 – blend_alpha: Parameter alpha for blend crossover, see Section 2.3.2 (default is 0.5).
- 950 – sbx_eta_c: Parameter eta_c for simulated binary crossover, see Section 2.3.2 (default
951 is 1.0).
- 952 – sbx_p_c: Parameter p_c for simulated binary crossover, see Section 2.3.2 (default is
953 0.9).
- 954 – uniform_mating_ratio: Parameter ratio for uniform crossover, see Section 2.3.2
955 (default is 0.5).
- 956 – mutate: The mutation method, currently possible values are uniform and shuffle
957 for both integer and float populations, and additionally gaussian only for float popu-
958 lations, see Section 2.3.3. (default is uniform).
- 959 – mutate_prob: Mutation probability (default is 0.1).

- 960 – `mutate_gene_prob`: Probability of mutating each gene if individual is mutated (default
961 is 0.1).
- 962 – `mutate_gaussian_sigma`: Parameter `sigma` for gaussian mutation, see Sec-
963 tion 2.3.3 (default is 1.0).
- 964 – `fittest_inds_from_gen`: Stores the fittest individual from each generation in an
965 array of length `max_generations` if the final achieved fitness value is larger than
966 `fitness_target`. If the GA terminates because a fitness below `fitness_target` has
967 been achieved, the length of the array will be equal to the number of generations that
968 were created up to this point.
- 969 – `pops_from_gen`: If present, stores the entire population at each generation. The user
970 should ensure that sufficient memory is available.
- 971 – `init_pop`: Initial population to start from instead of randomly generating one at the
972 start of the GA.
- 973 – `final_pop`: If present, stores the entire population after the GA has terminated.

974 The return object `best_ind` of the function is the individual with the best fitness that was
975 found during the process. A minimal call of `evolve_population` for a continuous optimiza-
976 tion problem (without specifying the optional arguments) and printing out the minimal value
977 of the fitness function that was found, looks like this:

```

978 1 use evortran__individuals_float, only : individual
979 2 use evortran__evolutions_float, only : evolve_population
980 3
981 4 type(individual) :: best_ind
982 5
983 6 best_ind = evolve_population(1000, 20, func)
984 7 write(*,*) best_ind%get_fitness()
```

985 Here the function `func` with 20 arguments is minimized using a GA with a population size of
986 1000.

987 In some applications, it may be beneficial to adapt the behavior of the GA over time. For
988 example, starting with more exploratory operations such as broad or disruptive crossover and
989 mutation strategies, and gradually transitioning to more fine-grained, exploitative methods as
990 the search progresses. `evortran` supports this type of staged evolution by allowing multiple
991 chained calls to `evolve_population`, each with different parameters. Between calls, one
992 can transfer either only the best individual using the `add_ind` argument or reuse the entire
993 final population from one stage as the initial population for the next via the `final_pop` and
994 `init_pop` arguments. This modular design enables the construction of highly flexible and
995 dynamic GAs that evolve their strategies over the course of the optimization process.

996 2.5 Migration of populations

997 In addition to the function `evolve_population`, `evortran` provides the function
998 `evolve_migration`, which operates on multiple populations simultaneously. This repre-
999 sents the highest abstraction level in the user-interface of `evortran`. Specifically, the func-
1000 tion `evolve_migration` evolves multiple populations independently over a series of *epochs*,
1001 where each epoch consists of a number of generations. After each epoch, individuals may mi-
1002 grate between populations. This form of co-evolution can help to maintain genetic diversity
1003 by reducing premature convergence, explore multiple areas of the search space concurrently,
1004 and to increase robustness by yielding several good-fit individuals (each corresponding to lo-
1005 cal minima of the fitness function and potentially sufficiently good solutions to the problem

at hand). Moreover, this approach naturally allows for performant and straightforward parallelization, as each population can be evolved independently before migration steps are applied, as is discussed in more detail in Section 2.6.

As in `evolve_population`, users can configure the GA, including selection, crossover, mutation, elitism, and stopping criteria. Additional parameters control the migration behavior. The interface of the function is:

```

1012 1 function evolve_migration( &
1013 2   pop_number, &
1014 3   epoches, &
1015 4   pop_size, &
1016 5   gene_length, &
1017 6   fit_func, &
1018 7   migration, &
1019 8   migration_size, &
1020 9   migration_order, &
1021 10  lower_lim, &
1022 11  upper_lim, &
1023 12  max_generations, &
1024 13  fitness_target, &
1025 14  verbose, &
1026 15  gene_seed, &
1027 16  selection, &
1028 17  selection_size, &
1029 18  tourn_size, &
1030 19  wheele_size, &
1031 20  elitism, &
1032 21  elite_size, &
1033 22  mating, &
1034 23  mating_prob, &
1035 24  blend_alpha, &
1036 25  sbx_eta_c, &
1037 26  sbx_p_c, &
1038 27  uniform_mating_ratio, &
1039 28  offspring_size, &
1040 29  offspring_include_elite, &
1041 30  mutate, &
1042 31  mutate_prob, &
1043 32  mutate_gene_prob, &
1044 33  mutate_gaussian_sigma, &
1045 34  add_ind, &
1046 35  fittest_inds_final_pops &
1047 36  ) result(best_ind)
1048 37
1049 38 integer, intent(in) :: pop_number
1050 39 integer, intent(in) :: epoches
1051 40 integer, intent(in) :: pop_size
1052 41 integer, intent(in) :: gene_length
1053 42 procedure(func_abstract) :: fit_func
1054 43 character(len=*), intent(in), optional :: migration
1055 44 integer, intent(in), optional :: migration_size
1056 45 character(len=*), intent(in), optional :: migration_order
1057 46 real(wp), intent(in), optional :: lower_lim
1058 47 real(wp), intent(in), optional :: upper_lim
1059 48 integer, intent(in), optional :: max_generations
1060 49 real(wp), intent(in), optional :: fitness_target

```

```

1061 50  logical, intent(in), optional :: verbose
1062 51  real(wp), intent(in), optional :: gene_seed
1063 52  character(len=*), intent(in), optional :: selection
1064 53  integer, intent(in), optional :: selection_size
1065 54  integer, intent(in), optional :: tourn_size
1066 55  integer, intent(in), optional :: wheele_size
1067 56  character(len=*), intent(in), optional :: elitism
1068 57  integer, intent(in), optional :: elite_size
1069 58  character(len=*), intent(in), optional :: mating
1070 59  real(wp), intent(in), optional :: mating_prob
1071 60  real(wp), intent(in), optional :: blend_alpha
1072 61  real(wp), intent(in), optional :: sbx_eta_c
1073 62  real(wp), intent(in), optional :: sbx_p_c
1074 63  real(wp), intent(in), optional :: uniform_mating_ratio
1075 64  integer, intent(in), optional :: offspring_size
1076 65  logical, intent(in), optional :: offspring_include_elite
1077 66  character(len=*), intent(in), optional :: mutate
1078 67  real(wp), intent(in), optional :: mutate_prob
1079 68  real(wp), intent(in), optional :: mutate_gene_prob
1080 69  real(wp), intent(in), optional :: mutate_gaussian_sigma
1081 70  type(individual), intent(in), optional :: add_ind
1082 71  type(individual), intent(out), dimension(:), allocatable, &
1083 72      optional :: fittest_inds_final_pops
1084 73  type(individual) :: best_ind
1085 74
1086 75  end function evolve_migration

```

1087 This function contains the following arguments in addition to the ones of the function
1088 `evolve_population` that were already discussed in Section 2.4:

- 1089 – `pop_number`: The number of populations evolved in parallel.
- 1090 – `epoches`: The number of epochs.
- 1091 – `migration`: The type of migration that is carried out after each epoche. The currently
1092 only implemented option is `rank`, where the best-fit individuals are selected to migrate
1093 to other populations.
- 1094 – `migration_size`: The number of individuals to migrate from each population per
1095 epoch.
- 1096 – `migration_order`: The migration order that determines the population to which in-
1097 dividuals migrate from one to the other. Assuming that the populations are labeled by
1098 $i = 1, \dots, N$, with N being equal to `migration_size`, possible options are (default is
1099 `random`):
 - 1100 LR: The individuals from population i migrate to population $i + 1$, except the indi-
1101 viduals from population $i = N$ migrate to population $i = 0$.
 - 1102 RL: The individuals from population i migrate to population $i - 1$, except the indi-
1103 viduals from population $i = 1$ migrate to population $i = N$.
 - 1104 random: For each population, after each epoch, the target population is randomly
1105 selected. In this case it is possible that individuals from different populations mi-
1106 grate to the same target population.
- 1107 – `fittest_inds_final_pops`: Stores the best-fit individuals from each population
1108 upon completion.

1109 The return value `best_ind` is the best-fit individual found across all populations after the
1110 GA completes, either by reaching the fitness target or by reaching the maximum number of
1111 epochs.

2.6 Parallelization using OpenMP

GAs are particularly well-suited for parallelization due to their inherently population-based structure. Since individuals in a population evolve mostly independently during fitness evaluation, selection, and crossover, many of the operations in a GA can be efficiently distributed across multiple CPU cores.⁴ This allows significant speed-up when tackling computationally intensive optimization problems if a sufficient number of CPU cores are available.

`evortran` supports parallel execution on multi-core CPUs through the OpenMP application programming interface. OpenMP is a widely adopted standard for shared-memory parallel programming in Fortran, C, and C++, which enables easy parallelization of loops and code sections through compiler directives that are supported by many Fortran compilers. `evortran` uses `fpm` as build system, where OpenMP support is activated by adding it as a meta-package in the `fpm.toml` configuration file, as discussed in more detail in Section 3.1.2.

The way parallelization is applied in `evortran` depends on the abstraction level used by the user. When operating at the level of individual populations (e.g. via `evolve_population`), `evortran` parallelizes internal loops over individuals. For instance, fitness evaluation, selection, and offspring generation can each be executed in parallel across individuals within a population. The user does not need to modify the runtime call to benefit from this. At the higher level of abstraction using `evolve_migration`, `evortran` evolves multiple populations in parallel. In this case, the outer loop over populations is parallelized, which is often more efficient than parallelizing individual operations, because fewer threads need to be launched and managed, thus reducing overhead. When selecting how many CPU cores to use, it can be beneficial to consider these differences: With `evolve_population`, performance may improve if the number of individuals in the population is a multiple of the available CPU cores. With `evolve_migration`, best efficiency is typically achieved when the number of populations matches or is a multiple of the number of available cores.

To ensure correctness during parallel execution, the user must make sure that the custom fitness function is thread-safe, i.e. it should not depend on or modify shared state in a non-synchronized manner. All internal components of `evortran` that are involved in parallel execution, such as random number generation and sorting routines, are implemented to be thread-safe, as will be discussed in more detail in Section 2.7. The number of threads used during execution can be controlled by the user via the `OMP_NUM_THREADS` environment variable at compile time (see also the discussion in Section 3.1). While this must be set before compilation, this is not a major limitation in practice, since `evortran` can be compiled in just a few seconds.

2.7 Core utilities and numerical tools

This section discusses essential building blocks that underpin the operation of GAs, and their implementation in `evortran`. These core utilities include the pseudo-random number generators (PRNGs), which are fundamental to introduce randomness into the algorithm, and sorting routines, which are crucial for implementing selection mechanisms based on fitness values of the individuals. In addition to these core components, `evortran` also includes a numerical interpolation module that can be valuable for regression or surrogate modeling tasks.

⁴The suitability of GAs for parallelization is reduced in special cases where operations (such as the fitness function or the selection procedure) depend not only on an individual's genes, but also collectively on the genes of multiple or all individuals in the population. Such global dependencies introduce synchronization constraints that make parallel execution less efficient or even impossible. These cases are not considered in this paper. In `evortran`, users can disable parallelization if such dependencies are required for a specific application.

2.7.1 Pseudo-random number generation

Pseudorandom number generation is a central component in GAs, as it governs stochastic processes such as initialization, mutation, selection, and crossover. In parallelized GAs, the PRNG desirably is thread-safe to avoid race conditions and ensure reproducibility. `evortran` provides two options for generating random numbers.

The default and recommended PRNG in `evortran` is a thread-safe implementation of the *Mersenne Twister algorithm* [53,54] (specifically, the 64-bit variant MT19937-64). The implementation contained in `evortran` is adapted from Ref. [55]. The adaptation integrates it with `evortran`'s internal real kind working precision (`wp`) and modifies it for parallel execution using OpenMP. Each OpenMP thread is assigned its own instance of the PRNG and initialized with a unique seed at the start of the program. This design ensures that random number generation is thread-safe, and that the results of the GA are deterministic and reproducible in parallel execution. Moreover, the performance is competitive compared to Fortran intrinsic PRNGs, making it suitable for large-scale stochastic sampling.⁵

Alternatively, `evortran` offers the option to generate random integer and float numbers based on the Fortran intrinsic function `random_number()`. While slightly faster in sequential execution, this option is not thread-safe, since concurrent calls by multiple threads result in race conditions. As a consequence, results are no longer deterministic when executed in parallel. This option is useful when strict reproducibility is not required and performance is paramount. However, typically the thread-safe implementation of the Mersenne Twister is strongly recommended.

Before using any functionality of the `evortran` library, the PRNG must be explicitly initialized. This is done by calling the subroutine `initialize_rands`. For instance, to use the Mersenne Twister PRNG, one has to call:

```
1 use evortran__prng_rand, only : initialize_rands
2
3 call initialize_rands(mode='twister', seed=0)
```

The second argument `seed` is an optional integer argument that sets an initial seed value for the Mersenne Twister PRNG (the default value is 0). Alternatively, to use the Fortran intrinsic PRNG function, one has to call:

```
1 call initialize_rands(mode='intrinsic')
```

Using this mode, the optional `seed` argument is ignored. If this routine is not called, the program will result in a runtime error if `evortran` was compiled in `DEBUG` mode, or in undefined behavior if compiled without it. The compilation flags, including enabling or disabling `DEBUG` mode, are discussed in detail in Section 3.1.

2.7.2 Sorting methods

Sorting individuals based on their fitness values is a central operation in GAs, especially for ranking-based selection methods and elitism. In `evortran`, sorting is used internally to determine the ordering of individuals according to their fitness, and the library provides two efficient and thread-safe sorting algorithms that are designed to be called in parallel using OpenMP.

The first sorting option is a parallel *merge sort* algorithm, which is the default sorting method in `evortran`. It is based on the merge sort implementation from the `orderpack`

⁵The Merseene Twister algorithm is also used in the modernized `fpm` version of `Pikaia` [50], whereas the original version uses the “Minimal standard” PRNG [56].

library [57]. The version used in `evortran` has been adapted from a parallel implementation provided in a public github repository [58], and modified for compatibility with the real working precision kind and data structures used in the library. The second available option is *quick sort*, implemented using a recursive algorithm adapted from a publicly available Fortran quicksort implementation [59]. Like the merge sort routine, it is thread-safe, allowing concurrent execution in OpenMP-parallelized regions of user code.

Users can explicitly select the sorting algorithm used by `evortran` by calling the subroutine `set_rank_method` with the desired mode:

```
1 use evortran__sorting_ranking, only : set_rank_method
2
3 ! Select merge sort
4 call set_rank_method(mode='merge')
5
6 ! Or select quicksort
7 call set_rank_method(mode='quick')
```

In typical use cases within `evortran`, both sorting methods were found to exhibit similar run-time performance. However, for specific use cases of the GA the user may wish to specifically chose one of the two options. Merge sort guarantees $\mathcal{O}(n \log n)$ time complexity in all cases and is stable (preserves relative ordering of equal elements), which can be advantageous in some applications. Quick sort may be faster in practice due to lower constant factors, but its performance can degrade to $\mathcal{O}(n^2)$ in the worst case, although this is rare with randomized pivoting. Because of its more predictable performance and stability, merge sort is the default sorting method in `evortran`.

2.7.3 Function interpolation

While not a core component of GAs, `evortran` includes a utility for performing cubic spline interpolation, which can be valuable in a range of optimization contexts where functions are approximated via discretization and a finite number of points. This functionality is implemented through pure Fortran procedures, making the routines thread-safe and thus suited for parallel execution. In GA applications, spline interpolation can be useful when the fitness function is based on experimental or computational data sampled at discrete values. Instead of restricting the optimization to those discrete points, a spline-based interpolant can provide a smooth and continuous approximation of the function, allowing for evaluations at arbitrary points in the parameter space. Additionally, spline interpolation may be helpful in hybrid optimization strategies where gradient-free methods like GA are combined with smooth approximations to facilitate local refinement or sensitivity analysis, by enabling smooth representations of otherwise discrete data.

The following code snippet demonstrates how to use the cubic spline interpolation feature to approximate the value of a function between a set of known data points:

```
1 use evortran__util_kinds, only : wp
2 use evortran__util_interp_spline, only : spline_construct
3 use evortran__util_interp_spline, only : spline_getval
4
5 integer, parameter :: n = 4 ! Number of known points
6 real(wp) :: x(n)           ! Array of x-values
7 real(wp) :: y(n)           ! Corresponding y-values = f(x)
8 real(wp) :: b(n)           ! Spline coefficient array
9 real(wp) :: c(n)           ! Spline coefficient array
10 real(wp) :: d(n)           ! Spline coefficient array
```

```

1244 11 real(wp) :: xi                ! Point at which to evaluate the
1245    spline
1246 12 real(wp) :: yi                ! Interpolated value at xi
1247 13
1248 14 ! Define interpolation points: f(x) = x^2
1249 15 x = [1.0e0_wp, 2.0e0_wp, 3.0e0_wp, 4.0e0_wp]
1250 16 y = [1.0e0_wp, 4.0e0_wp, 9.0e0_wp, 16.0e0_wp]
1251 17
1252 18 xi = 2.5e0_wp ! Target x-value for interpolation
1253 19
1254 20 ! Compute spline coefficients based on input data
1255 21 call spline_construct(x, y, b, c, d, n)
1256 22
1257 23 ! Evaluate the spline at xi = 2.5
1258 24 yi = spline_getval(xi, x, y, b, c, d, n)

```

Specifically, this example interpolates the function $f(x) = x^2$ using four data points. After constructing the spline coefficients using `spline_construct`, it evaluates the interpolated value at a midpoint $x_i = 2.5$ using `spline_getval`.

1262 3 User instructions

1263 In this section we give practical guidance on how to get started with `evortran`. In Section 3.1,
 1264 we explain how to install the library and its dependencies. In Section 3.2 we introduce the
 1265 key functionalities of `evortran` and demonstrates how to develop a custom GA.

1266 3.1 Installation

1267 To use `evortran`, a few prerequisites must be installed on the system. These are standard
 1268 tools in modern Fortran development and are typically easy to set up on most platforms.

1269 3.1.1 Prerequisites

1270 `evortran` is written in modern Fortran using an object-oriented user interface. The recom-
 1271 mended compiler to build `evortran` is the GNU Fortran compiler `gfortran`.⁶ On Ubuntu or
 1272 Debian-based systems `gfortran` can be installed with:

```

1273 1 sudo apt update
1274 2 sudo apt install gfortran

```

1275 `evortran` was developed and tested using the versions 11, 12 and 13 of `gfortran`.

1276 For the build process and for managing dependencies, `evortran` uses the Fortran Package
 1277 Manager `fpm` [51]. There are various ways to install `fpm`, for instance, using package managers
 1278 like `pip`,

```

1279 1 pip install fpm

```

1280 or `conda`,

⁶While other modern Fortran compilers exist, they are either not yet compatible with key features used in `evortran` or lack integration with the Fortran Package Manager. `lfortran`, currently in alpha stage and under active development, still lacks full support for OpenMP. Moreover, LLVM `flang` is not yet widely supported by `fpm` (as of version 0.12.0).

```
1281 1 conda config --add channels conda-forge
1282 2 conda create -n fpm fpm
1283 3 conda activate fpm
```

1284 One can also install fpm by downloading a binary for the latest stable release which are avail-
1285 able for Windows, MacOS, and Linux, or build fpm from source, see Ref. [60].

1286 3.1.2 Building evortran

1287 With gfortran and fpm installed, one can build evortran. The first step is to clone the
1288 repository and to navigate to the evortran directory:

```
1289 1 git clone https://gitlab.com/thomas.biekoetter/evortran
1290 2 cd evortran
```

1291 Then one has to source fpm environment variables which define compiler flags and the number
1292 of OpenMP threads that should be used. This can be done by sourcing one of two provided
1293 scripts. Running

```
1294 1 source exports_debug.sh
```

1295 sets compiler flags appropriate for debugging, including options that enable stricter compile-
1296 time checks. More importantly, it activates a wide range of runtime argument checks specific
1297 to evortran that help ensure correct usage of the library. These checks are only available
1298 in debug mode and are strongly recommended while setting up or developing the GA. For
1299 performance runs, one should instead run

```
1300 1 source exports_run.sh
```

1301 which disables these runtime checks through preprocessor directives, activates compiler op-
1302 timization (`-O3 -march=native`) and omits array out-of-bounds checking. This results in
1303 significantly faster execution but should only be used once the implementation is known to
1304 be correct. In both cases, the number of threads used for parallel regions is controlled by the
1305 `OMP_NUM_THREADS` environment variable, which is set to 8 by default in both files but can be
1306 modified as needed.

1307 As was already mentioned in Section 2.1.2, by default the real kind working preci-
1308 sion `wp` corresponds to double precision, as defined in the module `evortran_util_kinds`
1309 using `selected_real_kind(15, 307)`. This corresponds to a precision of at least
1310 15 significant digits. The precision can be upgraded to quadruple precision, using
1311 `selected_real_kind(30, 4931)`, by setting the `QUAD` preprocessor flag. In this case,
1312 evortran operates with at least 30 significant digits. The real kind precision can be changed
1313 at compile time by appending `-DQUAD` to the `FPM_FFLAGS` environment variable, for example:

```
1314 1 export FPM_FFLAGS="$FPM_FFLAGS -DQUAD"
```

1315 Alternatively, the user can add the `-DQUAD` flag directly to the `exports_debug.sh` or
1316 `exports_run.sh` files, where `FPM_FFLAGS` is defined. These files should be sourced before
1317 compilation to ensure the correct build configuration is used, as discussed above.

1318 Once the environment variables are sourced, one can compile the project with:

```
1319 1 fpm build
```

The build process is handled by `fpm`, which automatically downloads and compiles all required dependencies. These include the meta-dependency `openmp`, which enables multithreaded parallelization, and a Fortran error-handling module:

```
1 [dependencies]
2 openmp = "*"
3 error-handling = { git = "https://github.com/SINTEF/
  fortran-error-handling.git", tag = "v0.2.0" }
```

In addition, dev-dependencies are specified in the `fpm.toml` file which are used in example applications and test programs:

```
1 [dev-dependencies]
2 csv-fortran = { git = "https://github.com/jacobwilliams/
  csv-fortran.git" }
3 pikaia = { git = "https://github.com/jacobwilliams/pikaia.
  git", tag = "2.0.0" }
```

The package `pikaia` is another GA framework implemented in Fortran [49,50]. It is included as a dev-dependency because it is used for comparisons with `evortran` in example applications, see Section 4.1.2 and Section 4.1.4. The package `csv-fortran` is used for exporting data to csv-files.

To use `evortran` as a dependency in another `fpm` project, one can simply add the following entry to the `fpm.toml` file of the project:

```
1 [dependencies]
2 evortran = { git = "https://gitlab.com/thomas.biekoetter/
  evortran" }
```

This makes it straightforward to integrate `evortran` into existing programs and libraries.

After building `evortran` one can install the compiled executables that are contained in the `app` folder locally by running:

```
1 fpm install
```

This command copies the built executables to a default location, typically `~/local/bin`, and the compiled module files are copied to `~/local/include`. If these paths are included in the `PATH` environment variable, one can run the executable from any directory without having to reference the full build path. If needed, you can change the installation prefix using the `-prefix` flag.

3.1.3 Running tests and applications

`evortran` includes a set of test programs to verify that the library is working correctly. To run a specific test program, use the `fpm test` command followed by the name of the test program:

```
1 fpm test <name_of_test_program>
```

This will execute the selected test and output the results to the terminal. To view the available test programs, navigate to the `test` directory and its sub-directories.

Similarly, `evortran` provides example application programs located in the `app` directory, which demonstrate how to use `evortran` in practical scenarios. To run a specific application, one can use the `fpm run` command followed by the name of the application program:

```
1361      1 fpm run <name_of_app_program>
```

1362 This will compile and execute the chosen application, displaying its output in the terminal.
 1363 One can explore the available application programs by browsing the app directory and its
 1364 sub-folders. These applications include several of the examples discussed in Section 4. These
 1365 are intended to be a convenient starting point for understanding the library and for developing
 1366 new programs that use evortran.

1367 3.2 Quick start: basic usage and main features

1368 To help new users quickly get started with evortran, this section presents a minimal yet
 1369 complete example that demonstrates how to use the library to solve an optimization problem.
 1370 The example program `quick_start` is located in the app directory and can be executed using
 1371 the following command:

```
1372      1 fpm run quick_start
```

1373 This program uses a GA to find the global minimum of the well-known *Rosenbrock function* [61], which is commonly used as a benchmark for optimization algorithms. The Rosenbrock function is defined as

$$f(x, y) = (a - x)^2 + b(y - x^2)^2, \quad (7)$$

1376 where $a = 1$ and $b = 100$ are parameters that define the shape of the function. The function has a global minimum at $(x, y) = (a, a^2) = (1, 1)$, where $f(a, a^2) = 0$. The Rosenbrock function is a suitable test case for optimization algorithms, as it poses challenges related to convergence to the global minimum since the minimum is located inside a long, narrow, parabolic-shaped flat valley. The source code for this example is the following:

```
1381      1 program quick_start
1382      2
1383      3 use evortran__util_kinds, only : wp
1384      4 use evortran__individuals_float, only : individual
1385      5 use evortran__evolutions_float, only : evolve_population
1386      6 use evortran__prng_rand, only : initialize_rands
1387      7
1388      8 implicit none
1389      9
1390     10 type(individual) :: best_ind
1391     11 real(wp) :: x
1392     12 real(wp) :: y
1393     13
1394     14 real(wp), parameter :: a = 1.0e0_wp
1395     15 real(wp), parameter :: b = 1.0e2_wp
1396     16 real(wp), parameter :: xmin = -2.0e0_wp
1397     17 real(wp), parameter :: xmax = 2.0e0_wp
1398     18 real(wp), parameter :: ymin = -1.0e0_wp
1399     19 real(wp), parameter :: ymax = 3.0e0_wp
1400     20
1401     21 call initialize_rands(mode='twister')
1402     22
1403     23 best_ind = evolve_population(  &
1404     24       100, 2, rosenbrock,  &
1405     25       mating='blend',  &
```

```

1406      26      elite_size=1, &
1407      27      fitness_target=1.0e-10_wp, &
1408      28      mutate='gaussian', &
1409      29      mutate_prob=0.5e0_wp, &
1410      30      mutate_gene_prob=0.5e0_wp, &
1411      31      mutate_gaussian_sigma=1.0e-3_wp)
1412      32
1413      33      call get_xy(best_ind%genes, x, y)
1414      34
1415      35      write(*,*) 'Rosenbrock function:'
1416      36      write(*,*) ' Minimum at x, y =', x, y
1417      37      write(*,*) ' f(x,y) =', best_ind%get_fitness()
1418      38
1419      39      contains
1420      40
1421      41      pure subroutine rosenbrock(ind, f)
1422      42
1423      43      class(individual), intent(in) :: ind
1424      44      real(wp), intent(out) :: f
1425      45
1426      46      real(wp) :: x
1427      47      real(wp) :: y
1428      48
1429      49      call get_xy(ind%genes, x, y)
1430      50
1431      51      f = (a - x)**2 + b * (y - x**2)**2
1432      52
1433      53      end subroutine rosenbrock
1434      54
1435      55      pure subroutine get_xy(genes, x, y)
1436      56
1437      57      real(wp), intent(in) :: genes(2)
1438      58      real(wp), intent(out) :: x
1439      59      real(wp), intent(out) :: y
1440      60
1441      61      x = xmin + genes(1) * (xmax - xmin)
1442      62      y = ymin + genes(2) * (ymax - ymin)
1443      63
1444      64      end subroutine get_xy
1445      65
1446      66      end program quick_start

```

1447 The program illustrates the key components needed to define and solve an optimization prob-
 1448 lem using evortran:

- 1449 – The program starts by importing the relevant modules and defining parameters for the
 1450 Rosenbrock function and the domain of the variables x and y .
- 1451 – The pseudo-random number generator is initialized with the Mersenne Twister algo-
 1452 rithm.
- 1453 – The call to `evolve_population` is the main entry point for the optimization. Here, we
 1454 define:
 - 1455 – A population size of 100 and gene length 2 (for variables x and y),
 - 1456 – The objective function `rosenbrock` as the fitness function,
 - 1457 – Blend crossover as mating method, and Gaussian mutation,
 - 1458 – Elitism with one elite individual per generation,
 - 1459 – A termination criterion based on reaching a fitness value below 10^{-10} .

1460 – The fitness function is defined as a pure subroutine taking an individual and returning
 1461 the value of the Rosenbrock function.⁷
 1462 – The helper subroutine `get_xy` rescales the genes values from the normalized interval
 1463 $[0, 1]$ to the domain $-2 \leq x \leq 2$ and $-1 \leq y \leq 3$ in which the global minimum should
 1464 be determined by the algorithm.
 1465 – Finally, the location of the found minimum and the corresponding value of the Rosen-
 1466 brock function is printed.
 1467 Executing this example yields the output:

```
1468 1  Rosenbrock function:
1469 2   Minimum at x, y =  0.99996858723522219
1470                      0.99993706186036069
1471 3   f(x,y) =      9.8805221531614218E-010
```

1472 This demonstrates that `evortran` successfully locates the global minimum of the Rosenbrock
 1473 function with high accuracy.

1474 Users can adapt this minimal example to define and optimize their own objective functions
 1475 by simply modifying the fitness function and adjusting the meta-parameters of the GA accord-
 1476 ingly. Instead of defining the fitness function inside of the main program after the `contains`
 1477 statement, one can also define the fitness function in a separate module and import the func-
 1478 tion at the beginning of the program.

1479 3.3 Using `evortran` from Python

1480 To increase accessibility and broaden the potential user base, a Python interface to the core
 1481 optimization routines of `evortran` is provided through a separate Fortran `fpm` package called
 1482 `pyevortran`. This interface allows users to take advantage of the performance of Fortran-
 1483 based GAs while working within Python environments.

1484 The `pyevortran` package is a minimal Fortran project that uses `evortran` as a de-
 1485 pendency. It contains only two modules: the module `pyevortran__evolutions_float`
 1486 provides a C-binding wrapper for the `evolve_population` routine, and the mod-
 1487 ule `pyevortran__migrations_float` provides a C-binding wrapper for the
 1488 `evolve_migration` routine. So far only the routines acting on float populations are
 1489 implemented. The two routines are compiled into a shared library which is then used by
 1490 the Python package `pyevortran` that is installed using `pip`. Within this Python package,
 1491 the shared library is accessed using Python's `ctypes` module to expose the two functions
 1492 `evolve_population` and `evolve_migration`. These functions can be called from Python
 1493 to optimize arbitrary Python functions of the form $f(x)$, where x is a NumPy array.

1494 The Python interface currently supports only the two mentioned high-level optimization
 1495 routines. Nevertheless, these routines allow the use of a variety of GA configurations by spec-
 1496 ifying optional arguments, just as in the native Fortran implementation. Another limitation to
 1497 note is performance: when using the Python interface, the fitness function is typically written
 1498 in Python and may run significantly slower than a compiled Fortran equivalent. If the evalu-
 1499 ation of the fitness function dominates runtime of the GA, it may be worthwhile to translate
 1500 the function into Fortran and use the native `evortran` package for optimal performance.

1501 For installation, the `pyevortran` interface requires a Python v.3 installation, the
 1502 `gfortran` Fortran compiler, and `fpm` version $\geq 0.12.0$, as earlier versions do not support
 1503 building shared libraries. The version of `fpm` currently distributed via PyPI is outdated (cur-
 1504 rently version 0.10.0) and will not work. To install a suitable version of `fpm`, one can download

⁷Recall that, unlike many other GA frameworks which maximize the fitness function, `evortran` minimizes it, such that the Rosenbrock function is implemented as shown in Eq. (7).

1505 a recent binary from the GitHub releases page [60], make it executable, and move it to a di-
1506 rectory in the system's PATH, e.g.:

```
1507     1 chmod +x fpm  
1508     2 mv fpm ~/.local/bin/
```

1509 In addition, `patchelf` must be installed to embed runtime library paths (RPATH) into the
1510 shared libraries, ensuring that Python can find them at runtime without needing to manually
1511 set `LD_LIBRARY_PATH`. On Debian-based systems, `patchelf` can be installed with:

```
1512     1 sudo apt install patchelf
```

1513 With the above mentioned prerequisites installed, one can proceed to install `pyevortran`.
1514 The first step is to clone the repository and navigate to its main folder:

```
1515     1 git clone https://gitlab.com/thomas.biekoetter/pyevortran  
1516     2 cd pyevortran
```

1517 Then one must source one of two provided environment setup scripts. As for `evortran`, see
1518 the discussion in Section 3.1.2, the script `exports_debug.sh` is intended for development
1519 and enables runtime checks and assertions, while `exports.sh` is optimized for production
1520 use by enabling compiler optimizations and disabling checks. These scripts also set up the
1521 number of OpenMP threads. To use the debug version, run:

```
1522     1 source exports.debug.sh
```

1523 Alternatively, to use the optimized configuration, run:

```
1524     1 source exports.sh
```

1525 Once the environment is configured, `pyevortran` can be built and installed with:

```
1526     1 make pyevortran
```

1527 The makefile invokes `fpm` to build the shared library, uses `pip` to install the Python wrapper
1528 into the current environment, and finally applies `patchelf` to embed the necessary RPATHs
1529 into the shared libraries. After successful installation, users can import `pyevortran` in Python
1530 and use the `evolve_population` and `evolve_migration` functions to apply GAs to their
1531 own objective functions.

1532 To test the installation, and to demonstrate the usage of `pyevortran`, a simple test pro-
1533 gram `test_rastrigin.py` is provided in the `python/test` folder:

```
1534     1 import numpy as np  
1535     2 from pyevortran.evolutions import evolve_population  
1536     3  
1537     4 A = 10  
1538     5 def rastrigin(x):  
1539     6     return A * len(x) + np.sum(x**2 - A * np.cos(2 * np.pi * x))  
1540     7  
1541     8  
1542     9 print()  
1543    10 print("Minimizing Rastrigin function:")
```

```

1544     10 print()
1545     11 for dim in range(2, 11):
1546         12     print("    Number of dimensions =", dim)
1547         13     xmin = evolve_population(
1548             14         rastrigin, dim,
1549             15         pop_size=1000,
1550             16         lower_lim=-5.12, upper_lim=5.12,
1551             17         max_generations=1000,
1552             18         fitness_target=1e-9, verbose=False,
1553             19         selection="rank", selection_size=100,
1554             20         elite_size=100)
1555         21     print("    Minimum at xmin =", xmin)
1556         22     print("    f(xmin) =", rastrigin(xmin))
1557         23     print()

```

1558 This script demonstrates the use of the `evolve_population` function from the Python interface to minimize the Rastrigin function, see Section 4.1.1 for details. The script performs minimization for dimensions ranging from two to ten and prints both the location of the minima and the corresponding function values. We note that only the first two arguments, the fitness function (`rastrigin`) and the dimensionality of the problem (`dim`), are required. All other arguments are optional and allow the user to specify GA parameters such as population size, selection strategy, elite size, and termination criteria.

1565 4 Example applications

1566 To demonstrate the flexibility and performance of `evortran`, this section presents several example applications ranging from standard mathematical benchmarks to physics-motivated use cases. In Section 4.1 we discuss the minimization of common multimodal test functions that are frequently used to evaluate optimization algorithms. Next, in Section 4.2 we showcase two realistic applications from theoretical physics. First, we present a fit of a beyond-the-Standard-Model (BSM) theory with an extended Higgs sector against data from the Large Hadron Collider (LHC) in Section 4.2.1. Afterwards, we show how `evortran` can be used to reconstruct a stochastic gravitational wave background predicted by a cosmological phase transition in the early Universe from mock data of the Laser Interferometer Space Antenne (LISA) in Section 4.2.2.

1576 4.1 Minimizing multimodal benchmark functions

1577 Multimodal test functions are commonly used in the evaluation and benchmarking of optimization algorithms, particularly GAs, due to their complex landscapes characterized by multiple local minima. Successfully identifying the global minimum of such functions is a core strength of GAs. In this subsection, we use `evortran` to minimize several standard multimodal functions to demonstrate its performance and to serve as templates that can be adapted by the user to new optimization problems.

1583 4.1.1 Rastrigin function

1584 The Rastrigin function [62–64] is a well-known and widely used multimodal benchmark function in global optimization. It is particularly challenging for optimization algorithms due to its highly repetitive landscape filled with many local minima. This makes it an excellent test function for GAs to locate the globally best solution under the presence of many sub-optimal




Figure 1: Left: Surface plot of the $n = 2$ dimensional Rastrigin function with $A = 10$ in the domain $x_{1,2} \in [-5.12, 5.12]$. Right: Number of calls to the Rastrigin function against the number of dimensions n until the global minimum has been determined with a function value $f_{\min} < 10^{-10}$ using the example application `benchmark_rastrigin`.

1588 candidate solutions. The Rastrigin function is defined as

$$f(x_i) = A \cdot n + \sum_{i=1}^n [x_i^2 - A \cdot \cos(2\pi x_i)], \quad (8)$$

1589 where $A = 10$ and $x_i = x_1, \dots, x_n$, with n being the number of dimensions. The global
 1590 minimum is located at $x_i = 0$ for all i , where the function reaches the minimum value
 1591 $f(x_i = 0) = 0$. The Rastrigin function is typically minimized in the domain $x_i \in [-5.12, 5.12]$.
 1592 The left plot of Fig. 1 shows a surface plot of the Rastrigin function in two dimensions.

1593 To demonstrate the capabilities of `evortran`, we performed a series of optimization
 1594 runs using the `benchmark_rastrigin` example program included in the app folder of the
 1595 repository. In this benchmark, the goal is to find the global minimum with a precision of
 1596 $f_{\min} < 10^{-10}$ for dimensions ranging from $n = 2$ to $n = 20$. The GA is executed for each
 1597 dimensionality separately, and the number of fitness function evaluations until convergence,
 1598 as well as the final minimum value of the function found, are stored in a CSV file. The core
 1599 of the `benchmark_rastrigin` program consists of a loop over the number of dimensions
 1600 (`currdim`) in which the `evolve_population` function is called:

```

1601     1 best_ind = evolve_population( &
1602     2     10000, currdim, rastrigin, &
1603     3     mating='blend', &
1604     4     elite_size=100, &
1605     5     lower_lim=-5.12e0_wp, &
1606     6     upper_lim=5.12e0_wp, &
1607     7     selection='rank', &
1608     8     selection_size=100, &
1609     9     fitness_target=1.0e-10_wp, &
1610    10     mutate_prob=0.1e0_wp, &
1611    11     mutate_gene_prob=0.1e0_wp)

```

1612 Here, a large population size of 10,000 individuals and a relatively high number of elite in-
 1613 dividuals (100) are used to ensure robust exploration across all dimensions. The GA uses

blend crossover, rank-based selection, and gaussian mutation, see Section 2.3 for details. The GA terminates once a fitness value of 10^{-10} has been found, which is set via the argument `fitness_target`.⁸

Despite using the same GA settings for all dimensions, this basic setup is sufficient to reliably identify the global minimum of the Rastrigin function in all tested dimensions. The performance could be further optimized by tuning the GA parameters individually for each dimension (for example, using smaller population sizes in lower-dimensional cases) but the aim here is to demonstrate the generality and robustness of the algorithm rather than maximizing efficiency. Even with this general setup, the full benchmark test program completes in approximately 7 seconds on a standard laptop equipped with 8 CPU threads. In the right plot of Fig. 1 we show the number of fitness function evaluations required to reach the desired precision of $f < 10^{-10}$ as a function of the number of dimensions n . The plot reveals that approximately 60,000 evaluations are needed for the two-dimensional test case, while the number increases gradually with dimensionality, reaching about 700,000 evaluations at $n = 20$. This growth is expected due to the exponential increase in the search space volume with dimension.

4.1.2 Michalewicz function

Another widely used multimodal test function for evaluating the performance of global optimization algorithms is the Michalewicz function [65]. The function is defined in n dimensions as

$$f(x_i) = - \sum_{i=1}^n \sin(x_i) \left[\sin\left(\frac{ix_i^2}{\pi}\right) \right]^{2m} \quad (9)$$

where the search domain is $x_i \in [0, \pi]$, and the parameter m controls the sharpness of the valleys and ridges that structure the function. We show a surface plot of the two-dimensional Michalewicz function in the left plot of Fig. 2. A common and recommended value is $m = 10$, which is also adopted in our analysis. As m increases, the local minima become steeper and narrower, making the optimization landscape significantly more difficult to navigate. In total, the Michalewicz function has $n!$ local minima, and only one of them corresponds to the global minimum.

A key distinction between the Michalewicz function and the Rastrigin function discussed in Section 4.1.1 lies in the nature of their local minima. The local minima of the Rastrigin function are located in a regular pattern, whereas the Michalewicz function features broad, almost flat valleys that can mislead an optimizer into converging prematurely. These valleys exhibit very small gradients, which can render gradient-based methods ineffective. At the same time, the global minimum is confined to a narrow, sharply defined region of the parameter space, further increasing the difficulty of the search.

To demonstrate how `evortran` can be used to tackle this problem, we include a test program `benchmark_michalewicz` in the `app` folder of the repository. This program runs a GA on the Michalewicz function for dimensions ranging from $n = 2$ to $n = 100$. To search for the global minimum, we use the following call to `evolve_population` from `evortran`:

```
1 best_ind = evolve_population( &
2   1000, n, michalewicz, &
3   lower_lim=0.0e0_wp, &
4   upper_lim=pi, &
5   selection='rank', &
6   mating='blend', &
```

⁸Using a fitness target value to control the desired precision of the solution is only appropriate in this case because the global minimum of the Rastrigin function is known to be exactly zero. For functions where the global minimum is not known, convergence criteria must be defined differently.




Figure 2: Left: Surface plot of the $n = 2$ dimensional Michalewicz function with $m = 10$ in the domain $x_{1,2} \in [0, \pi]$. Right: Minimal function values f_{\min} of the Michalewicz function for $m = 10$ against the number of dimensions $n = 2, \dots, 25$ that were found using the example application `benchmark_michalewicz`.

```

1657     7   mutate='gaussian', &
1658     8   selection_size=100, &
1659     9   elite_size=10, &
1660    10   mutate_prob=0.4e0_wp, &
1661    11   mutate_gene_prob=0.1e0_wp)

```

This configuration uses a population size of 1,000, applies rank-based selection, blend crossover and gaussian mutation, and it includes both elitism with 10 individuals per generation. In the right plot of Fig. 2 we show the minimum value of the test function achieved at the end of the GA as a function of the dimension n up to $n = 25$. For $n = 2, 5, 10$ the global minimum of the Michalewicz function is known, and we find good agreement with the minimum found using `evortran`.

For larger number of dimensions, the global minimum of the Michalewicz function is in general not known. To assess the quality of the solutions found by `evortran`, we therefore apply also the `Pikaia` GA framework to the same problem, see also the discussion in Section 1. For the comparison, we use the default settings of `Pikaia`, except we increase the population size to 1,000 and the maximum number of generations to 10,000. The latter is ten times higher than the corresponding setting in the `evortran` run. We found that in this way both algorithms use roughly the same runtime. It is important to emphasize that our goal is not a performance comparison between `Pikaia` and `evortran`. The goal of this comparison is simply to verify that `evortran` reliably identifies minima that are at least as deep as those found by `Pikaia`, and to therefore be able to validate the `evortran` result in the absence of known solutions to the optimization problem.

In Fig. 3 we show the minimum values of the Michalewicz function f_{\min} divided by the number of dimensions n as a function of n that were found using `evortran` (blue) and `Pikaia` (orange). One can observe that for each value of n the values of f_{\min}/n determined with `evortran` are in agreement or slightly smaller than the values obtained with `Pikaia`. For $n \gtrsim 50$, we observe that for both `evortran` and `Pikaia` the values of f_{\min}/n start to grow with increasing value of n . This potentially indicates that both codes struggle to determine the exact global minima in this regime given the settings used in the example program `benchmark_michalewicz`.




Figure 3: Minimal function values f_{\min} of the Michalewicz function normalized to the dimensionality n for $m = 10$ as a function of the number of dimensions $n = 2, \dots, 100$ that were found using the example application benchmark_michalewicz. Blue and orange points indicate the values obtained with evortran and Pikaia, respectively, see text for details.

4.1.3 Himmelblau function

The Himmelblau function [66] serves as a classic benchmark in the study of multimodal optimization problems. Unlike the Rastrigin and Michalewicz functions discussed above, which feature a single global minimum (albeit in a complex landscape), the Himmelblau function presents a qualitatively different challenge because it possesses multiple global minima of equal depth. The four minima are separated by relatively shallow barriers. This makes it an ideal benchmark function for evaluating the ability of an optimization framework not just to find a global minimum, but to recover multiple degenerate global optima. The Himmelblau function is defined as

$$f(x, y) = (x^2 + y - 11)^2 + (x + y^2 - 7)^2. \quad (10)$$

It has four known global minima in the search domain $x, y \in [-5, 5]$, located approximately at

$$(x, y) \approx (3.0, 2.0), \quad (11)$$

$$(x, y) \approx (-2.805, 3.131), \quad (12)$$

$$(x, y) \approx (-3.779, -3.283), \quad (13)$$

$$(x, y) \approx (3.584, -1.848), \quad (14)$$

all with a function value of $f(x, y) = 0$. In Fig. 4 we show a surface plot of the Himmelblau function in the search domain.

To demonstrate how evortran can successfully identify all of these minima, we make use of the evolve_migration routine, which is designed to evolve multiple populations in parallel, see the discussion in Section 2.5. In this example, we disable migration between the evolving populations (by choosing a single epoche, see the discussion below), such that each population evolves independently. Due to the stochastic nature of GAs, different populations initialized with random gene values can then converge to different minima. Using a sufficient




Figure 4: Surface plot of the $n = 2$ dimensional Himmelblau function in the domain $x, y \in [-5, 5]$.

1706 number of evolving populations enhances the likelihood of recovering all four global minima
 1707 of the Himmelblau function within a single execution. The corresponding example program
 1708 `benchmar_himmelblau` can be found in the app folder of the repository. In this program,
 1709 the call to the `evolve_migration` function is as follows:

```
1710     1 best_ind = evolve_migration( &
1711     2     pop_number=20, &
1712     3     epoches=1, &
1713     4     pop_size=50, &
1714     5     gene_length=2, &
1715     6     fit_func=himmelblau, &
1716     7     mating='sbx', &
1717     8     elite_size=1, &
1718     9     lower_lim=-5.0e0_wp, &
1719    10     upper_lim=5.0e0_wp, &
1720    11     max_generations=100, &
1721    12     fittest_inds_final_pops=fittest_inds_final_pops)
```

1722 20 independent populations of size 50 are evolved in parallel for 100 generations. Each in-
 1723 dividual encodes two genes, corresponding to the two-dimensional input of the Himmelblau
 1724 function, with gene values bounded between -5 and 5. Simulated binary crossover is used
 1725 for mating, and one elite individual is retained in each generation. Only a single epoch is
 1726 used, which means no migration of individuals occurs between populations since migration in
 1727 `evolve_migration` is only applied across multiple epochs. This setup allows each population
 1728 to converge independently. The function returns the best-fit individual across all populations
 1729 (`best_ind`). Since we are interested in finding all minima, we additionally store the best-
 1730 fit individual of each population after the completion of the GA using the optional argument
 1731 `fittest_inds_final_pops`.

1732 Upon completion, the `benchmark_himmelblau` program prints the best solution found
 1733 across all populations, followed by a detailed list of the best solutions from within each of
 1734 the 20 independent populations:

```
1735     1 Fittest overall individual:
1736     2 Genes:    3.5844E+00 -1.8481E+00
1737     3 Fitness:    0.0000E+00
1738     4
```

```

1739 5  Fittest individuals in each population:
1740 6      i      x      y      fmin
1741 7      1  3.0000E+00  2.0000E+00  4.4727E-21
1742 8      2  3.5844E+00 -1.8481E+00  0.0000E+00
1743 9      3  3.5844E+00 -1.8481E+00  0.0000E+00
1744 10     4  3.0000E+00  2.0000E+00  9.6754E-19
1745 11     5  3.0000E+00  2.0000E+00  4.2069E-26
1746 12     6 -2.8051E+00  3.1313E+00  7.8886E-31
1747 13     7 -2.8051E+00  3.1313E+00  7.8886E-31
1748 14     8 -2.8051E+00  3.1313E+00  1.3647E-28
1749 15     9  3.5844E+00 -1.8481E+00  1.1177E-22
1750 16    10  3.0000E+00  2.0000E+00  1.1292E-25
1751 17    11 -3.7793E+00 -3.2832E+00  2.9196E-22
1752 18    12  3.5844E+00 -1.8481E+00  0.0000E+00
1753 19    13  3.0000E+00  2.0000E+00  0.0000E+00
1754 20    14  3.5844E+00 -1.8481E+00  0.0000E+00
1755 21    15  3.0000E+00  2.0000E+00  0.0000E+00
1756 22    16 -2.8051E+00  3.1313E+00  1.3996E-24
1757 23    17  3.5844E+00 -1.8481E+00  0.0000E+00
1758 24    18 -3.7793E+00 -3.2832E+00  7.1510E-27
1759 25    19  3.0000E+00  2.0000E+00  5.8376E-28
1760 26    20 -3.7793E+00 -3.2832E+00  3.1554E-30

```

1761 The table lists the population index, the gene values, i.e. the x and y coordinates, of the fittest
 1762 individual, and the achieved minimum of the Himmelblau function. In the example shown,
 1763 all four known global minima of the Himmelblau function are discovered by different popu-
 1764 lations. This demonstrates the effectiveness of evolving multiple independent populations in
 1765 parallel for identifying multiple (approximately) degenerate solutions of multimodal objective
 1766 functions.

1767 4.1.4 Drop-Wave function

1768 As a final benchmark, we consider the Drop-Wave function, a challenging multimodal test
 1769 function often used to evaluate the robustness of global optimization methods. The definition
 1770 of the Drop-Wave function is

$$f(x_i) = -\frac{1 + \cos(12||x||)}{0.5||x||^2 + 2} \quad \text{with } ||x||^2 = \sum_{i=1}^n x_i^2. \quad (15)$$

1771 Its global minimum with $f(x_i) = -1$ is located at the center $x_i = 0$ of the search domain
 1772 $x_i \in [-5.12, 5.12]$. In Fig. 5 we show a surface plot of the Drop-Wave function in two di-
 1773 mensions over the search domain. Due to the presence of steep central basins surrounded
 1774 by increasingly shallow, oscillating ripples that form many local minima, the landscape of the
 1775 function misleads optimization algorithms away from the global minimum. This structure
 1776 makes it extremely difficult for optimization methods to locate the global minimum, even for
 1777 a relatively small number of dimensions. The Drop-Wave function is particularly well-suited
 1778 to test the ability of GAs to escape local minima. In this benchmark, we again compare the
 1779 results obtained with `evortran` with the ones obtained using the `Pikaia` library.

1780 We apply both frameworks to search for the global minimum of the Drop-Wave func-
 1781 tion in dimensionalities ranging from $n = 2$ to $n = 8$. The corresponding example program
 1782 `benchmark_dropwave_pikaia` is located in the `app` folder of the `evortran` repository. For
 1783 `evortran`, we use the `evolve_migration` routine with the following call:




Figure 5: Left: Surface plot of the $n = 2$ dimensional Drop-Wave function in the domain $x_{1,2} \in [-5.12, 5.12]$. Right: Number of calls to the Drop-Wave function against the number of dimensions n until the GA completes by either finding the global minimum with a precision of 10^{-4} (filled points) or by reaching the maximum number of epochs/generations (empty points) using the example application benchmark_dropwave_pikaia. Blue and orange points correspond to using evortran and Pikaia, respectively, with the GAs configured as described in the text.

```

1784 1 best_ind = evolve_migration( &
1785 2   pop_number=90, &
1786 3   epoches=1000, &
1787 4   pop_size=200, &
1788 5   max_generations=300, &
1789 6   gene_length=i, &
1790 7   fit_func=dropwave, &
1791 8   migration_size=10, &
1792 9   elite_size=10, &
1793 10  selection_size=100, &
1794 11  mating='blend', &
1795 12  fitness_target=-1.0e0_wp + 1.0e-4_wp, &
1796 13  selection='roulette', &
1797 14  wheele_size=7, &
1798 15  mutate='uniform', &
1799 16  mutate_prob=0.2e0_wp)

```

Here the argument i for the `gene_size` corresponds to the number of dimensions which are iterated over. This setup results in a total of 18,000 individuals evolving in parallel in 90 different populations of size 200 each, over a maximum number of 300 generations and 1000 epoches, see the discussion in Section 2.5 for details. We make use of elitism (10 individuals in each population), roulette wheel selection (with `wheele_size=7`), blend crossover, and uniform mutation (with a mutation probability of 20%).⁹ Migration exchanges 10 individuals between populations after each epoch. The algorithm halts when the fitness falls below -0.9999, which is within 10^{-4} of the known global minimum of the Drop-Wave function, or when the maximum number of epochs is reached.

For comparison, Pikaia is configured with similar computational resources by assigning it

⁹A total number of 90 populations is chosen because the program was executed on a cluster with 90 CPU cores available.

the same total number of individuals and a maximum of 5000 generations. The initialization is performed as follows:

```

1812     1 call pikaia%init( &
1813     2     i, xl, xu, &
1814     3     dropwave_pikaia, &
1815     4     status_pikaia, &
1816     5     ngen=5000, &
1817     6     np=200*90)

```

The large number of maximum generations allows Pikaia to perform up to approximately 100 million fitness evaluations, which is a number comparable to what is typically required by evortran to converge to the global minimum in more than 5 dimensions. The arguments `xl` and `xu` are arrays that determine the search domain in each x_i -direction. Since Pikaia maximizes the fitness function, whereas evortran minimizes, we define a separate function `dropwave_pikaia` here, which differs by an overall minus sign from the fitness function `dropwave` used in the `evolve_migration` call of evortran. We again would like to emphasize that this setup is not intended to directly compare runtime performance between evortran and Pikaia, as the frameworks differ in design and parallelization, but only to validate the evortran results against a similar available GA implementation.

In the right plot of Fig. 5 we show the number of times the Drop-Wave function was evaluated for the different values of dimensions n when using the example program `benchmark_dropwave_pikaia`, with the orange points indicating the calls from evortran and the blue points indicating the calls from Pikaia.¹⁰ The filled points indicate if the GA converged successfully by converging to the global minimum, whereas the empty points indicate if the GA failed by converging to a local minimum. We observe that the GA applied with evortran is able to find the global minimum of the Drop-Wave function up to $n = 7$ dimensions, requiring a total number of about $5 \cdot 10^7$ function calls for $n = 2$ dimensions and of about $5 \cdot 10^8$ function calls for $n = 7$ dimensions. The GA applied with Pikaia is able to find the global minimum of the Drop-Wave function with a substantially smaller number of function evaluations for $n = 2$ and $n = 3$ dimensions, and with a similar number of functions calls than the GA applied with evortran for $n = 4$ dimensions. For $n > 4$ the GA applied with Pikaia is not able to locate the global minimum in the give maximum number of generations, and thus shows a larger number of function calls for $n = 4, 5, 6$ than the GA applied with evortran because the latter halts once the global minimum is found within the required precision.

To demonstrate the flexibility of the evortran library, and to compare the performance of different crossover methods, we conducted a comprehensive set of runs using the `evolve_migration` function to minimize the Drop-Wave function using different crossover routines. For each dimensionality from $n = 2$ to $n = 10$, we tested each crossover operator (`blend`, `sbx`, `one-point`, `two-point`, `uniform`) in combination with all possible permutations of the three available selection routines (`tournament`, `rank`, `roulette`) and the three mutation strategies (`uniform`, `shuffle`, `gaussian`). Each unique combination was run 10 times, resulting in a total of $3 \cdot 3 \cdot 10 = 90$ runs per crossover method and dimension. The GA was configured via the following call:

```

1852     1 best_ind = evolve_migration( &
1853     2     pop_number=90, &

```

¹⁰We slightly modified the Pikaia algorithm for this example by changing the convergence condition. We implemented that the Pikaia algorithm only halts if either the global minimum was found with a precision of 10^{-4} , or if the maximum number of generations was reached. In this way the Pikaia algorithm allows for a larger number of function calls and behaves more similarly to the evortran algorithm.




Figure 6: Number of calls to the Drop-Wave function against the number of dimensions n until the GA successfully converged to the global minimum for the different crossover methods implemented in `evortran`. The horizontal bars indicate the mean values per dimension for each crossover method, and the colored numbers show the total number of successfully converged runs out of a total number of 90 runs (see the discussion in the text for details).

```

1854     3     epoches=1000, &
1855     4     pop_size=200, &
1856     5     max_generations=300, &
1857     6     gene_length=number_dimensions, &
1858     7     fit_func=dropwave, &
1859     8     migration_size=2, &
1860     9     elite_size=2, &
1861    10     selection_size=100, &
1862    11     selection=selection_opts(i_selection), &
1863    12     mating=mating_opts(i_mating), &
1864    13     mutate=mutate_opts(i_mutate), &
1865    14     fitness_target=-0.999, &
1866    15     wheele_size=7, &
1867    16     verbose=verbose)

```

Here, `evolve_migration` was used to evolve 90 populations in parallel with light migration (`migration_size=2`) between them. The number of epochs was set to 1000, and each population consisted of 200 individuals, evolved over up to 300 generations per epoch. The `fitness_target` value was set to -0.999, which lies below the value of any local minimum of the Drop-Wave function, thereby serving as an effective criterion to identify convergence to the true global minimum. Default values were used for all optional arguments of the selection, crossover and mutation routines, except for a `wheele_size` of 7 for roulette selection.

The results are summarized in Fig. 6, which shows the number of function evaluations required for successful convergence versus dimensionality n . The total number of successful runs is indicated with numbers per method and dimension to quantify robustness. Also shown with horizontal bars are the mean values of the function calls per dimension for each crossover method, including only the successfully converged runs. The plot reveals several key features regarding the robustness of the different crossover strategies. The crossover methods

specifically designed for continuous optimization problems, `blend` and `sbx`, outperform the more generic binary-inspired crossovers, `one-point`, `two-point`, and `uniform`, particularly in lower and intermediate dimensions $n \leq 6$. This suggests that using continuous crossover operators can significantly enhance the reliability of a GA in continuous solution spaces. Up to dimension $n = 7$, the `blend` crossover shows the highest robustness, achieving successful convergence in at least 75 out of 90 runs, highlighting its effectiveness across a wide range of settings. For higher dimensionalities ($n = 8, \dots, 10$), the `sbx` crossover becomes more robust, maintaining a convergence success rate of over 20%. Interestingly, the `uniform` crossover, while generally less robust at lower dimensionality, shows a certain robustness in performance at high dimensionality, matching the robustness of `blend` and `sbx` for $n = 8$ and beyond. It maintains a minimum success rate of roughly 10% across all dimensions.

These results underscore the importance of carefully selecting the components of a GA to match the characteristics of the specific optimization problem. The flexible design of `evortran` allows users to easily explore and combine different evolutionary operators. This modularity is a key advantage of the library, making it a powerful tool in wide areas of scientific computing.

4.2 Physics applications

To demonstrate the capabilities of `evortran` in real-world research settings, we present two physics-motivated applications that go beyond the mathematical benchmark problems discussed above. The first application focuses on a global fit of an extended Higgs sector in a beyond-the-Standard-Model (BSM) scenario to existing data from the Large Hadron Collider (LHC). This includes fitting the observed signal strengths of the Higgs boson at 125 GeV as well as incorporating cross section limits from searches for additional Higgs bosons that have (so far) not given rise to a discovery. The second application addresses a problem in cosmology: reconstructing the frequency spectrum of a stochastic gravitational wave background produced by a cosmological first-order phase transition, such as the ones expected from an electroweak phase transition in the early universe. Here, the goal is to reconstruct a consistent signal from LISA mock data, which includes both an injected gravitational wave signal and realistic instrumental noise.

4.2.1 Confronting extended Higgs sector with LHC data

A common challenge in studies of BSM physics is the efficient exploration of high-dimensional parameter spaces subject to a complex set of constraints. In particular, models with extended scalar/Higgs sectors often feature many free parameters (eleven in the first scenario studied below, and 14 in a second more general scan). These parameters are subject to both theoretical consistency requirements (such as vacuum stability or perturbativity) and a wide range of experimental constraints. Among the latter are 95% confidence level exclusion bounds on production cross sections from direct searches for additional Higgs bosons at the LHC, as well as precision measurements of the observed 125 GeV Higgs boson. Many of these constraints are either non-differentiable (e.g., hard cutoffs on excluded cross sections) or involve discrete features in the parameter space, which makes gradient-based optimization methods less effective.

GAs offer a natural solution to this type of problem. Their population-based and non-gradient nature allows them to effectively navigate large, non-linear, and non-smooth landscapes, making them well-suited for parameter scans that need to identify viable regions consistent with a diverse set of constraints. An additional advantage of GAs is their ability to uncover multiple, qualitatively distinct regions of parameter space that are all consistent with theoretical and experimental constraints within their respective uncertainties. This is par-

particularly important when different parameter regions compatible with the constraints yield different phenomenology. Since these parameter regions may correspond to local minima of the χ^2 -function or likelihood that are only marginally suboptimal compared to the global minimum within the margin of uncertainty, identifying (ideally) all of these regions may be crucial. GAs are well-suited for this task because their stochastic and population-based search can naturally discover such local optima, rather than converging exclusively to a single best-fit solution.

As an example, we focus here on the singlet-extended two Higgs doublet model (S2HDM) [16], a well-motivated BSM scenario that augments the Standard Model by a second Higgs doublet and a complex scalar singlet. We utilized a GA to explore the phenomenology of the S2HDM in previous studies in Refs. [16–18] using the Python GA framework DEAP [42]. In the S2HDM, the presence of the second Higgs doublet opens the possibility of a strong first-order electroweak phase transition, which is an essential requirement for electroweak baryogenesis to explain the baryon asymmetry of the universe, and which cannot be realized in the Standard Model. Additionally, the complex singlet respects a softly-broken global U(1) symmetry, which is spontaneously broken when the real component of the singlet acquires a vacuum expectation value. This results in a pseudo-Nambu-Goldstone boson from the imaginary part of the singlet field, which is stable and provides a viable Higgs-portal dark matter candidate. Notably, a pseudo-Nambu-Goldstone dark matter particle can achieve the observed relic abundance through the standard thermal freeze-out mechanism, while evading the stringent limits from dark matter direct detection experiments due to momentum-suppressed scattering cross sections at leading order [67,68].

A comprehensive discussion of the S2HDM can be found in Ref. [16]. Here, we briefly summarize the key features relevant for the following analysis. The model contains the same fermionic and gauge field content as the Standard Model, but due to the extended scalar sector the physical spectrum includes a total of three CP-even neutral scalar Higgs bosons h_i ($i = 1, 2, 3$) which mix with each other, a CP-odd pseudoscalar Higgs boson A , a pair of singly charged Higgs bosons H^\pm , and a stable spin-0 dark matter candidate χ .¹¹ We consider two Yukawa structures: first, a so-called Type I structure where only one Higgs doublet is coupled to fermions, and second, a flavour-aligned setup which can be parameterized by three so-called flavour alignment parameters $\xi_{u,d,\ell}$ [69]. The other free parameters used in the analysis below include the masses $m_{h_{1,2,3}}$, m_A , m_{H^\pm} , m_χ , the three CP-even scalar mixing angles $\alpha_{1,2,3}$, the ratio of the Higgs doublet vacuum expectation values $\tan\beta$, the singlet vacuum expectation value v_S , and an additional mass scale parameter M , which controls the allowed mass range of the BSM Higgs states.

To identify phenomenologically viable points in the parameter space of the S2HDM, we construct a global χ^2 -function that incorporates a range of theoretical and experimental constraints. This function is then minimized using a GA implemented in `evortran`. Since evaluating the fitness function requires interfacing with external codes, namely `HDECAY` [70,71] for computing Higgs boson decay properties and `HiggsTools` [72–75] for checking consistency against LHC data (see below), the evaluation is computationally expensive. For this reason, we employ a relatively economical GA with a population size of only 40 individuals, evolved using `evortran`’s `evolve_population` routine over a maximum of 1000 generations, applying tournament selection, blend crossover and uniform mutation.

The theory constraints included in the analysis are the following:

- **Vacuum stability:** We impose that the scalar potential is bounded from below, ensuring that no field direction leads to the potential tending to $-\infty$ for large field values. At tree-level, this leads to analytic conditions requiring certain combinations of quartic couplings appearing in the potential to be positive. The corresponding expressions can be found

¹¹The Standard Model of particle physics predicts a single CP-even Higgs boson.

in Refs. [71, 76].

- **Perturbative unitarity:** We verify that the leading-order $2 \rightarrow 2$ scalar scattering amplitudes remain below the threshold 8π in the high-energy limit. This results in a set of inequalities on combinations of the scalar quartic couplings, whose precise form can be found in Ref. [16].

Both theory constraints are implemented as hard cuts and introduce non-differentiable features into the χ^2 function. The experimental constraints that we consider here are the following:

- **125 GeV Higgs cross sections:** We include cross section measurements of the observed Higgs boson in various production and decay channels, including also the measurements presented in the form of the Simplified Template Cross Section (STXS) framework.
- **Limits from BSM spin-0 resonance searches:** We apply 95% confidence level exclusion limits from a large set of direct LHC searches for additional neutral and charged Higgs bosons. These constraints are implemented as hard cuts.
- **Electroweak precision observables:** We require compatibility with the measured electroweak parameter $\Delta\rho$ within its experimental uncertainty [77], based on its one-loop prediction in the S2HDM [16]. This constraint is included as a hard cut, rejecting parameter points predicting a value of $\Delta\rho$ deviating by more than two standard deviations from the experimental central value, corresponding to a confidence level of about 95%.

The check against the LHC data is carried out in our analysis with the help of the public C++ package HiggsTools, which performs a global χ^2 fit to the cross section measurements of the 125 GeV Higgs bosons and checks if all existing cross section limits from BSM scalar searches are satisfied. The HiggsTools library can be exposed to Fortran via the `iso_c_binding` module. We created a minimal working example for using HiggsTools within an fpm project that is available in a dedicated GitLab repository [78].

The global χ^2 function minimized by `evortran` includes the contributions from HiggsTools for the 125 GeV Higgs measurements, denoted $\chi^2(h_{125})$ in the following, while all other constraints are incorporated via large fixed penalty values if they are not satisfied. This setup effectively translates the task of finding allowed parameter points into minimizing $\chi^2(h_{125})$ under the condition that all other theoretical and experimental constraints are satisfied, for which derivative-free optimization strategies like GAs are especially useful. To define a meaningful condition at which the GA shall halt, we subtract the Standard Model prediction $\chi_{\text{SM}}^2(h_{125})$ from the total χ^2 , such that $\chi^2 = 0$ corresponds to the S2HDM fitting the LHC data as well as the Standard Model (while satisfying all other constraints), while $\chi^2 < 0$ indicates a better fit than the Standard Model. The GA halts if a parameter point predicting $\chi^2 < 0$ was found. During the minimization process, we not only record the best-fit point but also store all parameter points generated during the evolution process that predict $\chi^2 = \chi^2(h_{125}) - \chi_{\text{SM}}^2(h_{125}) \leq 6.18$, which approximately corresponds to a 95% confidence region assuming two degrees of freedom and assuming that the Standard Model prediction is a good approximation of the best fit to the LHC data (see Ref. [75] for details). To obtain a diverse sample of viable parameter points across the scanned regions of parameter space, we run the GA multiple times with different random seeds.

Scenario 1: Scanning the S2HDM Type I – 11 free parameters: $\{m_{h_2}, m_{h_3}, m_A, m_{H^\pm}, m_\chi, \tan\beta, \alpha_{1,2,3}, M, v_S\}$

In the first scenario, we use `evortran` to perform a global scan of the S2HDM with Yukawa Type I, using the full parameter space summarized in Table 4. This constitutes a very generic scan where the goal is to test whether the GA is capable of identifying regions in parameter space that yield a 125 GeV Higgs boson (here h_1) with properties resembling those predicted by the Standard Model within current experimental precision, while also satisfying all other

Parameter	Range
m_{h_1}	125.1 GeV (fixed)
$m_{h_2}, m_{h_3}, m_A, m_{H^\pm}, m_\chi$	[30, 1000] GeV
$\alpha_{1,2,3}$	$[-\frac{\pi}{2}, \frac{\pi}{2}]$
$\tan \beta$	[1, 20]
$M(= m_{12}^2/(\sin \beta \cos \beta))$	[30, 1000] GeV
v_S	[10, 3000] GeV
Scenario 1:	Yukawa Type I
Scenario 2:	Flavour alignment: $\xi_{u,d,\ell} \in [10^{-3}, 10^3]$ (log prior)

Table 4: The top rows show the S2HDM parameter ranges used in the scans. The last two rows indicate the Yukawa structure chosen for the scenario 1 and the scenario 2.

theoretical and experimental constraints discussed above. In the case where the additional Higgs bosons are substantially heavier, the properties of the 125 GeV Higgs boson are mainly governed by the mixing angles $\alpha_{1,2,3}$ and $\tan \beta$, which must be tuned with some precision in order to reproduce the observed Higgs boson signal strengths. The other parameters are relevant for satisfying the remaining constraints. For instance, the masses of the BSM states have to be chosen in a range that is not excluded by LHC searches. Their allowed values are also strongly correlated with the parameter $\tan \beta$, the mass parameters M and v_S , and the mass splitting among the BSM states is constrained by the $\Delta \rho$ parameter.

Technically, this parameter scan is a minimization of a χ^2 function defined over eleven free parameters. The complexity of the task is significant since the χ^2 function encodes roughly 150 independent LHC measurements of the 125 GeV Higgs boson cross sections, in addition to a vast number of cross section limits from direct searches for BSM Higgs bosons. This results in a highly structured and non-trivial eleven-dimensional optimization landscape.

In Fig. 7 we show results from scenario 1, where each point corresponds to a valid parameter point identified by the GA. The left plot shows the distribution of $\chi^2(h_{125})$ values obtained with HiggsTools against the coupling coefficient κ_V of the CP-even Higgs boson h_1 to vector bosons $V = W, Z$, defined as $\kappa_V = g_{h_1 V V} / g_{h_{\text{SM}} V V}$, where $g_{h_1 V V}$ is the coupling predicted in the S2HDM and $g_{h_{\text{SM}} V V}$ is the coupling predicted for a Standard Model Higgs boson of the same mass. This plot demonstrates that the GA successfully identified parameter points consistent with the 125 GeV Higgs boson data at the level of the Standard Model ($\chi^2 \approx 0$) and even slightly better ($\chi^2 < 0$), though the latter is not a statistically significant improvement considering the larger number of additional parameters of the S2HDM compared to the Standard Model.

The right plot of Fig. 7 shows the mass of the CP-odd Higgs boson m_A against the mass of the charged Higgs boson m_{H^\pm} . The GA identified valid parameter points over a wide mass range up to the upper limit 1 TeV of the scan for the masses of the BSM states. The lightest masses found for A and H^\pm are around 200 GeV. Below this, experimental searches from the LHC increasingly constrain the parameter space, and a light H^\pm also introduces substantial loop-level corrections to the di-photon decay rate of the 125 GeV Higgs boson h_1 , making it harder to achieve agreement with the data. However, this does not imply that smaller values of m_A or m_{H^\pm} are excluded in the S2HDM. Uncovering valid parameter space in this regime would require a dedicated scan that biases the GA toward lower mass ranges (or higher values of $\tan \beta$), instead of the setup applied here that constitutes a broad and generic exploration of parameter space. Biasing the GA towards smaller masses could, for instance, be achieved using a logarithmic prior instead of linear prior for the masses of the BSM Higgs bosons when




Figure 7: Each point in the two plots corresponds to a valid parameter point found with the GA in the scenario 1 in the S2HDM with type I Yukawa structure. Left: $\chi^2(h_{125})$ obtained with HiggsTools against the coupling coefficient $|\kappa_V|$ of the 125 GeV Higgs boson h_1 . Right: mass of the CP-odd Higgs boson m_A against the mass of the charged Higgs bosons m_{H^\pm} .

the GA is initialized, see also the discussion in Section 4.2.2.

In Fig. 8 we show the couplings and masses of the three CP-even Higgs bosons h_1 , h_2 , and h_3 in the S2HDM with type I Yukawa structure for the valid parameter points found in scenario 1. In each plot, for each valid parameter point three points are displayed with the following color-coding: blue for h_1 , orange for h_2 , and green for h_3 . The left plot shows the vector boson coupling coefficient $\kappa_V(h_i)$ versus the Higgs boson mass m_{h_i} . Here it should be noted that due to unitarity there is a sum rule for these coupling coefficients: $\sum_i \kappa_V(h_i)^2 = 1$. Since LHC measurements require $\kappa_V(h_1) \gtrsim 0.93$, see left plot of Fig. 7, this forces the couplings of h_2 and h_3 to electroweak gauge bosons to be small. The GA identified parameter points with this coupling configuration by accurately sampling the mixing angles $\alpha_{1,2,3}$, as is visible in the plot where both $\kappa_V(h_2)$ and $\kappa_V(h_3)$ lie below about 0.3. Accordingly, for h_1 the GA efficiently converges to $\kappa_V(h_1) \approx 1$, in agreement with LHC data requiring the 125 GeV Higgs boson to resemble the Standard Model prediction within an experimental precision at the level of 10%.

Using the Type I Yukawa structure, the modifications of the Higgs boson couplings to fermions can be expressed by means of a single coupling coefficient $\kappa_f(h_i)$ for each Higgs boson, independently of the fermion kind. The right plot shows the fermion coupling coefficients defined as $\kappa_f(h_i) = g_{h_i f \bar{f}} / g_{h_{\text{SM}} f \bar{f}}$, where $g_{h_i f \bar{f}}$ is the coupling predicted for the state h_i in the S2HDM, and $g_{h_{\text{SM}} f \bar{f}}$ is the coupling predicted in the Standard Model for a Higgs boson of the same mass. In the type I Yukawa structure, there is an upper bound of $|\kappa_f(h_i)| \leq 1$. Unlike the gauge couplings, $|\kappa_f(h_2)|$ and $|\kappa_f(h_3)|$ can be sizable, i.e. as large as $|\kappa_f(h_1)|$, without violating current LHC data. This behavior is visible in the right plot. Again, as before for $|\kappa_V(h_1)|$ shown in the left plot of Fig. 8, the GA converges to $\kappa_f(h_1) \approx 1$ for the 125 GeV Higgs boson, such that the state h_1 resembles a SM Higgs boson.

Since the scan covers all physically distinct combinations of the three scalar mixing angles $\alpha_{1,2,3}$, see Table 4, no distinction between h_2 and h_3 is imposed on their possible masses and couplings. As a result, the orange points corresponding to the state h_2 and the green points corresponding to the state h_3 show a similar distribution in the two plots of Fig. 8. Furthermore, the mass ranges for h_2 and h_3 span from about 63 GeV to 1 TeV. The lower bound arises because masses below 62.5 GeV would open the decay channels $h_1 \rightarrow h_2 h_2 / h_3 h_3$, which tends to spoil the Standard-Model-like nature of h_1 unless the corresponding couplings governing




Figure 8: For each valid parameter point found with the GA in the scenario 1 in the S2HDM with type I Yukawa structure, the plots show three points with properties related to the Higgs bosons h_1 , h_2 and h_3 in blue, orange and green, respectively. Left: coupling coefficient κ_V of the respective state h_i against the mass of the Higgs boson m_{h_i} . Left: coupling coefficient κ_f of the respective state h_i against the mass of the Higgs boson m_{h_i} .

these decays are fine-tuned to suppress the decays. The GA does not converge to such tuned regions of parameter space in this broad scan. On the upper end, the scan reaches the maximum mass range of 1 TeV set in the input.

We finally note that some points shown in the plots in Fig. 7 and Fig. 8 are clustered along a line in the plot, which reflects the fact that during the GA evolution, all parameter points satisfying $\chi^2 \leq 6.18$ are stored, and not just the final best-fit point. As a result, parameter points originating from gradual changes to a successful candidate solutions during the optimization appears as an approximately continuous trajectory in parameter space.

Scenario 2: Scanning the flavor-aligned S2HDM – 14 free parameters: $\{m_{h_2}, m_{h_3}, m_A, m_{H^\pm}, m_\chi, \tan \beta, \alpha_{1,2,3}, M, v_S, \xi_{u,d,\ell}\}$

In this second scenario, we consider a more general Yukawa sector for the S2HDM, namely the flavor alignment mentioned above. In contrast to the Type I Yukawa structure where only one Higgs doublet couples to all fermions, the flavor-aligned setup allows both Higgs doublets to couple to fermions, controlled via three additional parameters ξ_u , ξ_d , and ξ_ℓ . These alignment parameters act as proportionality factors between the Yukawa couplings of the two Higgs doublets and determine which doublet dominantly couples to a given fermion type: up-type quarks u , down-type quarks d , and charged leptons ℓ . Specifically, values of $\xi_{u,d,\ell} \ll 1$ correspond to dominant couplings to the first Higgs doublet, while $\xi_{u,d,\ell} \gg 1$ correspond to dominant couplings to the second doublet.

An important consequence is that compared to the Type I Yukawa structure, where the couplings of the Higgs bosons to fermions are governed by a universal modifier κ_f for all fermion types, the flavor alignment leads to an independent coupling modifier for each fermion kind: κ_u , κ_d , and κ_ℓ , defined analogously to κ_f as the ratio of the coupling of a state h_i in the S2HDM to the corresponding coupling of a Higgs boson in the Standard Model with the same mass as the state h_i . This results in additional freedom to accommodate the LHC Higgs boson measurements. The coupling coefficients $\kappa_{u,d,\ell}$ depend on the parameters $\xi_{u,d,\ell}$, $\tan \beta$ and the mixing angles $\alpha_{1,2,3}$, such that the couplings of the 125 GeV Higgs bosons depends on various independent parameters, and where various entirely different regions of the complex parameter space can predict a Higgs boson h_1 in agreement with the LHC measurements.




Figure 9: For each valid parameter point found with the GA in the scenario 2 in the flavor-aligned S2HDM, the left plot shows the the values of $\chi^2(h_{125})$ obtained with HiggsTools against the coupling coefficient $|\kappa_V|$ of the 125 GeV Higgs boson h_1 . The right plot shows the h_1 coupling coefficient κ_t against the coupling coefficient κ_b . In both plots, the orange points belong to the same parameter point which stands out as the only parameter point for which κ_t and κ_b have the opposite sign.

In Fig. 9 we show the results obtained for scenario 2, where the GA was used to scan the flavor-aligned S2HDM, see Table 4. Each point in both plots corresponds to a valid parameter point that satisfies all theoretical and experimental constraints. In the left plot, we show the values of the global $\chi^2(h_{125})$ as computed with HiggsTools plotted against the absolute value of the coupling coefficient $|\kappa_V|$ of the 125 GeV Higgs boson h_1 . The plot demonstrates that the GA successfully identifies parameter points where $|\kappa_V| \approx 1$ with $\chi^2(h_{125})$ close to or below the Standard Model value $\chi^2_{\text{SM}}(h_{125})$, indicating good agreement with the LHC measurements of the Higgs boson. This confirms that even in the more general flavor-aligned setup with a total of 14 free parameters the GA is able to determine parameter space regions with the desired features. In this scenario, we find that smaller values of the coupling coefficient $|\kappa_V|$ are still compatible with current LHC data. Values down to $|\kappa_V| \approx 0.912$ are allowed while still yielding valid parameter points. This is in contrast to the more restrictive scenario 1 with Yukawa Type I, see the left plot of Fig. 7, where viable parameter points were only found for $|\kappa_V| \gtrsim 0.935$. Notably, even some parameter points with $|\kappa_V| \lesssim 0.92$ result in a total $\chi^2(h_{125})$ below the Standard Model value $\chi^2_{\text{SM}}(h_{125})$. This indicates that, compared to the Yukawa Type I, the added freedom of the flavor-aligned Yukawa structure allows the model to better accommodate the LHC measurements in case of sizable deviations in κ_V from the SM prediction $\kappa_V = 1$.

In the right plot of Fig. 9, we show the values of the coupling modifiers κ_u vs. κ_d , which specifically correspond to the ratios of the h_1 couplings to top and bottom quarks, respectively, compared to the Standard Model. Unlike in the Yukawa Type I, these two couplings are now controlled independently via the alignment parameters ξ_u and ξ_d . The distribution shows that most viable parameter points cluster in the region where both κ_u and κ_d are close to either +1 or -1, reflecting Standard-Model-like behavior. However, one point clearly stands out as it corresponds to a parameter point where κ_u and κ_d have opposite signs. The two points in the left and the right plot of Fig. 9 corresponding to this parameter point are highlighted in orange. This sign configuration between κ_u and κ_d (also referred to as wrong-sign Yukawa coupling regime) is a distinctive feature of the flavor-aligned S2HDM compared to the S2HDM Type I and can, as observed here, still be consistent with current data, though it is associated with

modified interference effects in loop-induced Higgs processes (such as gluon fusion production or the $h \rightarrow \gamma\gamma$ decay).

In summary, the two example scenarios demonstrate that GAs are effective tools for scanning the complex parameter space of BSM theories. Despite the high dimensionality of the search (eleven and fourteen free parameters) and the large amount of experimental constraints (including around 150 measurements of the 125 GeV Higgs boson and a plethora of exclusion limits from searches for additional scalars), the GA reliably identifies viable parameter regions. Notably, one of the key strengths of GAs is their ability to uncover distinct and potentially isolated solutions in parameter space that are consistent with all constraints and may even yield a better fit to the data. Such solutions might easily be missed by more local or gradient-based methods. This is exemplified in scenario 2 by the identification of a parameter point with opposite signs in the top and bottom Yukawa coupling modifiers, a feature that nonetheless yields an acceptable fit to the LHC data. The S2HDM serves here as one specific but sufficiently complex example to showcase the power of GAs, demonstrating their potential for parameter scans in BSM theories. More broadly, GAs hold great promise for exploring a wide range of particle physics models with a substantial number of unknown parameters and with similar or even greater complexity.

4.2.2 Reconstructing gravitational wave spectrum from LISA mock data

To explore the utility of GAs, and in particular the `evortran` library, in a cosmological context, we consider the problem of reconstructing a stochastic gravitational wave signal generated by a first-order phase transition in the early universe. The analysis begins with the construction of mock observational data for the upcoming LISA experiment, into which a synthetic gravitational wave signal is injected based on a physically motivated template predicted for such a cosmological phase transition. To simulate realistic observational conditions, Gaussian noise simulating the LISA instrument sensitivity is added to the signal. This introduces a stochastic component to the data, which complicates the parameter inference and makes traditional gradient-based minimization techniques less effective, whereas a GA is well suited for this type of problem. For the fitting process we use a GA implemented with `evortran` to minimize an overall χ^2 -function that quantifies the deviation between the theoretical signal (including LISA's sensitivity curve) and the noisy mock data. This procedure is repeated multiple times to generate a set of reconstructed signals. Each reconstructed signal corresponds to a set of cosmological parameters that govern the spectral shape and amplitude of the gravitational wave signal, such as the strength, duration, and energy release of the phase transition. The resulting distribution of these parameter sets reveals the regions of parameter space compatible with the data, and allows for a comparison with the values originally used for signal injection.

The gravitational wave spectrum produced during a cosmological phase transition carries information about the underlying physics of the early universe. The shape and amplitude of the signal can be parametrized in terms of the strength of the phase transition α , defined as the ratio of the vacuum energy released to the radiation energy density, the inverse duration of the transition normalized to the Hubble rate, β/H , the transition temperature T_* at which the signal is generated, the number of relativistic degrees of freedom in the plasma at that temperature, g_* , and the terminal velocity v_w of the bubble walls expanding through the plasma. In this study, we use signal templates derived from numerical simulations that model the generation of gravitational waves produced during a first-order phase transitions. The total gravitational wave spectral power density $\Omega_{\text{GW}} h^2$, with $h = 0.68$ being the dimensionless Hubble constant, is composed of three main contributions,

$$\Omega_{\text{GW}} h^2 = \Omega_{\text{sw}} h^2 + \Omega_{\text{turb}} h^2 + \Omega_{\text{coll}} h^2. \quad (16)$$

Each of these components contributes with a characteristic spectral shape and peak frequency,

dependent on the physical parameters mentioned above. The sound wave contribution $\Omega_{\text{sw}} h^2$ results from gravitational wave production from the acoustic oscillations in the plasma after bubble collisions, which dominates the signal in scenarios in which the bubble walls reach a terminal velocity before colliding [79]. The turbulence contribution $\Omega_{\text{turb}} h^2$ arises from magnetohydrodynamic turbulence, i.e. nonlinear plasma motion generated after the transition. The turbulence contribution are not yet well understood, but numerical simulations indicate that it peaks at slightly higher frequencies than the sound wave contribution and with peak amplitudes that are substantially smaller than the one of the sound wave contribution [80]. Finally, $\Omega_{\text{coll}} h^2$ contains the contributions from bubble wall collisions, which account for the direct collisions of expanding bubbles during the transition [81]. Specifically, we model the three contributions using the following templates available in the literature: the sound wave contribution follows the power-law parametrization given in Ref. [82], the turbulence spectrum is implemented using the results of Ref. [83], and the bubble collision part is described by the broken power-law given in Ref. [84].

To simulate realistic LISA mock data and model the detector sensitivity, we follow the methodology outlined in Ref. [85]. The total power spectral density includes contributions from instrumental noise due to the optical metrology system and mass acceleration, assuming a standard LISA configuration with an arm length of $L = 2.5 \cdot 10^6$ km. We incorporate the full LISA response function as detailed in the same reference. For simplicity, we do not include uncertainties on the effective functions parametrizing the two noise components. In a more realistic scenario, these could be constrained by measuring in the low- and high-frequency regions where no gravitational wave signal is expected. The data are simulated over a frequency range from $f_{\text{min}} = 3 \cdot 10^{-5}$ Hz to $f_{\text{max}} = 0.5$ Hz, with a resolution of $\Delta f = 10^{-6}$ Hz, determined by the length of the time stream. To inject a signal, we generate at each frequency 94 individual signal power values with Gaussian noise and compute their average to obtain the final mock data. This mimics an expected 4-year observational run of LISA with approximately 75% observing efficiency, which results in 94 statistically independent data chunks.

To reconstruct the gravitational wave signal from the simulated LISA data, we use `evortran` to minimize a χ^2 -function that quantifies the difference between the model and the data, with the data including the injected signal. Specifically, we minimize

$$\chi^2(\alpha, \beta/H, T_*, g_*, v_w) = N_{\text{chunks}} \sum_i \frac{1}{2} \left[\frac{\bar{D}_i - \Omega_{\text{GW}} h^2 - \Omega_s h^2}{\sigma_i} \right]^2, \quad (17)$$

where $\Omega_{\text{GW}} h^2$ is the template for the gravitational wave spectrum from a cosmological phase transition, see Eq. (16), depending on the five physical parameters α , β/H , T_* , G_* , and v_w , as discussed above. $\Omega_s h^2$ is the LISA face sensitivity curve, \bar{D}_i are the averaged simulated signal powers at frequency bin i , and σ_i are the variances over the $N_{\text{chunks}} = 94$ individual realizations that were averaged to produce the mock data (see Ref. [85] for details). The sum in Eq. (17) runs over the frequency bins from the minimum frequency $3 \cdot 10^{-5}$ Hz up to a frequency of 10^{-2} Hz, and the bins at higher frequency are discarded since the gravitational wave signals are far below the LISA sensitivity there.

We employ the `evolve_population` function of `evortran` to perform the optimization and locate parameter values that minimize χ^2 . The GA is configured with tournament selection, `sbx` crossover and uniform mutation. The populations size is 200, the selection size is 100, and the elite size is four. The population is evolved over a maximum number of 500 generations, or until a minimal χ^2 threshold value of $1.11 \cdot 10^{-2}$ was achieved. This value was determined heuristically because we observed that below this value the instrumental noise prevents improving the signal reconstruction to a higher level of precision. For each example presented below, which differ by the injected signal or the parameter set to be reconstructed from the mock data, the minimization is repeated 200 times to explore potential variations

and degeneracies in the fit. The resulting distribution of reconstructed parameter sets is then compared to the true parameters used to inject the signal, providing insight into the precision with which LISA may constrain phase transition parameters if a stochastic gravitational wave background is observed.

Before turning to the discussion of specific example scenarios, we briefly comment on the simplifications made in this analysis. First, we do not include uncertainties in the LISA sensitivity curve, which in a full analysis would arise from limited knowledge of the noise power spectral densities and calibration uncertainties [85]. Second, we ignore stochastic astrophysical foregrounds, such as the unresolved foregrounds from stellar binary systems like white dwarfs, neutron stars or black holes [86, 87], which are expected to contribute in the relevant frequency range and may complicate signal extraction. Third, we assume that the shape of the gravitational wave spectrum follows fixed template forms based on hydrodynamic simulations, rather than reconstructing the spectrum in a binned, model-independent way from the data, as considered in various LISA forecasting studies. Furthermore, we do not perform a statistically comprehensive likelihood analysis to determine allowed parameter ranges at a given confidence level. Instead, we effectively over-fit the data to provide signal reconstructions that agree well with the observations. Finally, we note that future improvements in theoretical modeling might reveal additional features in the signal templates, which could allow more precise parameter extraction if present in real data. These simplifications are justified here since our goal is to illustrate how `evortran` can be used for gravitational wave signal reconstruction as a general-purpose, customizable tool. A comprehensive treatment that includes these more realistic aspects and a more sound statistical interpretation is left for future work. For studies that address these issues in detail, see e.g. Refs. [84, 85].

Scenario 1: Reconstructing EWPT signal – Free parameters: $\{\alpha, \beta/H, T_*, g_*, v_w\}$

As a first example, we consider a gravitational wave signal injected into the LISA mock data that is consistent with an electroweak phase transition in the early universe. The underlying parameters for this signal reflect a realistic scenario in BSM physics. We assume a transition temperature $T_* = 100$ GeV, corresponding to the order of the electroweak scale. For the transition strength we assume a value of $\alpha = 0.4$, which lies at the upper end of what can be achieved in simple scalar extensions of the Standard Model such as models with an additional singlet [88, 89] and/or a second Higgs doublet [90–92], without invoking significant supercooling. The terminal velocity of the expanding bubbles is taken to be $v_w = 0.9$, close to the speed of light, since in strong transitions with $\alpha \gtrsim 0.1$ the bubble expansion is expected to proceed as relativistic detonations [93]. The number of effective relativistic degrees of freedom is set to $g_* = 110$, accounting for the ones of the Standard Model plus a modest number of BSM states that facilitate a strong electroweak phase transition. Finally, we use $\beta/H = 100$ as a representative inverse duration of the transition, which is typical for such scenarios.

The upper plot of Fig. 10 shows the LISA face sensitivity curve (magenta), the injected gravitational wave signal (orange), and the mock data after adding Gaussian detector noise (blue). As described above, we use `evortran` to minimize the χ^2 function shown in Eq. (17) in order to reconstruct the signal from this noisy data. This reconstruction is performed 200 times to explore degeneracies and noise-induced variance, where we include all five parameters $\{\alpha, \beta/H, T_*, g_*, v_w\}$ as free parameters to be fitted to the data, under the conditions that $g_* \leq 10^3$, $\alpha \leq 10^4$ and $v_w \geq 0.1$. The resulting reconstructed spectra are shown in green. For this specific scenario, the contribution from bubble collisions is omitted, as the expanding bubbles are not expected to runaway in a typical electroweak phase transition, and the resulting collision signal is expected to be subdominant compared to sound waves and turbulence in the LISA frequency band.

The plot reveals an important degeneracy in the signal reconstruction. `evortran` consistently identifies two qualitatively distinct classes of solutions that fit the data taking into




Figure 10: Top: Gravitational wave power spectrum as a function of frequency for the scenario 1. The magenta line shows the LISA power-law face sensitivity curve, the orange line is the injected gravitational wave signal composed of sound wave and turbulence contributions, and the blue line shows the mock data including Gaussian noise. The green lines represent 200 reconstructed gravitational wave signals obtained using the evortran by minimizing the χ^2 function given in Eq. (17). Bottom: Corner plot showing the distributions of the phase transition parameters corresponding to the reconstructed signals. Each green point marks a parameter set that produced a signal consistent with the mock data, while the orange star indicates the parameters used to generate the injected signal.

account instrumental noise. The first class closely resembles the injected signal, with the peak from the sound wave contribution lying within the most sensitive frequency range of LISA. In this case, the turbulence contribution remains largely irrelevant, as its amplitude is suppressed, and its peak falls at higher frequencies where the experimental sensitivity is strongly reduced. The second class of reconstructed signals, however, fits the data using the turbulence peak instead. Here, the entire signal is shifted to lower frequencies, and although the corresponding sound wave component is much stronger, it is shifted to the left of the LISA sensitivity curve and thus effectively undetected. Despite arising from entirely different physical parameters and microphysics, these two alternative reconstructions produce a gravitational wave signal that would be indistinguishable from the injected signal within the noise level of the simulated data. This example highlights the practical challenges and degeneracies involved in interpreting gravitational wave observations from cosmological phase transitions.

In the same plot, we also show the distributions of the reconstructed parameter values corresponding to the signals that are consistent with the mock data. One can see that none of the parameters can be extracted given the available data. In particular, the parameters α and g_* remain effectively unconstrained. Importantly, this imprecision is not solely due to the existence of the two different classes of viable signals, but also persists when considering only the subset of reconstructed signals that closely resemble the injected one. This residual uncertainty reflects inherent degeneracies in the dependence of the gravitational wave spectrum on the underlying parameters. In the future, if LISA will detect a signal consistent with an electroweak phase transition, these degeneracies might severely limit the possibility of distinguishing between different BSM theories that might have given rise to the electroweak phase transition.

The lower plot in Fig. 10 is a corner plot showing the parameter distributions of the 200 reconstructed signals. Each green point corresponds to a parameter combination that yields a signal compatible with the mock data (green lines in the top plot), while the orange star indicates the true values of the injected signal (orange line in the top plot). The corner plot shows the presence of strong degeneracies, as the green points are broadly scattered, filling large portions of the allowed parameter space across all pairwise projections. In particular, a prominent degeneracy is visible between the parameters α , β/H and T_* . This degeneracy will be further analyzed and discussed in the next example.

Scenario 2: Reconstructing EWPT signal assuming $\alpha \leq 1$ and $g_* = 110$ – Free parameters: $\{\alpha, \beta/H, T_*, v_w\}$

In the second example, we build upon the previous analysis by introducing additional constraints that reflect a more model-dependent interpretation of the gravitational wave signal. Specifically, we restrict the strength of the phase transition to values $\alpha \leq 1$, and we fix the effective number of relativistic degrees of freedom to $g_* = 110$. These choices are motivated by the expectation that an electroweak phase transition occurring in minimal extensions of the Standard Model, such as those with a singlet scalar, a second Higgs doublet, or a Higgs triplet, will involve only a modest increase in the particle content and will not exhibit significant supercooling. As a result, this setup provides a more focused reconstruction of the signal under the assumption that the underlying physics corresponds to a specific electroweak-scale model. In contrast, the broader parameter space explored in the previous example remains more agnostic to the origin of the signal and is also compatible with other cosmological phase transitions that might have occurred in the early universe. We again take into account only the sound wave and turbulence contribution to the gravitational wave signal, which is consistent with the considered range of α .

The results of this second example are shown in Fig. 11, with the top plot displaying the power spectra and the bottom plot presenting the corner plot of reconstructed parameter values. Due to the additional assumptions on α and g_* , only reconstructed signals that closely




Figure 11: As in Fig. 10 for the scenario 2.

resemble the injected one are found. The second class of solutions observed in the previous example, characterized by a peak at lower frequencies dominated by the turbulence contribution as visible in the upper plot of Fig. 10, disappears. This is a consequence of requiring $\alpha \leq 1$ here. As a result of the additional assumptions, the parameter reconstruction becomes more useful. From the distribution of reconstructed signals, we infer that the transition temperature T_* is constrained between about 25 and 150 GeV, α must be larger than about 0.1, β/H lies between 27 and 223, and the bubble wall velocity v_w is reconstructed to be above about 0.4. Here one should note that the lower limit on T_* and the upper bound on β/H are both consequences of the upper limit assumed on α , and thus not a direct consequence of the fitting procedure.

The corner plot at the bottom of Fig. 11 further reveals that the bubble wall velocity v_w remains practically unconstrained. However, fixing $g_* = 110$ gives rise to a clearer correlation between the other three parameters T_* , α and β/H , with α and β/H decreasing with increasing values of T_* , see the two bottom panes in the left column of the corner plot. The size of the bands in which the green points are concentrated in these plots results from the unknown bubble wall velocity v_w which is also fitted to the data in this example. In the following example we will investigate the correlations between the parameters by further assuming that a prediction for v_w is available for the electroweak phase transition, in which case v_w does not have to be reconstructed from the LISA data but can be set to the predicted value.

Scenario 3: Reconstructing EWPT signal assuming $\alpha \leq 1$, $g_* = 110$ and $v_w = 0.9$ – Free parameters: $\{\alpha, \beta/H, T_*\}$

The third example builds upon the second scenario with an even more constrained fit. In addition to assuming $\alpha \leq 1$ and fixing the effective number of degrees of freedom to $g_* = 110$, we now also fix the bubble wall velocity to $v_w = 0.9$, motivated by the expectation of relativistic expansion for phase transitions with $\mathcal{O}(0.1-1)$ values of α . This setup reflects a more model-dependent interpretation in which we assume that in the future when LISA is in operation it may be possible to reliably compute the bubble wall velocity from first principles in a given BSM scenario. Consequently, the reconstruction is now performed only for the three parameters α , β/H and T_* . While these additional assumptions reduce generality, they significantly enhance the precision of the parameter reconstruction, as we will demonstrate. The injected signal parameters remain the same as in the previous two examples discussed above, and we again only consider the sound wave and turbulence contribution to the gravitational wave signal.

In Fig. 12 we show the results for this third example, again showing the reconstructed power spectra in the top plot and the reconstructed values of the fitted parameters in the corner plot at the bottom. The upper plot illustrates that the signal is now reconstructed with high precision across the frequency range relevant for LISA. However, despite the overall good match between the reconstructed signals and the injected one, the underlying parameter values corresponding to the injected signal are still not recovered. This is a result of the degeneracy between the three free parameters α , β/H and T_* . As shown in the corner plot, the viable parameter values consistent with the data lie along thin lines in the parameter space. This indicates that a detection of a stochastic signal with LISA could effectively be used to express two of the parameters as functions of the third.

While the observed degeneracy between the parameters still prevents precise extraction of the parameter values of the injected signal, the reconstruction becomes significantly more informative. In particular, it enables meaningful model discrimination power. If a given BSM theory can predict a set of values for α , β/H and T_* that fall on top of the reconstructed lines in the corner plot, that model remains viable within experimental uncertainty and could provide an explanation for the detected signal. Conversely, if the predicted parameter correlations in a specific BSM theory fall outside the reconstructed viable region, not overlapping with the lines in the corner plot, the model could potentially be ruled out. It is important to note, however,




Figure 12: As in Fig. 10 for the scenario 3.

that this type of model testing hinges on the assumption that the bubble wall velocity v_w is known and fixed. If a precise prediction for v_w is not available in the future when LISA is in operation, the discrimination power between different models is significantly worse, see the scenarios discussed above.

Scenario 4: Reconstructing stronger signal assuming $\alpha \leq 10^3$, $g_* \leq 150$ and $v_w = 1$ – Free parameters: $\{\alpha, \beta/H, T_*, g_*\}$

In this fourth and final scenario, we return to a more general setup and consider a substantially stronger gravitational wave signal originating from a cosmological phase transition with a large strength parameter of $\alpha = 45$. The motivation behind this choice is to investigate how well the signal reconstruction and parameter inference is improved when the injected signal has a significantly higher signal-to-noise ratio, thereby enhancing its detectability across a wider range in the LISA frequency band. In this example, the contribution from bubble collisions might not be negligible, and we therefore include this third source component in the signal template. The bubble collision peak appears at slightly lower frequencies than the sound wave and turbulence contributions, providing additional structure in the spectrum that could potentially help break some of the degeneracies observed in earlier examples.

A key focus of this example is to explore the influence of the prior distribution used for the reconstructed parameters. In particular the sampled range of the strength parameter α span several orders of magnitude. To investigate the impact of different initialization of gene values in a GA, we perform two separate reconstructions: one using a linear prior on α and the other using a logarithmic prior. The comparison between the resulting distributions of reconstructed parameters highlights that the performance and coverage of the solution space of GAs can depend sensitively on the initial seeding of gene values, i.e. on how the sampling space is explored from the start. As this example will demonstrate, the choice of prior can have significant consequences for the robustness and reliability of the inferred parameter ranges in multi-scale parameter spaces.

In Fig. 13 we show the results for the fourth scenario, where a strong gravitational wave signal is injected with parameters $T_* = 100$ GeV, $\alpha = 45$, $\beta/H = 100$, $g_* = 110$, and $v_w = 1$. The large signal-to-noise ratio allows for a very precise reconstruction of the spectral shape, as visible in the top plot, with the sound wave peak placed near the maximum sensitivity of LISA and the turbulence and collision peaks located to either side but still within the sensitive band. In the corner plot below, we show two sets of reconstructed parameter values. The green points correspond to a linear prior on α , while purple points come from using a log prior. The linear prior leads to a more concentrated reconstruction, especially for g_* , as visible in the upper pane of the corner plot. This might misleadingly suggest that this parameter is well constrained by the data. However, the results using the log prior reveal that a wide range of values, including the whole sampled range of g_* , are actually compatible with the injected signal. This discrepancy arises because the linear prior oversamples values of α at the upper end of the sampled interval, whereas the log prior allows the GA to explore several orders of magnitude more evenly as visible in the bottom row of the corner plot. Notably, only the log prior reconstruction recovers the injected parameter values (orange stars), while the linear prior biases the fit toward larger α and β/H values. This example illustrates the importance of prior choice in GA-based inference, especially when parameters span several orders of magnitude.

5 Conclusions

We have introduced `evortran`, a lightweight, flexible, and efficient genetic algorithm (GA) library written in modern Fortran. The `evortran` package is available at:




Figure 13: Same as in Fig. 10 for the scenario 4. The corner plot additionally shows reconstructed parameter values using a logarithmic prior on the parameter α at initialization of the GA.

<https://gitlab.com/thomas.biekoetter/evortran>.

With its modular design and simple user interface, `evortran` enables users to easily apply evolutionary strategies to complex optimization problems, including those with non-differentiable, discontinuous, or noisy fitness functions. The library supports customization of GA components, native real and integer encodings, and parallel execution via OpenMP. `evortran` is installed with the Fortran package manager `fpm`, ensuring a straightforward dependency management, compilation and installation process, as well as a seamless integration into both simple scripts and larger code bases. To further enhance accessibility, `evortran` provides Python bindings available at:

<https://gitlab.com/thomas.biekoetter/pyevortran>.

This interface allows users to run the core optimization routines of `evortran` directly from Python.

To demonstrate its robustness and versatility, we first validated `evortran` on a set of well-known multi-modal benchmark functions commonly used in global optimization, showing reliable convergence and the ability to locate global optima even in rugged fitness landscapes. As a complex, real-world application from particle physics, we used `evortran` to perform high-dimensional parameter scans of the Singlet-extended Two-Higgs-Doublet Model (S2HDM), involving eleven to 14 free parameters, a combination of theoretical constraints, and an extensive set of LHC data. As a second physics application from cosmology, we then applied the library to the reconstruction of primordial gravitational wave signals and their underlying parameters from mock data of the upcoming LISA space observatory. In both cases, `evortran` performed successfully, identifying viable solutions efficiently in challenging search spaces.

While our focus here has been on specific scientific use cases, the design of `evortran` makes it broadly applicable to a wide range of optimization problems in physics, engineering, and other fields requiring global search strategies. We hope that `evortran` becomes a useful tool for GAs in the Fortran ecosystem and scientific computing.

Acknowledgements

I gratefully acknowledge the open-source Fortran community for their continued efforts in developing and modernizing the Fortran ecosystem, with special thanks to the contributors of the Fortran Package Manager (FPM), whose work was beneficial for the development of `evortran`.

Funding information The project that gave rise to these results received the support of a fellowship from the “la Caixa” Foundation (ID 100010434). The fellowship code is LCF/BQ/PI24/12040018. We acknowledge the support of the Spanish Agencia Estatal de Investigación through the grant “IFT Centro de Excelencia Severo Ochoa CEX2020-001007-S”.

References

- [1] C. Damian, L. R. Diaz-Barron, O. Loaiza-Brito and M. Sabido, *Slow-Roll Inflation in Non-geometric Flux Compactification*, JHEP **06**, 109 (2013), doi:[10.1007/JHEP06\(2013\)109](https://doi.org/10.1007/JHEP06(2013)109), [1302.0529](https://arxiv.org/abs/1302.0529).

- [2] C. Damian and O. Loaiza-Brito, *More stable de Sitter vacua from S-dual nongeometric fluxes*, Phys. Rev. D **88**(4), 046008 (2013), doi:[10.1103/PhysRevD.88.046008](https://doi.org/10.1103/PhysRevD.88.046008), [1304.0792](#).
- [3] J. Blåbäck, D. Roest and I. Zavala, *De Sitter Vacua from Nonperturbative Flux Compactifications*, Phys. Rev. D **90**(2), 024065 (2014), doi:[10.1103/PhysRevD.90.024065](https://doi.org/10.1103/PhysRevD.90.024065), [1312.5328](#).
- [4] S. Abel and J. Rizos, *Genetic Algorithms and the Search for Viable String Vacua*, JHEP **08**, 010 (2014), doi:[10.1007/JHEP08\(2014\)010](https://doi.org/10.1007/JHEP08(2014)010), [1404.7359](#).
- [5] F. Ruehle, *Evolving neural networks with genetic algorithms to study the String Landscape*, JHEP **08**, 038 (2017), doi:[10.1007/JHEP08\(2017\)038](https://doi.org/10.1007/JHEP08(2017)038), [1706.07024](#).
- [6] K. Bull, Y.-H. He, V. Jela and C. Mishra, *Machine Learning CICY Threefolds*, Phys. Lett. B **785**, 65 (2018), doi:[10.1016/j.physletb.2018.08.008](https://doi.org/10.1016/j.physletb.2018.08.008), [1806.03121](#).
- [7] A. Cole, A. Schachner and G. Shiu, *Searching the Landscape of Flux Vacua with Genetic Algorithms*, JHEP **11**, 045 (2019), doi:[10.1007/JHEP11\(2019\)045](https://doi.org/10.1007/JHEP11(2019)045), [1907.10072](#).
- [8] S. AbdusSalam, S. Abel, M. Cicoli, F. Quevedo and P. Shukla, *A systematic approach to Kähler moduli stabilisation*, JHEP **08**(08), 047 (2020), doi:[10.1007/JHEP08\(2020\)047](https://doi.org/10.1007/JHEP08(2020)047), [2005.11329](#).
- [9] N. Cabo Bizet, C. Damian, O. Loaiza-Brito, D. K. M. Peña and J. A. Montañez Barrera, *Testing Swampland Conjectures with Machine Learning*, Eur. Phys. J. C **80**(8), 766 (2020), doi:[10.1140/epjc/s10052-020-8332-9](https://doi.org/10.1140/epjc/s10052-020-8332-9), [2006.07290](#).
- [10] G. J. Loges and G. Shiu, *Breeding Realistic D-Brane Models*, Fortsch. Phys. **70**(5), 2200038 (2022), doi:[10.1002/prop.202200038](https://doi.org/10.1002/prop.202200038), [2112.08391](#).
- [11] P. Berglund, Y.-H. He, E. Heyes, E. Hirst, V. Jela and A. Lukas, *New Calabi–Yau manifolds from genetic algorithms*, Phys. Lett. B **850**, 138504 (2024), doi:[10.1016/j.physletb.2024.138504](https://doi.org/10.1016/j.physletb.2024.138504), [2306.06159](#).
- [12] B. C. Allanach, D. Grellscheid and F. Quevedo, *Genetic algorithms and experimental discrimination of SUSY models*, JHEP **07**, 069 (2004), doi:[10.1088/1126-6708/2004/07/069](https://doi.org/10.1088/1126-6708/2004/07/069), [hep-ph/0406277](#).
- [13] Y. Akrami, P. Scott, J. Edsjo, J. Conrad and L. Bergstrom, *A Profile Likelihood Analysis of the Constrained MSSM with Genetic Algorithms*, JHEP **04**, 057 (2010), doi:[10.1007/JHEP04\(2010\)057](https://doi.org/10.1007/JHEP04(2010)057), [0910.3950](#).
- [14] J. E. Camargo-Molina, T. Mandal, R. Pasechnik and J. Wessén, *Heavy charged scalars from $c\bar{s}$ fusion: A generic search strategy applied to a 3HDM with $U(1) \times U(1)$ family symmetry*, JHEP **03**, 024 (2018), doi:[10.1007/JHEP03\(2018\)024](https://doi.org/10.1007/JHEP03(2018)024), [1711.03551](#).
- [15] S. Abel, D. G. Cerdeño and S. Robles, *The Power of Genetic Algorithms: what remains of the pMSSM?* (2018), [1805.03615](#).
- [16] T. Biekötter and M. O. Olea-Romacho, *Reconciling Higgs physics and pseudo-Nambu-Goldstone dark matter in the S2HDM using a genetic algorithm*, JHEP **10**, 215 (2021), doi:[10.1007/JHEP10\(2021\)215](https://doi.org/10.1007/JHEP10(2021)215), [2108.10864](#).
- [17] T. Biekötter, S. Heinemeyer and G. Weiglein, *The CMS di-photon excess at 95 GeV in view of the LHC Run 2 results*, Phys. Lett. B **846**, 138217 (2023), doi:[10.1016/j.physletb.2023.138217](https://doi.org/10.1016/j.physletb.2023.138217), [2303.12018](#).

- [18] T. Biekötter, S. Heinemeyer and G. Weiglein, *95.4 GeV diphoton excess at ATLAS and CMS*, Phys. Rev. D **109**(3), 035005 (2024), doi:[10.1103/PhysRevD.109.035005](https://doi.org/10.1103/PhysRevD.109.035005), [2306.03889](https://arxiv.org/abs/2306.03889).
- [19] J. Wessén and E. Camargo-Molina, *A diversity-enhanced genetic algorithm for efficient exploration of parameter spaces* (2024), [2412.17104](https://arxiv.org/abs/2412.17104).
- [20] R. D. Ball *et al.*, *Parton distributions for the LHC Run II*, JHEP **04**, 040 (2015), doi:[10.1007/JHEP04\(2015\)040](https://doi.org/10.1007/JHEP04(2015)040), [1410.8849](https://arxiv.org/abs/1410.8849).
- [21] S. Carrazza, S. Forte, Z. Kassabov, J. I. Latorre and J. Rojo, *An Unbiased Hessian Representation for Monte Carlo PDFs*, Eur. Phys. J. C **75**(8), 369 (2015), doi:[10.1140/epjc/s10052-015-3590-7](https://doi.org/10.1140/epjc/s10052-015-3590-7), [1505.06736](https://arxiv.org/abs/1505.06736).
- [22] S. Carrazza and N. P. Hartland, *Minimisation strategies for the determination of parton density functions*, J. Phys. Conf. Ser. **1085**(5), 052007 (2018), doi:[10.1088/1742-6596/1085/5/052007](https://doi.org/10.1088/1742-6596/1085/5/052007), [1711.09991](https://arxiv.org/abs/1711.09991).
- [23] H. Moutarde, P. Sznajder and J. Wagner, *Unbiased determination of DVCS Compton Form Factors*, Eur. Phys. J. C **79**(7), 614 (2019), doi:[10.1140/epjc/s10052-019-7117-5](https://doi.org/10.1140/epjc/s10052-019-7117-5), [1905.02089](https://arxiv.org/abs/1905.02089).
- [24] S. Abdullin, D. Acosta, P. Bartalini, R. Cavanaugh, A. Drozdetskiy, G. Karapostoli, G. Mitselmakher, Y. Pakhotin, B. Scurlock and M. Spiropulu, *GARCON: Genetic algorithm for rectangular cuts optimization: User's manual for version 2.0* (2006), [hep-ph/0605143](https://arxiv.org/abs/hep-ph/0605143).
- [25] L. Tani, D. Rand, C. Veelken and M. Kadastik, *Evolutionary algorithms for hyperparameter optimization in machine learning for application in high energy physics*, Eur. Phys. J. C **81**(2), 170 (2021), doi:[10.1140/epjc/s10052-021-08950-y](https://doi.org/10.1140/epjc/s10052-021-08950-y), [2011.04434](https://arxiv.org/abs/2011.04434).
- [26] K. Nowak and A. F. Zarnecki, *Optimising top-quark threshold scan at CLIC using genetic algorithm*, JHEP **07**, 070 (2021), doi:[10.1007/JHEP07\(2021\)070](https://doi.org/10.1007/JHEP07(2021)070), [2103.00522](https://arxiv.org/abs/2103.00522).
- [27] C. Bonilla, A. E. Cárcamo Hernández, J. a. Gonçalves, F. F. Freitas, A. P. Morais and R. Pasechnik, *Collider signatures of vector-like fermions from a flavor symmetric model*, JHEP **01**, 154 (2022), doi:[10.1007/JHEP01\(2022\)154](https://doi.org/10.1007/JHEP01(2022)154), [2107.14165](https://arxiv.org/abs/2107.14165).
- [28] T. Ohlsson and W. Winter, *Reconstruction of the earth's matter density profile using a single neutrino baseline*, Phys. Lett. B **512**, 357 (2001), doi:[10.1016/S0370-2693\(01\)00731-6](https://doi.org/10.1016/S0370-2693(01)00731-6), [hep-ph/0105293](https://arxiv.org/abs/hep-ph/0105293).
- [29] S. K. Agarwalla *et al.*, *Optimised sensitivity to leptonic CP violation from spectral information: the LBNO case at 2300 km baseline* (2014), [1412.0593](https://arxiv.org/abs/1412.0593).
- [30] R. Acciarri *et al.*, *Long-Baseline Neutrino Facility (LBNF) and Deep Underground Neutrino Experiment (DUNE): Conceptual Design Report, Volume 2: The Physics Program for DUNE at LBNF* (2015), [1512.06148](https://arxiv.org/abs/1512.06148).
- [31] A. Alekou *et al.*, *The European Spallation Source neutrino super-beam conceptual design report*, Eur. Phys. J. ST **231**(21), 3779 (2022), doi:[10.1140/epjs/s11734-022-00664-w](https://doi.org/10.1140/epjs/s11734-022-00664-w), [Erratum: Eur.Phys.J.ST 232, 15–16 (2023)], [2206.01208](https://arxiv.org/abs/2206.01208).
- [32] J. Rolla, A. Machtay, A. Patton, W. Banzhaf, A. Connolly, R. Debolt, L. Deer, E. Fahimi, E. Ferstle, P. Kuzma, C. Pfendner, B. Sipe *et al.*, *Using evolutionary algorithms to design antennas with greater sensitivity to ultrahigh energy neutrinos*, Phys. Rev. D **108**(10), 102002 (2023), doi:[10.1103/PhysRevD.108.102002](https://doi.org/10.1103/PhysRevD.108.102002), [2112.03246](https://arxiv.org/abs/2112.03246).

- [33] X.-L. Luo, J. Feng and H.-H. Zhang, *A genetic algorithm for astroparticle physics studies*, Comput. Phys. Commun. **250**, 106818 (2020), doi:[10.1016/j.cpc.2019.06.008](https://doi.org/10.1016/j.cpc.2019.06.008), [1907.01090](https://arxiv.org/abs/1907.01090).
- [34] F. Vargas, F. De Colle, D. Brethauer, R. Margutti and C. G. Bernal, *Survival of the Fittest: Numerical Modeling of SN 2014C*, Astrophys. J. **930**(2), 150 (2022), doi:[10.3847/1538-4357/ac649d](https://doi.org/10.3847/1538-4357/ac649d), [2102.12581](https://arxiv.org/abs/2102.12581).
- [35] J. Crowder, N. J. Cornish and L. Reddinger, *Darwin meets Einstein: LISA data analysis using genetic algorithms*, Phys. Rev. D **73**, 063011 (2006), doi:[10.1103/PhysRevD.73.063011](https://doi.org/10.1103/PhysRevD.73.063011), [gr-qc/0601036](https://arxiv.org/abs/gr-qc/0601036).
- [36] C. Bogdanos and S. Nesseris, *Genetic Algorithms and Supernovae Type Ia Analysis*, JCAP **05**, 006 (2009), doi:[10.1088/1475-7516/2009/05/006](https://doi.org/10.1088/1475-7516/2009/05/006), [0903.2805](https://arxiv.org/abs/0903.2805).
- [37] R. Arjona, *Machine learning meets the redshift evolution of the CMB temperature*, JCAP **08**, 009 (2020), doi:[10.1088/1475-7516/2020/08/009](https://doi.org/10.1088/1475-7516/2020/08/009), [2002.12700](https://arxiv.org/abs/2002.12700).
- [38] R. Arjona, H.-N. Lin, S. Nesseris and L. Tang, *Machine learning forecasts of the cosmic distance duality relation with strongly lensed gravitational wave events*, Phys. Rev. D **103**(10), 103513 (2021), doi:[10.1103/PhysRevD.103.103513](https://doi.org/10.1103/PhysRevD.103.103513), [2011.02718](https://arxiv.org/abs/2011.02718).
- [39] A. Kamerkar, S. Nesseris and L. Pinol, *Machine learning cosmic inflation*, Phys. Rev. D **108**(4), 043509 (2023), doi:[10.1103/PhysRevD.108.043509](https://doi.org/10.1103/PhysRevD.108.043509), [2211.14142](https://arxiv.org/abs/2211.14142).
- [40] G. Alestas, L. Kazantzidis and S. Nesseris, *Machine learning constraints on deviations from general relativity from the large scale structure of the Universe*, Phys. Rev. D **106**(10), 103519 (2022), doi:[10.1103/PhysRevD.106.103519](https://doi.org/10.1103/PhysRevD.106.103519), [2209.12799](https://arxiv.org/abs/2209.12799).
- [41] R. Medel-Esquivel, I. Gómez-Vargas, A. A. M. Sánchez, R. García-Salcedo and J. Alberto Vázquez, *Cosmological Parameter Estimation with Genetic Algorithms*, Universe **10**(1), 11 (2024), doi:[10.3390/universe10010011](https://doi.org/10.3390/universe10010011), [2311.05699](https://arxiv.org/abs/2311.05699).
- [42] F.-A. Fortin, F.-M. De Rainville, M.-A. Gardner, M. Parizeau and C. Gagné, *DEAP: Evolutionary algorithms made easy*, Journal of Machine Learning Research **13**, 2171 (2012).
- [43] A. F. Gad, *PyGAD: An Intuitive Genetic Algorithm Python Library*, Multimedia Tools and Applications **83**(20), 1573 (2024), doi:[10.1007/s11042-023-17167-y](https://doi.org/10.1007/s11042-023-17167-y), [2106.06158](https://arxiv.org/abs/2106.06158).
- [44] N. Hansen and A. Ostermeier, *Completely derandomized self-adaptation in evolution strategies*, Evolutionary Computation **9**(2), 159 (2001), doi:[10.1162/106365601750190398](https://doi.org/10.1162/106365601750190398).
- [45] S. A. Adcock, *GAUL: The Genetic Utility Library*, GitHub repository: <https://github.com/pgRouting/gaul-devel>.
- [46] M. Keijzer, J. J. Merelo, G. Romero and M. Schoenauer, *Evolving objects: A general purpose evolutionary computation library*, Artificial Evolution **2310**, 829 (2002).
- [47] A. Mohammadi, H. Asadi, S. Mohamed, K. Nelson and S. Nahavandi, *OpenGA, a C++ Genetic Algorithm Library*, In Systems, Man, and Cybernetics (SMC), 2017 IEEE International Conference on, pp. 2051–2056. IEEE (2017).
- [48] D. M. Levine, P. L. Hallstrom, D. M. Noelle, B. P. Walenz, D. Eddelbuettel and R. Schlatterbeck, *PGAPack*, GitHub repository: <https://github.com/schlatterbeck/pgapack>.
- [49] P. Charbonneau, *Genetic Algorithms in Astronomy and Astrophysics*, Astrophysical Journal Supplement **101**, 309 (1995), doi:[10.1086/192242](https://doi.org/10.1086/192242).

- [50] J. Williamson, *Pikaia: Modern Fortran Edition of the PIKAIA Genetic Algorithm*, GitHub repository: <https://github.com/jacobwilliams/pikaia>.
- [51] S. Ehlert, O. Čertík, M. Curcic, J. Jelínek, L. Kedward, V. Magnin, E. Pagone, B. Richardson and J. Urban, *Fortran package manager*, In *International Fortran Conference 2021*. Zurich, Switzerland, La présentation est publiée sous Licence MIT. (2021).
- [52] M. Curcic, O. Čertík, B. Richardson, S. Ehlert, L. Kedward, A. Markus, I. Pribec and J. Vandenplas, *Toward modern fortran tooling and a thriving developer community* (2021), [2109.07382](https://arxiv.org/abs/2109.07382).
- [53] T. Nishimura, *Tables of 64-bit mersenne twisters*, ACM Trans. Model. Comput. Simul. **10**(4), 348–357 (2000), doi:[10.1145/369534.369540](https://doi.org/10.1145/369534.369540).
- [54] M. Matsumoto and T. Nishimura, *Mersenne twister: a 623-dimensionally equidistributed uniform pseudo-random number generator*, ACM Trans. Model. Comput. Simul. **8**(1), 3–30 (1998), doi:[10.1145/272991.272995](https://doi.org/10.1145/272991.272995).
- [55] J. Williamson, *Mersenne Twister pseudorandom number generator*, GitHub repository: <https://github.com/jacobwilliams/mersenne-twister-fortran>.
- [56] S. K. Park and K. W. Miller, *Random number generators: good ones are hard to find*, Commun. ACM **31**(10), 1192–1201 (1988), doi:[10.1145/63039.63042](https://doi.org/10.1145/63039.63042).
- [57] M. Olagnon, *Orderpack 2.0 – unconditional, unique, and partial ranking, sorting, and permutation downloadable fortran 90 source code*, <http://www.fortran-2000.com/rank/>.
- [58] C. Cadiou, *Fortran-parallel-sort: A fortran library to perform parallel sorts*, GitHub repository: <https://github.com/cphyc/Fortran-parallel-sort>.
- [59] T. Nishimatsu, *Quick sort in Fortran*, GitHub gist: <https://gist.github.com/t-nissie/479f0f16966925fa29ea>.
- [60] *Fortran Package Manager*, GitHub repository: <https://github.com/fortran-lang/fpm>.
- [61] H. H. Rosenbrock, *An automatic method for finding the greatest or least value of a function*, The Computer Journal **3**(3), 175 (1960), doi:[10.1093/comjnl/3.3.175](https://doi.org/10.1093/comjnl/3.3.175), <https://academic.oup.com/comjnl/article-pdf/3/3/175/988633/030175.pdf>.
- [62] R. L. A., *Systems of extremal control*, Nauka (1974).
- [63] F. Hoffmeister and T. Bäck, *Genetic algorithms and evolution strategies: Similarities and differences*, In H.-P. Schwefel and R. Männer, eds., *Parallel Problem Solving from Nature*, pp. 455–469. Springer Berlin Heidelberg, Berlin, Heidelberg, ISBN 978-3-540-70652-6 (1991).
- [64] H. Mühlenbein, M. Schomisch and J. Born, *The parallel genetic algorithm as function optimizer*, Parallel Computing **17**(6), 619 (1991), doi:[https://doi.org/10.1016/S0167-8191\(05\)80052-3](https://doi.org/10.1016/S0167-8191(05)80052-3).
- [65] Z. Michaliwicz, *Genetic Algorithms + Data Structures = Evolution Programs*, Springer Verlag (1996).
- [66] D. M. Himmelblau, *Applied Nonlinear Programming*, McGraw-Hill (2007).

- [67] C. Gross, O. Lebedev and T. Toma, *Cancellation Mechanism for Dark-Matter–Nucleon Interaction*, Phys. Rev. Lett. **119**(19), 191801 (2017), doi:[10.1103/PhysRevLett.119.191801](https://doi.org/10.1103/PhysRevLett.119.191801), [1708.02253](https://arxiv.org/abs/1708.02253).
- [68] T. Biekötter, P. Gabriel, M. O. Olea-Romacho and R. Santos, *Direct detection of pseudo-Nambu-Goldstone dark matter in a two Higgs doublet plus singlet extension of the SM*, JHEP **10**, 126 (2022), doi:[10.1007/JHEP10\(2022\)126](https://doi.org/10.1007/JHEP10(2022)126), [2207.04973](https://arxiv.org/abs/2207.04973).
- [69] A. Pich and P. Tuzon, *Yukawa Alignment in the Two-Higgs-Doublet Model*, Phys. Rev. D **80**, 091702 (2009), doi:[10.1103/PhysRevD.80.091702](https://doi.org/10.1103/PhysRevD.80.091702), [0908.1554](https://arxiv.org/abs/0908.1554).
- [70] A. Djouadi, J. Kalinowski and M. Spira, *HDECAY: A Program for Higgs boson decays in the standard model and its supersymmetric extension*, Comput. Phys. Commun. **108**, 56 (1998), doi:[10.1016/S0010-4655\(97\)00123-9](https://doi.org/10.1016/S0010-4655(97)00123-9), [hep-ph/9704448](https://arxiv.org/abs/hep-ph/9704448).
- [71] M. Muhlleitner, M. O. P. Sampaio, R. Santos and J. Wittbrodt, *The N2HDM under Theoretical and Experimental Scrutiny*, JHEP **03**, 094 (2017), doi:[10.1007/JHEP03\(2017\)094](https://doi.org/10.1007/JHEP03(2017)094), [1612.01309](https://arxiv.org/abs/1612.01309).
- [72] P. Bechtle, O. Brein, S. Heinemeyer, G. Weiglein and K. E. Williams, *HiggsBounds: Confronting Arbitrary Higgs Sectors with Exclusion Bounds from LEP and the Tevatron*, Comput. Phys. Commun. **181**, 138 (2010), doi:[10.1016/j.cpc.2009.09.003](https://doi.org/10.1016/j.cpc.2009.09.003), [0811.4169](https://arxiv.org/abs/0811.4169).
- [73] P. Bechtle, S. Heinemeyer, O. Stål, T. Stefaniak and G. Weiglein, *HiggsSignals: Confronting arbitrary Higgs sectors with measurements at the Tevatron and the LHC*, Eur. Phys. J. C **74**(2), 2711 (2014), doi:[10.1140/epjc/s10052-013-2711-4](https://doi.org/10.1140/epjc/s10052-013-2711-4), [1305.1933](https://arxiv.org/abs/1305.1933).
- [74] H. Bahl, T. Biekötter, S. Heinemeyer, C. Li, S. Paasch, G. Weiglein and J. Wittbrodt, *HiggsTools: BSM scalar phenomenology with new versions of HiggsBounds and HiggsSignals*, Comput. Phys. Commun. **291**, 108803 (2023), doi:[10.1016/j.cpc.2023.108803](https://doi.org/10.1016/j.cpc.2023.108803), [2210.09332](https://arxiv.org/abs/2210.09332).
- [75] H. Bahl, T. Biekötter, S. Heinemeyer, K. Radchenko and G. Weiglein, *HiggsTools for LHC Run-3 and Beyond*, IFT-UAM/CSIC-25-072 (2025).
- [76] K. G. Klimenko, *On Necessary and Sufficient Conditions for Some Higgs Potentials to Be Bounded From Below*, Theor. Math. Phys. **62**, 58 (1985), doi:[10.1007/BF01034825](https://doi.org/10.1007/BF01034825).
- [77] S. Navas *et al.*, *Review of particle physics*, Phys. Rev. D **110**(3), 030001 (2024), doi:[10.1103/PhysRevD.110.030001](https://doi.org/10.1103/PhysRevD.110.030001).
- [78] Biekötter, Thomas, *A template fpm project for using HiggsTools in Fortran programs*, GitLab repository: <https://gitlab.com/thomas.biekoetter/fpmhtcaller>.
- [79] M. Hindmarsh, S. J. Huber, K. Rummukainen and D. J. Weir, *Gravitational waves from the sound of a first order phase transition*, Phys. Rev. Lett. **112**, 041301 (2014), doi:[10.1103/PhysRevLett.112.041301](https://doi.org/10.1103/PhysRevLett.112.041301), [1304.2433](https://arxiv.org/abs/1304.2433).
- [80] C. Caprini, R. Durrer and G. Servant, *The stochastic gravitational wave background from turbulence and magnetic fields generated by a first-order phase transition*, JCAP **12**, 024 (2009), doi:[10.1088/1475-7516/2009/12/024](https://doi.org/10.1088/1475-7516/2009/12/024), [0909.0622](https://arxiv.org/abs/0909.0622).
- [81] A. Kosowsky and M. S. Turner, *Gravitational radiation from colliding vacuum bubbles: envelope approximation to many bubble collisions*, Phys. Rev. D **47**, 4372 (1993), doi:[10.1103/PhysRevD.47.4372](https://doi.org/10.1103/PhysRevD.47.4372), [astro-ph/9211004](https://arxiv.org/abs/astro-ph/9211004).

- [82] C. Caprini *et al.*, *Detecting gravitational waves from cosmological phase transitions with LISA: an update*, JCAP **03**, 024 (2020), doi:[10.1088/1475-7516/2020/03/024](https://doi.org/10.1088/1475-7516/2020/03/024), [1910.13125](https://arxiv.org/abs/1910.13125).
- [83] J. Ellis, M. Lewicki and J. M. No, *Gravitational waves from first-order cosmological phase transitions: lifetime of the sound wave source*, JCAP **07**, 050 (2020), doi:[10.1088/1475-7516/2020/07/050](https://doi.org/10.1088/1475-7516/2020/07/050), [2003.07360](https://arxiv.org/abs/2003.07360).
- [84] C. Caprini, R. Jinno, M. Lewicki, E. Madge, M. Merchand, G. Nardini, M. Pieroni, A. Roper Pol and V. Vaskonen, *Gravitational waves from first-order phase transitions in LISA: reconstruction pipeline and physics interpretation*, JCAP **10**, 020 (2024), doi:[10.1088/1475-7516/2024/10/020](https://doi.org/10.1088/1475-7516/2024/10/020), [2403.03723](https://arxiv.org/abs/2403.03723).
- [85] C. Caprini, D. G. Figueroa, R. Flauger, G. Nardini, M. Peloso, M. Pieroni, A. Ricciardone and G. Tasinato, *Reconstructing the spectral shape of a stochastic gravitational wave background with LISA*, JCAP **11**, 017 (2019), doi:[10.1088/1475-7516/2019/11/017](https://doi.org/10.1088/1475-7516/2019/11/017), [1906.09244](https://arxiv.org/abs/1906.09244).
- [86] A. J. Farmer and E. S. Phinney, *The gravitational wave background from cosmological compact binaries*, Mon. Not. Roy. Astron. Soc. **346**, 1197 (2003), doi:[10.1111/j.1365-2966.2003.07176.x](https://doi.org/10.1111/j.1365-2966.2003.07176.x), [astro-ph/0304393](https://arxiv.org/abs/astro-ph/0304393).
- [87] P. A. Rosado, *Gravitational wave background from binary systems*, Phys. Rev. D **84**, 084004 (2011), doi:[10.1103/PhysRevD.84.084004](https://doi.org/10.1103/PhysRevD.84.084004), [1106.5795](https://arxiv.org/abs/1106.5795).
- [88] J. Ellis, M. Lewicki, M. Merchand, J. M. No and M. Zych, *The scalar singlet extension of the Standard Model: gravitational waves versus baryogenesis*, JHEP **01**, 093 (2023), doi:[10.1007/JHEP01\(2023\)093](https://doi.org/10.1007/JHEP01(2023)093), [2210.16305](https://arxiv.org/abs/2210.16305).
- [89] T. Biekötter, A. Dashko, M. Löschner and G. Weiglein, *Perturbative aspects of the electroweak phase transitions in the cxSM* , to be published (2025).
- [90] T. Biekötter, S. Heinemeyer, J. M. No, M. O. Olea-Romacho and G. Weiglein, *The trap in the early Universe: impact on the interplay between gravitational waves and LHC physics in the 2HDM*, JCAP **03**, 031 (2023), doi:[10.1088/1475-7516/2023/03/031](https://doi.org/10.1088/1475-7516/2023/03/031), [2208.14466](https://arxiv.org/abs/2208.14466).
- [91] P. Bittar, S. Roy and C. E. M. Wagner, *Self Consistent Thermal Resummation: A Case Study of the Phase Transition in 2HDM* (2025), [2504.02024](https://arxiv.org/abs/2504.02024).
- [92] T. Biekötter and M. O. Olea-Romacho, *Benchmarking a fading window: electroweak baryogenesis in the C2HDM, LHC constraints after Run 2 and prospects for LISA* (2025), [2505.09670](https://arxiv.org/abs/2505.09670).
- [93] T. Krajewski, M. Lewicki and M. Zych, *Bubble-wall velocity in local thermal equilibrium: hydrodynamical simulations vs analytical treatment*, JHEP **05**, 011 (2024), doi:[10.1007/JHEP05\(2024\)011](https://doi.org/10.1007/JHEP05(2024)011), [2402.15408](https://arxiv.org/abs/2402.15408).